AMENDATORY SECTION (Amending WSR 05-12-119, filed 5/31/05, effective 7/1/05)

WAC 222-30-020 *Harvest unit planning and design. (1) **Preapplication consultation and harvest-related forest practices hydraulic projects.**

(a) Landowners contemplating forest practices hydraulic projects related to timber harvest are encouraged to consult with the department and the department of fish and wildlife prior to submitting an application to help ensure that project plans and specifications meet fish protection standards.

(b) Harvest-related forest practices hydraulic projects include, but are not limited to, projects associated with:

(i) Felling and bucking (WAC 222-30-050);

(ii) Cable yarding (WAC 222-30-060); and

(iii) Large woody material removal or repositioning (WAC 222-30-062).

(2) **Logging system.** The logging system, including forest biomass removal operations, should be appropriate for the terrain, soils, and timber type so that yarding or skidding can be economically accomplished and achieve the ecological goals of WAC 222-30-010 (2), (3) and (4) in compliance with these rules.

*((~~(2)~~)) (3) **Landing locations.** Locate landings to prevent damage to public resources. Avoid excessive excavation and filling.

*((~~(3)~~)) (4) **Western Washington riparian management zones.** (See WAC 222-30-021 and 222-30-023.)

*((~~(4)~~)) (5) **Eastern Washington riparian management zones.** (See WAC 222-30-022 and 222-30-023.)

*((~~(5)~~)) (6) **Riparian leave tree areas.** (See WAC 222-30-021, 222-30-022, and 222-30-023.)

*((~~(6)~~)) (7) **Forested wetlands.** Within the wetland, unless otherwise approved in writing by the department, harvest methods shall be limited to low impact harvest or cable systems. Where feasible, at least one end of the log shall be suspended during yarding.

(a) When forested wetlands are included within the harvest area, landowners are encouraged to leave a portion (((~~30 to 70%~~)) thirty to seventy percent) of the wildlife reserve tree requirement for the harvest area within a wetland. In order to retain undisturbed habitat within forested wetlands, these trees should be left in clumps. Leave tree areas should be clumped adjacent to streams, riparian management zones, or wetland management zones where possible and they exist within forested wetlands. Green recruitment trees should be representative of the size and species found within the wetland. Leave nonmerchantable trees standing where feasible.

(b) If a RMZ or WMZ lies within a forested wetland, the leave tree requirement associated with those areas may be counted toward the percentages in (a) of this subsection.

(c) Where riparian associated wetlands are present in the outer zone of a RMZ, trees may be left in the zone to maximize wetland function. See WAC 222-30-021 *(1)(c)(ii).

(d) If the conditions described in (a) and (b) of this subsection are met, the distribution requirements for wildlife reserve trees and green recruitment trees (subsection (11)(e) of this section) are modified as follows: For purposes of distribution, no point within the harvest unit shall be more than ((~~1000~~)) one thousand feet from a wildlife reserve tree and green recruitment tree retention area.

(e) Approximate determination of the boundaries of forested wetlands greater than ((~~3~~)) three acres shall be required. Approximate boundaries and areas shall be deemed to be sufficient for harvest operations.

(f) The department shall consult with the department of fish and wildlife and affected Indian tribes about site specific impacts of forest practices on wetland-sensitive species in forested wetlands.

*((~~(7)~~)) (8) **Wetland management zones (WMZ).** These zones shall apply to Type A and B Wetlands, as indicated in (a) of this subsection, and shall be measured horizontally from the wetland edge or the point where the nonforested wetland becomes a forested wetland, as determined by the method described in the board manual section 8, and shall be of an average width as described in (a) of this subsection. These zones shall not be less than the minimum nor more than the maximum widths described in (a) of this subsection. When these zones overlap a riparian management zone the requirement which best protects public resources shall apply.

*(a) Wetland management zones (WMZ) shall have variable widths based on the size of the wetland and the wetland type, described as follows:

Wetland Management Zones

Wetland Type	Acres of Nonforested Wetland*	Maximum WMZ Width	Average WMZ Width	Minimum WMZ Width
A (including bogs)	Greater than 5	200 feet	100 feet	50 feet
A (including bogs)	0.5 to 5	100 feet	50 feet	25 feet
A (bogs only)	0.25 to 0.5	100 feet	50 feet	25 feet
B	Greater than 5	100 feet	50 feet	25 feet
B	0.5 to 5			25 feet
B	0.25 to 0.5	No WMZ required	No WMZ required	

* For bogs, both forested and nonforested acres are included.

(b) Within the WMZ, leave a total of ((~~75~~)) seventy-five trees per acre of WMZ greater than ((~~6~~)) six inches dbh in western Washington and greater than ((~~4~~)) four inches dbh in eastern Washington, ((~~25~~)) twenty-five of which shall be greater than ((~~12~~)) twelve inches dbh including ((~~5~~)) five trees greater than ((~~20~~)) twenty inches dbh, where they exist. Leave trees shall be

representative of the species found within the WMZ.

(c) Retain wildlife reserve trees where feasible. Type 1 and 3 wildlife reserve trees may be counted among, and need not exceed, the trees required in (b) of this subsection. Leave all cull logs on site.

(d) Partial-cutting or removal of groups of trees is acceptable within the WMZ. The maximum width of openings created by harvesting within the WMZ shall not exceed ((~~100~~)) one hundred feet as measured parallel to the wetland edge. Openings within WMZs shall be no closer than ((~~200~~)) two hundred feet. Landowners are encouraged to concentrate leave trees within the WMZ to the wetland edge.

*(e) Tractors, wheeled skidders, or other ground based harvesting systems shall not be used within the minimum WMZ width without written approval of the department.

*(f) When ((~~10%~~)) ten percent or more of a harvest unit lies within a wetland management zone and either the harvest unit is a clearcut of ((~~30~~)) thirty acres or less or the harvest unit is a partial cut of ((~~80~~)) eighty acres or less, leave not less than ((~~50%~~)) fifty percent of the trees required in (b) of this subsection.

*((~~(8)~~)) (9) **Type A or B Wetlands.** Within the boundaries of Type A or B Wetlands the following shall apply:

(a) Individual trees or forested wetland areas less than 0.5 acre in size may occur. These trees have a high habitat value to the nonforested wetland. Leave individual trees or forested wetlands less than 0.5 acre. These trees may be counted toward the WMZ requirements.

(b) Harvest of upland areas or forested wetlands which are surrounded by Type A or B Wetlands must be conducted in accordance with a plan, approved in writing by the department.

(c) No timber shall be felled into or cable yarded across Type A or B Wetlands without written approval of the department.

(d) Harvest shall not be allowed within a Type A Wetland which meets the definition of a bog.

((~~(9)~~)) (10) **Future productivity.** Harvesting shall leave the land in a condition conducive to future timber production except:

(a) To the degree required for riparian management zones; or

(b) Where the lands are being converted to another use or classified urban lands as specified in WAC 222-34-050.

((~~(10)~~)) (11) **Wildlife habitat.** This subsection is designed to encourage timber harvest practices that would protect wildlife habitats, provided, that such action shall not unreasonably restrict landowners action without compensation.

(a) The applicant should make every reasonable effort to cooperate with the department of fish and wildlife to identify critical habitats (state) as defined by the board. Where these habitats are known to the applicant, they shall be identified in the application or notification.

(b) Harvesting methods and patterns in established big game winter ranges should be designed to ensure adequate access routes and escape cover where practical.

(i) Where practical, cutting units should be designed to conform with topographical features.

(ii) Where practical on established big game winter ranges, cutting units should be dispersed over the area to provide cover, access for wildlife, and to increase edge effect.

((~~(11)~~)) (12) **Wildlife reserve tree management.** In areas where leaving wildlife reserve trees under this section will not create a significant fire hazard, or significant hazard to overhead power lines and operations that are proposed in the vicinity of wildlife reserve trees will not create a significant safety or residential hazard nor conflict with achieving conformance with the limitation of or performance with the provisions of chapter 76.04 RCW (snag falling law) and chapter 49.17 RCW (safety), wildlife reserve trees will be left to protect habitat for cavity nesting wildlife in accordance with the following:

(a) For the purposes of this subsection the following defines eastern and western Washington boundaries for wildlife reserve tree management. Beginning at the International Border and Okanogan National Forest boundary at the N1/4 corner Section 6, T. 40N, R. 24E., W.M., south and west along the Pasayten Wilderness boundary to the west line of Section 30, T. 37N, R. 19E.,

Thence south on range line between R. 18E. and R. 19E., to the Lake Chelan-Sawtooth Wilderness at Section 31, T. 35N, R. 19E.,

Thence south and east along the eastern wilderness boundary of Lake Chelan-Sawtooth Wilderness to the west line of Section 18, T. 31N, R. 19E. on the north shore of Lake Chelan,

Thence south on the range line between R. 18E. and R. 19E. to the SE corner of T. 28N, R. 18E.,

Thence west on the township line between T. 27N, and T. 28N to the NW corner of T. 27N, R. 17E.,

Thence south on range line between R. 16E. and R. 17E. to the Alpine Lakes Wilderness at Section 31, T. 26N, R. 17E.,

Thence south along the eastern wilderness boundary to the west line of Section 6, T. 22N, R. 17E.,

Thence south on range line between R. 16E. and R. 17E. to the SE corner of T. 22N, R. 16E.,

Thence west along township line between T. 21N, and T. 22N to the NW corner of T. 21N, R. 15E.,

Thence south along range line between R. 14E. and R. 15E. to the SW corner of T. 20N, R. 15E.,

Thence east along township line between T. 19N, and T. 20N to the SW corner of T. 20N, R. 16E.,

Thence south along range line between R. 15E. and R. 16E. to the SW corner of T. 18N, R. 16E.,

Thence west along township line between T. 17N, and T. 18N to the SE corner of T. 18N, R. 14E.,

Thence south along range line between T. 14E. and R. 15E. to the SW corner of T. 14N, R. 15E.,

Thence south and west along Wenatchee National Forest boundary to the NW corner of T. 12N, R. 14E.,

Thence south along range line between R. 13E. and R. 14E. to the SE corner of T. 10N, R. 13E.,

Thence west along township line between T. 9N, and T. 10N to

the NW corner of T. 9N, R. 12E.,

Thence south along range line between R. 11E. and R. 12E. to the SE corner of T. 8N, R. 11E.,

Thence west along township line between T. 7N, and T. 8N to the Gifford Pinchot National Forest boundary,

Thence south along forest boundary to the SE corner of Section 33, T. 7N, R. 11E.,

Thence west along township line between T. 6N, and T. 7N to the SE corner of T. 7N, R. 9E.,

Thence south along Skamania-Klickitat County line to Oregon-Washington.

(b) In western Washington, for each acre harvested ((~~3~~)) three wildlife reserve trees, ((~~2~~)) two green recruitment trees, and ((~~2~~)) two down logs shall be left. In eastern Washington for each acre harvested ((~~2~~)) two wildlife reserve trees, ((~~2~~)) two green recruitment trees, and ((~~2~~)) two down logs shall be left. Type 1 wildlife reserve trees may be counted, at the landowner's option, either as a wildlife reserve tree or as a green recruitment tree. If adequate wildlife reserve trees are not available, no additional green recruitment trees will be required as substitutes. Landowners shall not under any circumstances be required to leave more than ((~~2~~)) two green recruitment trees per acre for the purpose of wildlife reserve tree recruitment, or be required to leave Type 3 or 4 wildlife reserve trees.

(c) In western Washington, only those wildlife reserve trees ((~~10~~)) ten or more feet in height and ((~~12~~)) twelve or more inches dbh shall be counted toward wildlife reserve tree retention requirements. In eastern Washington, only those wildlife reserve trees ((~~10~~)) ten or more feet in height and ((~~10~~)) ten or more inches dbh shall be counted toward wildlife reserve tree retention requirements. Green recruitment trees, ((~~10~~)) ten or more inches dbh and ((~~30~~)) thirty or more feet in height and with at least ((~~1/3~~)) one-third of their height in live crown, left standing after harvest may be counted toward green recruitment tree requirements. Green recruitment trees and/or wildlife reserve trees left to meet other requirements of the rules or those left voluntarily by the landowner shall be counted toward satisfying the requirements of this section. Large, live defective trees with broken tops, cavities, and other severe defects are preferred as green recruitment trees. Only down logs with a small end diameter greater than or equal to ((~~12~~)) twelve inches and a length greater than or equal to ((~~20~~)) twenty feet or equivalent volume shall be counted under (a) of this subsection. Large cull logs are preferred as down logs.

(d) In the areas where wildlife reserve trees are left, the largest diameter wildlife reserve trees shall be retained to meet the specific needs of cavity nesters. Where the opportunity exists, larger trees with numerous cavities should be retained and count as recruitment trees.

(e) In order to facilitate safe and efficient harvesting operations, wildlife reserve trees and recruitment trees may be left in clumps. For purposes of distribution, no point within the harvest unit shall be more than ((~~800~~)) eight hundred feet from a

wildlife reserve tree or green recruitment tree retention area. Subject to this distribution requirement, the location of these retention areas and the selection of recruitment trees shall be at the landowner's discretion. Closer spacing of retention areas through voluntary action of the landowner is encouraged. Wildlife reserve tree and green recruitment tree retention areas may include, but are not limited to, riparian management zones, riparian leave tree areas, other regulatory leave areas, or voluntary leave areas that contain wildlife reserve trees and/or green recruitment trees.

(f) In order to provide for safety, landowners may remove any Type 3 or 4 wildlife reserve tree, which poses a threat to humans working, recreating, or residing within the hazard area of that tree. In order to provide for fire safety, the distribution of wildlife reserve tree retention areas, described in (e) of this subsection, may be modified as necessary based on a wildlife reserve tree management plan proposed by the landowner and approved by the department.

*((~~(12)~~)) (13) **Channel migration zones.** No harvest, construction or salvage will be permitted within the boundaries of a channel migration zone except for the construction and maintenance of road crossings in accordance with applicable rules and the creation and use of yarding corridors consistent with WAC 222-24-020(6), 222-30-060(1), and 222-30-045(2)((~~, and chapter 220-110 WAC (Hydraulic code rules)~~)).

((~~(13)~~)) (14) **Bankfull width.** No harvest or construction will be permitted within the bankfull width of any Type S or F Water or any buffered length of Type Np Water, except for the construction and maintenance of road crossings in accordance with applicable rules and creation and use of yarding corridors consistent with WAC 222-30-020 *((~~(5)(a),~~)) (6) and 222-24-060(1)((~~, and chapter 220-110 WAC (Hydraulic code rules)~~)). No salvage may take place within the bankfull width of any typed water (see WAC 222-30-045).

AMENDATORY SECTION (Amending WSR 12-05-083, filed 2/17/12, effective 3/19/12)

WAC 222-30-021 *Western Washington riparian management zones. These rules apply to all typed waters on forest land in western Washington, except as provided in WAC 222-30-023. RMZs are measured horizontally from the outer edge of the bankfull width or channel migration zone, whichever is greater, and extend to the limits as described in this section. See board manual section 7 for riparian design and layout guidelines.

*(1) **Western Washington RMZs for Type S and F Waters** have three zones: The core zone is nearest to the water, the inner zone is the middle zone, and the outer zone is furthest from the water. (See definitions in WAC 222-16-010.) RMZ dimensions vary depending

on the site class of the land, the management harvest option, and the bankfull width of the stream. See tables for management options 1 and 2 below.

None of the limitations on harvest in each of the three zones listed below will preclude or limit the construction and maintenance of roads for the purpose of crossing streams in WAC 222-24-030 and 222-24-050, or the creation and use of yarding corridors in WAC 222-30-060(1).

The shade requirements in WAC 222-30-040 must be met regardless of harvest opportunities provided in the inner zone RMZ rules. See board manual section 1.

(a) **Core zones.** No timber harvest or construction is allowed in the core zone except operations related to forest roads as detailed in subsection (1) of this section. Any trees cut for or damaged by yarding corridors in the core zone must be left on the site. Any trees cut as a result of road construction to cross a stream may be removed from the site, unless used as part of a large woody debris placement strategy or as needed to reach stand requirements.

(b) **Inner zones.** Forest practices in the inner zone must be conducted in such a way as to meet or exceed stand requirements to achieve the goal in WAC 222-30-010(2). The width of the inner zone is determined by site class, bankfull width, and management option. Timber harvest in this zone must be consistent with the stand requirements in order to reach the desired future condition targets.

"Stand requirement" means a number of trees per acre, the basal area and the proportion of conifer in the combined inner zone and adjacent core zone so that the growth of the trees would meet desired future conditions. The following table defines basal area targets when the stand is one hundred forty years old.

Site Class	Desired future condition target basal area per acre (at 140 years)
I	325 sq. ft.
II	325 sq. ft.
III	325 sq. ft.
IV	325 sq. ft.
V	325 sq. ft.

Growth modeling is necessary to calculate whether a particular stand meets stand requirement and is on a trajectory towards these desired future condition basal area target. The appropriate growth model will be based on stand characteristics and will include at a minimum, the following components: The number of trees by diameter class, the percent of conifer and hardwood, and the age of the stand. See board manual section 7.

(i) **Hardwood conversion in the inner zone.** When the existing stands in the combined core and inner zone do not meet stand requirements, no harvest is permitted in the inner zone, except in connection with hardwood conversion.

The landowner may elect to convert hardwood-dominated stands

in the **inner zone** to conifer-dominated stands. Harvesting and replanting shall be in accordance with the following limits:

Conversion activities in the **inner zone** of any harvest unit are only allowed where all of the following are present:

- Existing stands in the combined core and inner zone do not meet stand requirements (WAC 222-30-021 (1)(b));
- There are fewer than fifty-seven conifer trees per acre eight inches or larger dbh in the conversion area;
- There are fewer than one hundred conifer trees per acre larger than four inches dbh in the conversion area;
- There is evidence (such as conifer stumps, historical photos, or a conifer understory) that the conversion area can be successfully reforested with conifer and support the development of conifer stands;
- The landowner owns five hundred feet upstream and five hundred feet downstream of the harvest unit;
- The core and inner zones contain no stream adjacent parallel roads;
- Riparian areas contiguous to the proposed harvest unit are owned by the landowner proposing to conduct the conversion activities, and meet shade requirements of WAC 222-30-040 or have a seventy-five foot buffer with trees at least forty feet tall on both sides of the stream for five hundred feet upstream and five hundred feet downstream of the proposed harvest unit (or the length of the stream, if less);
- If the landowner has previously converted hardwood-dominated stands, then post-harvest treatments must have been performed to the satisfaction of the department.

In addition to the conditions set forth above, permitted conversion activities in the **inner zone** of any harvest unit are limited by the following:

- Each continuous conversion area is not more than five hundred feet in length; two conversion areas will be considered "continuous" unless the no-harvest area separating the two conversion areas is at least half the length of the larger of the two conversion areas.
- Type S and F (Type 1, 2, or 3) Water: Up to fifty percent of the inner zone area of the harvest unit on one side of the stream may be converted provided that:
  - The landowner owns the opposite side of the stream and the landowner's riparian area on the opposite bank meets the shade requirements of WAC 222-30-040 or has a seventy-five foot buffer of trees at least forty feet tall or:
  - The landowner does not own land on the opposite side of the stream but the riparian area on the opposite bank meets the shade requirements of WAC 222-30-040 or has a seventy-five foot buffer of trees at least forty feet tall.
- Not more than twenty-five percent of the inner zone of the harvest unit on both sides of a Type S or F Water may be converted if the landowner owns both sides.

Where conversion is allowed in the **inner zone**, trees within the conversion area may be harvested except that:

- Conifer trees larger than twenty inches dbh shall not be harvested;
- Not more than ten percent of the conifer stems greater than eight inches dbh, exclusive of the conifer noted above, within the conversion area may be harvested; and
- The landowner must exercise reasonable care in the conduct of harvest activities to minimize damage to all residual conifer trees within the conversion area including conifer trees less than eight inches dbh.

Following harvest in conversion areas, the landowner must:

- Reforest the conversion area with **conifer** tree species suitable to the site in accordance with the requirements of WAC 222-34-010; and
- Conduct post-harvest treatment of the site until the conifer trees necessary to meet acceptable stocking levels in WAC 222-34-010(2) have crowns above the brush or until the conversion area contains a minimum of one hundred fifty conifer trees greater than eight inches dbh per acre.
- Notify the department in writing within three years of the approval of the forest practices application for hardwood conversion, if the hardwood conversion has been completed.

Tracking hardwood conversion. The purpose of tracking hardwood conversion is to determine if hardwood conversion is resulting in adequate enhancement of riparian functions toward the desired future condition while minimizing the short term impacts on functions. The department will use existing or updated data bases developed in cooperation with the Washington Hardwoods Commission to identify watershed administrative units (WAUs) with a high percentage of hardwood-dominated riparian areas and, thus have the potential for excessive hardwood conversion under these rules. The department will track the rate of conversion of hardwoods in the riparian zone: (1) Through the application process on an annual basis; and (2) at a WAU scale on a biennial basis as per WAC 222-30-120 through the adaptive management process which will develop thresholds of impact for hardwood conversion at the watershed scale.

(ii) **Harvest options.**

(A) No inner zone management. When the existing stands in the combined core and inner zone do not meet stand requirements, no harvest is permitted in the inner zone. When no harvest is permitted in the inner zone or the landowner chooses not to enter the inner zone, the width of core, inner and outer zones are as provided in the following table:

No inner zone management RMZ widths for western Washington

Site Class	RMZ width	Core zone width (measured from outer edge of bankfull width or outer edge of CMZ of water)	Inner zone width (measured from outer edge of core zone)		Outer zone width (measured from outer edge of inner zone)	
			stream width ≤10'	stream width >10'	stream width ≤10'	stream width >10'
I	200'	50'	83'	100'	67'	50'

Site Class	RMZ width	Core zone width (measured from outer edge of bankfull width or outer edge of CMZ of water)	Inner zone width (measured from outer edge of core zone)		Outer zone width (measured from outer edge of inner zone)	
			stream width ≤10'	stream width >10'	stream width ≤10'	stream width >10'
II	170'	50'	63'	78'	57'	42'
III	140'	50'	43'	55'	47'	35'
IV	110'	50'	23'	33'	37'	27'
V	90'	50'	10'	18'	30'	22'

(B) Inner zone management. If trees can be harvested and removed from the inner zone because of surplus basal area consistent with the stand requirement, the harvest and removal of the trees must be undertaken consistent with one of two options:

(I) **Option 1. Thinning from below.** The objective of thinning is to distribute stand requirement trees in such a way as to shorten the time required to meet large wood, fish habitat and water quality needs. This is achieved by increasing the potential for leave trees to grow larger than they otherwise would without thinning. Thinning harvest under option 1 must comply with the following:

- Residual trees left in the combined core and inner zones must meet stand requirements necessary to be on a trajectory to desired future condition. See board manual section 7 for guidelines.
- Thinning must be from below, meaning the smallest dbh trees are selected for harvest first, then progressing to successively larger diameters.
- Thinning cannot decrease the proportion of conifer in the stand.
- Shade retention to meet the shade rule must be confirmed by the landowner for any harvest inside of seventy-five feet from the outer edge of bankfull width or outer edge of CMZ, whichever is greater.
- The number of residual conifer trees per acre in the inner zone will equal or exceed fifty-seven.

Option 1. Thinning from below.

Site class	RMZ width	Core zone width (measured from outer edge of bankfull width or outer edge of CMZ of water)	Inner zone width (measured from outer edge of core zone)		Outer zone width (measured from outer edge of inner zone)	
			stream width ≤10'	stream width >10'	stream width ≤10'	stream width >10'
I	200'	50'	83'	100'	67'	50'
II	170'	50'	63'	78'	57'	42'
III	140'	50'	43'	55'	47'	35'
IV	110'	50'	23'	33'	37'	27'
V	90'	50'	10'	18'	30'	22'

(II) **Option 2. Leaving trees closest to the water.**

Management option 2 applies only to riparian management zones for site class I, II, and III on streams that are less than or equal to ten feet wide and RMZs in site class I and II for streams greater than ten feet wide. Harvest must comply with the following:

- Harvest is not permitted within thirty feet of the core zone for streams less than or equal to ten feet wide and harvest is not permitted within fifty feet of the core zone for streams greater than ten feet wide;
- Residual leave trees in the combined core and inner zone must meet stand requirements necessary to be on a trajectory to desired future condition. See board manual section 7 for calculating stand requirements;
- A minimum of twenty conifers per acre, with a minimum twelve inch dbh, will be retained in any portion of the inner zone where even-age harvest occurs. These riparian leave trees will be counted towards meeting applicable stand requirements. The number of riparian leave trees cannot be reduced below twenty for any reason.
- Trees are selected for harvest starting from the outer most portion of the inner zone first then progressively closer to the stream.
- If (b)(ii)(B)(II) of this subsection results in surplus basal area per the stand requirement, the landowner may take credit for the surplus by harvesting additional riparian leave trees required to be left in the adjacent outer zone on a basal area-for-basal area basis. The number of leave trees in the outer zone can be reduced only to a minimum of ten trees per acre.

Option 2. Leaving trees closest to water.

Site class	RMZ width	Core zone width (measured from outer edge of bankfull width or outer edge of CMZ of water)	Inner zone width				Outer zone width (measured from outer edge of inner zone)	
			stream width ≤10'	stream width ≤10'	stream width >10'	stream width >10'	stream width ≤10'	stream width >10'
				minimum floor distance		minimum floor distance		
			(measured from outer edge of core zone)	(measured from outer edge of core zone)	(measured from outer edge of core zone)	(measured from outer edge of core zone)		
I	200'	50'	84'	30'	84'	50'	66'	66'
II	170'	50'	64'	30'	70'	50'	56'	50'
III	140'	50'	44'	30'	**	**	46'	**

** Option 2 for site class III on streams >10' is not permitted because of the minimum floor (100') constraint.

(iii) **Where the basal area components of the stand requirement cannot be met** within the sum of the areas in the inner and core zone due to the presence of a stream-adjacent parallel road in the inner or core zone, a determination must be made of the approximate basal area that would have been present in the inner and core zones

if the road was not occupying space in the core or inner zone and the shortfall in the basal area component of the stand requirement. See definition of "stream-adjacent parallel road" in WAC 222-16-010.

(A) Trees containing basal area equal to the amount determined in (b)(iii) of this subsection will be left elsewhere in the inner or outer zone, or if the zones contain insufficient riparian leave trees, substitute riparian leave trees will be left within the RMZ width of other Type S or F Waters in the same unit or along Type Np or Ns Waters in the same unit in addition to all other RMZ requirements on those same Type S, F, Np or Ns Waters.

(B) When the stream-adjacent road basal area calculated in (b)(iii) of this subsection results in an excess in basal area (above stand requirement) then the landowner may receive credit for such excess which can be applied on a basal area-by-basal area basis against the landowner's obligation to leave trees in the outer zone of the RMZ of such stream or other waters within the same unit, provided that the number of trees per acre in the outer zone is not reduced to less than ten trees per acre.

(C) When the basal area requirement cannot be met, as explained in (b)(iii) of this subsection, the shortfall may be reduced through the implementation of an acceptable large woody debris placement plan. See board manual section 26 for guidelines.

(iv) If a harvest operation includes both yarding and harvest activities within the RMZ, all calculations of basal area for stand requirements will be determined as if the yarding corridors were constructed prior to any other harvest activities. If trees cut or damaged by yarding are taken from excess basal area, these trees may be removed from the inner zone. Trees cut or damaged by yarding in a unit which does not meet the basal area target of the stand requirements cannot be removed from the inner zone. Any trees cut or damaged by yarding in the core zone may not be removed.

(c) **Outer zones.** Timber harvest in the outer zone must leave twenty riparian leave trees per acre after harvest. **"Outer zone riparian leave trees"** are trees that must be left after harvest in the outer zone in western Washington. Riparian leave trees must be left uncut throughout all future harvests:

Outer zone riparian leave tree requirements

Application	Leave tree spacing	Tree species	Minimum dbh required
Outer zone	Dispersed	Conifer	12" dbh or greater
Outer zone	Clumped	Conifer	12" dbh or greater
Protection of sensitive features	Clumped	Trees representative of the overstory including both hardwood and conifer	8" dbh or greater

The twenty riparian leave trees to be left can be reduced in number under the circumstances delineated in (c)(iv) of this subsection. The riparian leave trees must be left on the landscape

according to one of the following two strategies. A third strategy is available to landowners who agree to a LWD placement plan.

(i) **Dispersal strategy.** Riparian leave trees, which means conifer species with a diameter measured at breast height (dbh) of twelve inches or greater, must be left dispersed approximately evenly throughout the outer zone. If riparian leave trees of twelve inches dbh or greater are not available, then the next largest conifers must be left. If conifers are not present, riparian leave trees must be left according to the clumping strategy in ((~~subsection~~)) (c)(ii) ((~~below~~)) of this subsection.

(ii) **Clumping strategy.** Riparian leave trees must be left clumped in the following way:

(A) Clump trees in or around one or more of the following **sensitive features** to the extent available within the outer zone. When clumping around sensitive features, riparian leave trees must be eight inches dbh or greater and representative of the overstory canopy trees in or around the sensitive feature and may include both hardwood and conifer species. Sensitive features are:

(I) Seeps and springs;

(II) Forested wetlands;

(III) Topographic locations (and orientation) from which leave trees currently on the site will be delivered to the water;

(IV) Areas where riparian leave trees may provide windthrow protection;

(V) Small unstable, or potentially unstable, slopes not of sufficient area to be detected by other site evaluations. See WAC 222-16-050 (1)(d).

(VI) Archaeological sites or historic archaeological resources as defined in RCW 27.53.030;

(VII) Historic sites eligible for listing on the National Register of Historic Places or the Washington Heritage Register as determined by the Washington state department of archaeology and historic preservation. See WAC 222-16-050 (1)(f); or

(VIII) Sites containing evidence of Native American cairns, graves or glyptic records as provided for in chapters 27.44 and 27.53 RCW. See WAC 222-16-050 (1)(f).

(B) If sensitive features are not present, then clumps must be well distributed throughout the outer zone and the leave trees must be of conifer species with a dbh of twelve inches or greater. When placing clumps, the applicant will consider operational and biological concerns. Tree counts must be satisfied regardless of the presence of stream-adjacent parallel roads in the outer zone.

(iii) **Large woody debris in-channel placement strategy.**

(A) In order to reduce the number of required outer zone trees, a landowner may design a LWD placement plan ((~~in cooperation with the department of fish and wildlife~~)) for department approval prior to submitting a forest practices application. The plan must be consistent with guidelines in board manual sections 5 and 26. ((~~The landowner may reduce the number of trees required to be left in the outer zone to the extent provided in the approved LWD placement plan.~~)) Landowners are encouraged to consult with the department and the department of fish and wildlife while designing

the plan and prior to submitting a forest practices application.

(B) Reduction of trees in the outer zone must not go below a minimum of ten trees per acre.

(C) If this strategy is chosen, the approved plan must be included in a complete forest practices application ((~~must include a copy of the WDFW approved hydraulics project approval (HPA) permit~~)).

(iv) **Twenty riparian leave trees must be left after harvest** with the exception of the following:

(A) If a landowner agrees to implement a placement strategy, see (iii) of this subsection.

(B) If trees are left in an associated channel migration zone, the landowner may reduce the number of trees required to be left according to the following:

(I) Offsets will be measured on a basal area-for-basal area basis.

(II) Conifer in a CMZ equal to or greater than six inches dbh will offset conifer in the outer zone at a one-to-one ratio.

(III) Hardwood in a CMZ equal to or greater than ten inches dbh will offset hardwood in the outer zone at a one-to-one ratio.

(IV) Hardwood in a CMZ equal to or greater than ten inches dbh will offset conifer in the outer zone at a three-to-one ratio.

*(2) **Western Washington protection for Type Np and Ns Waters.**

(a) An **equipment limitation zone** is a thirty-foot wide zone measured horizontally from the outer edge of the bankfull width of a Type Np or Ns Water where equipment use and other forest practices that are specifically limited by these rules. It applies to all perennial and seasonal streams.

(i) On-site mitigation is required if any of the following activities exposes the soil on more than ten percent of the surface area of the zone:

(A) Ground based equipment;

(B) Skid trails;

(C) Stream crossings (other than existing roads); or

(D) Cabled logs that are partially suspended.

(ii) Mitigation must be designed to replace the equivalent of lost functions especially prevention of sediment delivery. Examples include water bars, grass seeding, mulching, etc.

(iii) Nothing in this subsection (2) reduces or eliminates the department's authority to prevent actual or potential material damage to public resources under WAC 222-46-030 or 222-46-040 or any related authority to condition forest practices notifications or applications.

(b) **Sensitive site and RMZs protection along Type Np Waters.** Forest practices must be conducted to protect Type Np RMZs and sensitive sites as detailed below:

(i) A fifty-foot, no-harvest buffer, measured horizontally from the outer edge of bankfull width, will be established along each side of the Type Np Water as follows:

Required no-harvest, 50-foot buffers on Type Np Waters.

Length of Type Np Water from the confluence of Type S or F Water	Length of 50' buffer required on Type Np Water (starting at the confluence of the Type Np and connecting water)
Greater than 1000'	500'
Greater than 300' but less than 1000'	Distance of the greater of 300' or 50% of the entire length of the Type Np Water
Less than or equal to 300'	The entire length of Type Np Water

(ii) No timber harvest is permitted in an area within fifty feet of the outer perimeter of a soil zone perennially saturated from a headwall seep.

(iii) No timber harvest is permitted in an area within fifty feet of the outer perimeter of a soil zone perennially saturated from a side-slope seep.

(iv) No timber harvest is permitted within a fifty-six foot radius buffer patch centered on the point of intersection of two or more Type Np Waters.

(v) No timber harvest is permitted within a fifty-six foot radius buffer patch centered on a headwater spring or, in the absence of a headwater spring, on a point at the upper most extent of a Type Np Water as defined in WAC 222-16-030(3) and 222-16-031.

(vi) No timber harvest is permitted within an alluvial fan.

(vii) At least fifty percent of a Type Np Waters' length must be protected by buffers on both sides of the stream (2-sided buffers). Buffered segments must be a minimum of one hundred feet in length. If an operating area is located more than five hundred feet upstream from the confluence of a Type S or F Water and the Type Np Water is more than one thousand feet in length, then buffer the Type Np Water according to the following table. If the percentage is not met by protecting sensitive sites listed in (b)(i) through (vii) of this subsection, then additional buffers are required on the Type Np Water to meet the requirements listed in the table.

Minimum percent of length of Type Np Waters to be buffered when more than 500 feet upstream from the confluence of a Type S or F Water

Total length of a Type Np Water upstream from the confluence of a Type S or F Water	Percent of length of Type Np Water that must be protected with a 50 foot no harvest buffer more than 500 feet upstream from the confluence of a Type S or F Water
1000 feet or less	Refer to table in this subsection (i) above
1001 - 1300 feet	19%

Total length of a Type Np Water upstream from the confluence of a Type S or F Water	Percent of length of Type Np Water that must be protected with a 50 foot no harvest buffer more than 500 feet upstream from the confluence of a Type S or F Water
1301 - 1600 feet	27%
1601 - 2000 feet	33%
2001 - 2500 feet	38%
2501 - 3500 feet	42%
3501 - 5000 feet	44%
Greater than 5000 feet	45%

The landowner must select the necessary priority areas for additional two-sided buffers according to the following priorities:

(A) Low gradient areas;

(B) Perennial water reaches of nonsedimentary rock with gradients greater than twenty percent in the tailed frog habitat range;

(C) Hyporheic and groundwater influence zones; and

(D) Areas downstream from other buffered areas.

Except for the construction and maintenance of road crossings and the creation and use of yarding corridors, no timber harvest will be allowed in the designated priority areas. Landowners must leave additional acres equal to the number of acres (including partial acres) occupied by an existing stream-adjacent parallel road within a designated priority area buffer.

(c) None of the limitations on harvest in or around Type Np Water RMZs or sensitive sites listed in (b) of this subsection will preclude or limit:

(i) The construction and maintenance of roads for the purpose of crossing streams in WAC 222-24-030 and 222-24-050.

(ii) The creation and use of yarding corridors in WAC 222-30-060(1).

To the extent reasonably practical, the operation will both avoid creating yarding corridors or road crossings through Type Np Water RMZ or sensitive sites and associated buffers, and avoid management activities which would result in soil compaction, the loss of protective vegetation or sedimentation in perennially moist areas.

Where yarding corridors or road crossings through Type Np Water RMZs or sensitive sites and their buffers cannot reasonably be avoided, the buffer area must be expanded to protect the sensitive site by an area equivalent to the disturbed area or by providing comparable functions through other management initiated efforts.

Landowners must leave additional acres equal to the number of acres (including partial acres) occupied by an existing stream-adjacent parallel road within a Type Np Water RMZs or sensitive site buffer.

AMENDATORY SECTION (Amending WSR 05-12-119, filed 5/31/05, effective 7/1/05)

WAC 222-30-022 *Eastern Washington riparian management zones. For eastside forests, riparian management is intended to provide stand conditions that vary over time. It is designed to mimic eastside disturbance regimes within a range that meets functional conditions and maintains general forest health. These desired future conditions are a reference point on the pathway to restoration of riparian functions, not an end point of riparian stand development. These rules apply to all typed waters on forest land in eastern Washington, except as provided in WAC 222-30-023. RMZs are measured horizontally from the outer edge of the bankfull width or channel migration zone, whichever is greater, and extend to the limits as described in the following section.

Eastern Washington RMZ for streams with bankfull width of less than or equal to 15 feet wide

Site Class	Total RMZ Width	Core Zone Width From outer edge of bankfull width or outer edge of CMZ, whichever is greater	Inner Zone Width	Outer Zone Width
I	130'	30'	45'	55'
II	110'	30'	45'	35'
III	90'	30'	45'	15'
IV	75'	30'	45'	0'
V	75'	30'	45'	0'

Eastern Washington RMZ for streams with bankfull width of greater than 15 feet wide

Site Class	Total RMZ Width	Core Zone Width From outer edge of bankfull width or outer edge of CMZ, whichever is greater	Inner Zone Width	Outer Zone Width
I	130'	30'	70'	30'
II	110'	30'	70'	10'
III	100'	30'	70'	0'
IV	100'	30'	70'	0'
V	100'	30'	70'	0'

*(1) **Eastern Washington RMZs on Type S and F Waters** have three zones: The core zone is nearest to the edge of the bankfull width or outer edge of the CMZ, whichever is greater. The inner zone is the middle zone, and the outer zone is furthest from the water. Permitted forest practices vary by timber habitat type and site class.

None of the limitations on harvest in each of the three zones listed below will preclude or limit the construction and

maintenance of roads for the purpose of crossing streams in accordance with WAC 222-24-030 and 222-24-050, or the creation and use of yarding corridors in accordance with WAC 222-30-060(1).

The shade requirements in WAC 222-30-040 must be met regardless of harvest opportunities provided in the inner zone RMZ rules. See ((~~the~~)) board manual((~~,~~)) section 1.

(a) **Core zones.** The core zone extends ((~~30~~)) thirty feet measured horizontally from the edge of the bankfull width or outer edge of the CMZ, whichever is greater, for all timber habitat types. No harvest or construction is allowed in the core zone except as detailed in subsection (1) of this section. Any trees cut for or damaged by yarding corridors must be left on site. Any trees cut as a result of road construction to cross a stream may be removed from the site unless used as part of a large woody debris replacement strategy.

(b) **Inner zones.** Width and leave tree requirements of the inner zone vary by timber habitat type as outlined below.

(i) **Ponderosa pine timber habitat type.**

(A) The width of the inner zone is ((~~70~~)) seventy feet measured horizontally from the outer edge of the core zone on streams greater than ((~~15~~)) fifteen feet bankfull width or ((~~45~~)) forty-five feet measured horizontally from the outer edge of the core zone on streams with a bankfull width of ((~~15~~)) fifteen feet or less.

(B) No harvest is allowed in the inner zone except as described in (b)(i)(C) or (D) of this subsection, and as allowed for stream crossings and yarding corridors as described ((~~above~~)) in this subsection (1).

(C) **Stands with a high basal area:** Harvest is permitted in the inner zone if the basal area in the inner zone is greater than ((~~110~~)) one hundred ten square feet per acre for conifer and hardwood trees equal to or greater than ((~~6~~)) six inches dbh. The harvest must leave at least ((~~50~~)) fifty trees per acre AND subject to (b)(i)(C)(III) of this subsection, a minimum leave tree basal area of at least ((~~60~~)) sixty square feet per acre. The trees to be left shall be selected as follows:

(I) The ((~~21~~)) twenty-one largest trees per acre must be left; and

(II) An additional ((~~29~~)) twenty-nine trees per acre that are ((~~10~~)) ten-inch dbh or greater must be left. If there are less than ((~~29 10~~)) twenty-nine ten-inch dbh or greater trees per acre, leave the ((~~29~~)) twenty-nine largest trees. If there are more than ((~~29 10~~)) twenty-nine ten-inch dbh or greater trees per acre, leave ((~~29 10~~)) twenty-nine ten-inch dbh or greater trees per acre based on the following priority order:

- Trees that provide shade to water;
- Trees that lean towards the water;
- Trees of the preferred species, as defined in WAC 222-16-010;
- Trees that are evenly distributed across the inner zone.

(III) If more than ((~~50~~)) fifty trees per acre are needed to meet the minimum leave tree basal area of ((~~60~~)) sixty square feet

per acre, then additional trees greater than ((~~6~~)) six-inch dbh must be left. If the minimum basal area cannot be met with fewer than ((~~100~~)) one hundred trees of at least ((~~6~~)) six inches dbh, then no more than ((~~100~~)) one hundred trees per acre of the largest remaining trees will be required to be left regardless of the basal area.

(D) **Stands with low basal areas and high density:** Thinning is permitted if the basal area of all species is less than ((~~60~~)) sixty square feet per acre AND there are more than ((~~100~~)) one hundred trees per acre. The thinning must leave a minimum of ((~~100~~)) one hundred trees per acre. The trees to be left must be selected as follows:

(I) The ((~~50~~)) fifty largest trees per acre must be left; and

(II) An additional ((~~50~~)) fifty trees per acre that are greater than ((~~6~~)) six inches dbh must be left. If there are not ((~~50 6~~)) fifty six-inch dbh or greater trees per acre, then all ((~~6~~)) six-inch dbh or greater trees per acre must be left plus the largest remaining trees to equal ((~~50~~)) fifty trees per acre. Select the additional ((~~50~~)) fifty trees based on the following priority order:

- Trees that provide shade to water;
- Trees that lean towards the water;
- Trees of the preferred species, as defined in WAC 222-16-010;
- Trees that are evenly distributed across the inner zone.

(E) To the extent down wood is available on site prior to harvest, at least twelve tons of down wood per acre must be left following harvest as follows:

(I) Six pieces greater than ((~~16~~)) sixteen inches diameter and ((~~20~~)) twenty feet in length; and

(II) Four pieces greater than ((~~6~~)) six inches in diameter and ((~~20~~)) twenty feet in length.

(III) Landowner/operator is not required to create down wood.

(F) See **stream-adjacent parallel roads for all timber habitat types** in (iv) of this subsection if there is a stream-adjacent parallel road in this zone.

(ii) **Mixed conifer timber habitat type.**

(A) The width of the inner zone is ((~~70~~)) seventy feet measured horizontally from the outer edge of the core zone on streams greater than ((~~15~~)) fifteen feet bankfull width or ((~~45~~)) forty-five feet measured horizontally from the outer edge of the core zone on streams with a bankfull width of ((~~15~~)) fifteen feet or less.

(B) No harvest is allowed in the inner zone except as described in (b)(ii)(C) or (D) of this subsection, and as allowed for stream crossings and yarding corridors as described ((~~above~~)) in this subsection (1).

(C) **Stands with a high basal area:**

(I) Harvest is permitted in the inner zone if the combined conifer and hardwood basal area for trees greater than ((~~6~~)) six inches dbh is:

- Greater than ((~~110~~)) one hundred ten square feet per acre

on low site indexes (site index less than ((~~90~~)) ninety); or

- Greater than ((~~130~~)) one hundred thirty square feet per acre on medium site indexes (site index between ((~~90~~)) ninety and ((~~110~~)) one hundred ten); or
- Greater than ((~~150~~)) one hundred fifty square feet per acre on high site indexes (site index greater than ((~~110~~)) one hundred ten).

(II) The harvest must leave at least ((~~50~~)) fifty trees per acre AND a minimum leave tree basal area of at least:

- ((~~70~~)) Seventy square feet per acre on low site indexes; or
- ((~~90~~)) Ninety square feet per acre on medium site indexes; or
- ((~~110~~)) One hundred ten square feet per acre on high site indexes.

(III) The trees to be left shall be selected as follows:

- The ((~~21~~)) twenty-one largest trees per acre must be left; and
- An additional ((~~29~~)) twenty-nine trees per acre that are ((~~10~~)) ten-inch dbh or greater must be left. If there are less than ((~~29-10~~)) twenty-nine ten-inch dbh or greater trees per acre, leave the ((~~29~~)) twenty-nine largest trees. If there are more than ((~~29-10~~)) twenty-nine ten-inch dbh or greater trees per acre, leave ((~~29-10~~)) twenty-nine ten-inch dbh trees per acre based on the following priority order:
- Trees that provide shade to water;
- Trees that lean towards the water;
- Trees of the preferred species, as defined in WAC 222-16-010; or
- Trees that are evenly distributed across the inner zone.
- If more than ((~~50~~)) fifty trees per acre are needed to meet the minimum leave tree basal area for the site index in (b)(ii)(C)(II) of this subsection, then additional trees greater than ((~~6~~)) six inches dbh must be left. If the minimum basal area cannot be met with fewer than ((~~100~~)) one hundred trees at least ((~~6~~)) six inches dbh, then no more than ((~~100~~)) one hundred trees per acre of the largest remaining trees will be required to be left regardless of the basal area.

(D) **Stands with low basal areas and high density:** Thinning is permitted if the basal area of all species is less than the minimum requirements for the site index in (b)(ii)(C)(II) of this subsection AND there are more than ((~~120~~)) one hundred twenty trees per acre. The thinning must leave a minimum of ((~~120~~)) one hundred twenty trees per acre. The trees to be left shall be selected as follows:

(I) The ((~~50~~)) fifty largest trees per acre must be left; and

(II) An additional ((~~70~~)) seventy trees per acre greater than ((~~6~~)) six inches dbh must be left. If there are not ((~~70-6~~)) seventy six-inch dbh or greater trees per acre, then all ((~~6~~)) six-inch dbh or greater trees per acre must be left plus the largest remaining trees to equal ((~~70~~)) seventy trees per acre. Select the additional ((~~70~~)) seventy trees based on the following priority order:

- Trees that provide shade to water;

- Trees that lean towards the water;
- Trees of the preferred species, as defined in WAC 222-16-010; or
- Trees that are evenly distributed across the inner zone.

(E) To the extent down wood is available on site prior to harvest, ((~~20~~)) twenty tons of down wood per acre is required to be left following harvest as follows:

(I) ((~~8~~)) Eight pieces greater than ((~~16~~)) sixteen inches diameter and ((~~20~~)) twenty feet in length; and

(II) ((~~8~~)) Eight pieces greater than ((~~6~~)) six inches in diameter and ((~~20~~)) twenty feet in length.

(III) Landowner/operator is not required to create down wood.

(F) **See stream-adjacent parallel roads for all timber habitat types** in (b)(iv) of this subsection if there is a parallel road in this zone.

(iii) **High elevation timber habitat type.**

(A) The width of the inner zone is ((~~45~~)) forty-five feet measured horizontally from the outer edge of the core zone on streams equal to or less than ((~~15~~)) fifteen feet bankfull width or ((~~70~~)) seventy feet measured horizontally from the outer edge of the core zone on streams with a bankfull width of greater than ((~~15~~)) fifteen feet.

(B) Follow stand requirements for western Washington riparian management zones, WAC 222-30-021 (1)(b).

Note: Option 2 is not permitted for eastside use, because of the minimum floor (100') constraint.

(C) To the extent down wood is available prior to harvest, ((~~30~~)) thirty tons per acre of down wood per acre must be left following harvest as follows:

(I) ((~~8~~)) Eight pieces greater than ((~~16~~)) sixteen inches diameter and ((~~20~~)) twenty feet in length; and

(II) ((~~8~~)) Eight pieces greater than ((~~6~~)) six inches in diameter and ((~~20~~)) twenty feet in length.

(III) Landowner/operator is not required to create down wood.

(D) See **stream-adjacent parallel roads for all timber habitat types** in (b)(iv) of this subsection if there is a parallel road in this zone.

(iv) **Stream-adjacent parallel roads for all timber habitat types in the inner zone.** The shade rule, WAC 222-30-040, must be met whether or not the inner zone includes a stream-adjacent parallel road. Where a stream-adjacent parallel road exists in the inner zone and the minimum required basal area cannot be met due to the presence of the road, then the location of the road determines the allowable operations as follows:

(A) For streams with a bankfull width that is greater than ((~~15~~)) fifteen feet:

(I) If the edge of the road closest to the stream is ((~~75~~)) seventy-five feet or more from the outer edge of bankfull width of the stream or outer edge of CMZ, whichever is greater, **no harvest is permitted in the inner zone.** This includes trees within the inner zone on the uphill side of the road.

(II) No harvest is permitted within the inner zone on the

streamside of the road. If the edge of the road closest to the stream is less than ((~~75~~)) seventy-five feet from the outer edge of bankfull width of the stream or outer edge of CMZ, whichever is greater then:

- Additional leave trees equal in total basal area to the trees lost due to the road must be left near the streams in or adjacent to the unit to be harvested; (See ((~~the~~)) board manual section 7.)
- Where the additional leave trees providing fish habitat for water quality function are determined to be not available or not practical by the department, landowners and operators will employ site specific management activities to replace lost riparian functions that may include placement of large woody debris in streams. (See ((~~the~~)) board manual section 7.)

(B) For streams with a bankfull width less than ((~~15~~)) fifteen feet:

(I) If the edge of the road closest to the stream is ((~~50~~)) fifty feet or more from the outer edge of bankfull width or outer edge of CMZ, whichever is greater, no harvest is permitted in the inner zone. This includes trees within the inner zone on the uphill side of the road.

(II) No harvest is permitted within the inner zone on the stream side of the road. If the edge of the road closest to the stream is less than ((~~50~~)) fifty feet from the bankfull width or CMZ, whichever is greater then:

- Additional leave trees equal in total basal area to the trees lost due to the road must be left near the streams in or adjacent to the unit to be harvested. (See ((~~the~~)) board manual section 7.)
- Where the additional leave trees providing fish habitat for water quality function are determined to be not available or not practical by the department, landowners and operators will employ site specific management activities to replace lost riparian functions that may include placement of large woody debris in streams. (See ((~~the~~)) board manual section 7.)

(C) **Wildlife reserve trees.** Leave all wildlife reserve trees within the inner zone of the riparian management zone where operations in the vicinity do not violate the safety regulations (chapter 296-54 WAC and chapter ((~~49-17~~)) 49.17 RCW administered by the department of labor and industries, safety division). Live wildlife reserve trees will contribute to the basal area requirements for inner zone leave trees and to leave tree counts if they are among the ((~~21~~)) twenty-one largest trees per acre; or meet the requirement of an additional ((~~29~~)) twenty-nine leave trees per acre as per (b)(ii)(E) ((~~above~~)) of this subsection.

(c) **Outer zones.** This zone has three categories based on timber habitat type: Ponderosa pine, mixed conifer and high elevation. The width of this zone is ((~~0 to 55~~)) zero to fifty-five feet measured horizontally from the outer edge of the inner zone depending on the site class and stream width. (See WAC 222-16-010 definition of "RMZ outer zone.")

(i) Tree counts that must be left per acre, regardless of the

presence of an existing stream-adjacent parallel road in the zone, are:

(A) Ponderosa pine habitat type - ((~~10~~)) Ten dominant or codominant trees.

(B) Mixed conifer habitat type - ((~~15~~)) Fifteen dominant or codominant trees.

(C) High elevation habitat type - See requirements for western Washington RMZs in WAC 222-30-021 (1)(c).

(ii) Outer zone leave tree requirements in ((~~section (i) above~~)) (c)(i) of this subsection may be reduced to ((~~5~~)) five trees per acre in the ponderosa pine zone, ((~~8~~)) eight trees per acre in the mixed forest habitat type and ((~~10~~)) ten trees per acre in the high elevation habitat type, if the landowner voluntarily implements a LWD placement plan consistent with board manual sections 5 and 26. Landowners are encouraged to consult with the department and the department of fish and wildlife while designing the plan and prior to submitting a forest practices application. If this strategy is chosen, the approved plan must be included in a complete forest practices application ((~~must include a copy of the WDFW-approved hydraulics project approval (HPA) permit~~)).

*(2) **Eastern Washington protection along Type Np and Ns Waters.**

(a) An **equipment limitation zone** is a ((~~30~~)) thirty-foot wide zone measured horizontally from the outer edge of bankfull width of a Type Np or Ns Water where equipment is limited. It applies to all perennial and seasonal streams.

(i) On-site mitigation is required if any of the following activities exposes the soil more than ((~~10%~~)) ten percent of the surface area of the zone:

(A) Ground based equipment;

(B) Skid trails;

(C) Stream crossings (other than existing roads); or

(D) Cabled logs that are partially suspended.

(ii) Mitigation must be designed to replace the equivalent of lost functions, especially prevention of sediment delivery. Examples include water bars, grass seeding, mulching, etc.

(iii) Nothing in this subsection ((~~(2)~~)) reduces or eliminates the department's authority to prevent actual or potential material damage to public resources under WAC 222-46-030 or 222-46-040 or any related authority to condition forest practices notifications or applications.

(b) **Type Np Waters.**

Within ((~~50~~)) fifty horizontal feet of the outer edge of bankfull width of the stream, the landowner must identify either a partial cut and/or clearcut strategy for each unit to be harvested:

Once approved by the department, the selected strategy will remain in effect until July 1, 2051. If a landowner transfers title of the harvest unit, the landowner must provide written notice of this continuing obligation to the new owner and send a copy to the department. See WAC 222-20-055.

(i) **For partial cuts:**

(A) Basal areas requirements are the same as those specified

for the timber habitat type in the eastern Washington RMZ inner zone.

(B) Where a stream-adjacent parallel road exists, the basal area required in (b)(i)(A) of this subsection is required to be left. (See stream-adjacent parallel roads for Type Np Waters in (c) ((~~below~~)) of this subsection.)

(C) The trees to be included in the basal area determination and left after harvest must include:

(I) The ((~~10~~)) ten largest trees per acre;

(II) Up to an additional ((~~40~~)) forty trees per acre greater than or equal to ((~~10~~)) ten inches dbh must be left. If all or some of the trees are not at least ((~~10~~)) ten inches dbh, then the largest of the remaining trees must be left. Select trees based on the following priority order:

- Provide streambank stability;
- Provide shade to water;
- Lean towards the water;
- Preferred species, as defined in WAC 222-16-010; or
- Evenly distributed; and

If the basal area target has not been met with the trees required above, up to an additional ((~~50~~)) fifty trees are required greater than ((~~6~~)) six inches in dbh based on the above priority order.

(D) Side slope seeps must be protected with a ((~~50~~)) fifty-foot partial cut buffer that meets the basal area and leave tree requirements of (b)(i)(A), (B), and (C) ((~~above~~)) of this subsection. The buffer shall be measured from the outer perimeter of the perennially saturated soil zone.

(ii) **For clearcuts:**

When the clearcut strategy in this subsection is selected, the landowner must simultaneously designate a ((~~2~~)) two-sided no-harvest ((~~50~~)) fifty-foot buffer along the stream reach in the harvest unit that:

(A) Is equal in total length to the clearcut portion of the stream reach in the harvest unit; and

(B) Meets the upper end of basal area requirements for each respective timber habitat type in the eastern Washington RMZ inner zone. See WAC 222-30-022 (1)(b)(i), (ii) or (iii).

(C) The streamside boundary of all clearcuts must:

(I) Not exceed in total ((~~30%~~)) thirty percent of the length of the stream reach in the harvest unit;

(II) Not exceed ((~~300~~)) three hundred continuous feet in length;

(III) Not be located within ((~~500~~)) five hundred feet of the intersection of a Type S or F Water; and

(IV) Not occur within ((~~50~~)) fifty feet of the following sensitive sites as defined in WAC 222-16-010:

- The outer perimeter of a soil zone perennially saturated from a headwall seep;
- The outer perimeter of a soil zone perennially saturated from a side-slope seep;
- The center of a headwater spring;
- An alluvial fan;

- The center point of intersection of two or more Type Np Waters.

(c) **Stream-adjacent parallel roads for Type Np Waters.** If a road exists in a Type Np RMZ and the basal area required to be left cannot be met within ((~~50~~)) fifty feet of the outer edge of bankfull width of the stream measured horizontally due to the presence of the road, then the distance of the road to the stream determines the allowable operations as follows:

(i) A road that is within ((~~30 to 49~~)) thirty to forty-nine feet measured horizontally from the outer edge of bankfull width of the stream requires:

(A) A total of ((~~100~~)) one hundred feet of riparian management zone measured horizontally (both sides of the stream count towards the total) must be left in a manner to provide maximum functions for nonfish use streams. If harvest is taking place on only one side of the stream, then ((~~50~~)) fifty feet of RMZ width must be left, regardless of presence of a stream-adjacent parallel road. The width of the road is not counted as part of the total width of the RMZ.

(B) The location of the riparian management zone required in (A) of this subsection shall be based on the following priority order:

(I) Preferred: The area between the stream and the stream side edge of the road.

(II) The area that provides the most shade to the channel.

(III) The area that is most likely to deliver large woody debris to the channel.

(ii) A road that is within less than ((~~30~~)) thirty feet from the outer edge of bankfull width of the stream measured horizontally requires, in addition to (c)(i)(A) and (B) of this subsection, that all trees between the stream and the streamside edge of the road must be left.

AMENDATORY SECTION (Amending WSR 05-12-119, filed 5/31/05, effective 7/1/05)

WAC 222-30-050 Felling and bucking. *(1) **Felling along water.**

(a) Except when removing or repositioning large woody debris per WAC 222-30-062, no trees will be felled into or removed from Type S and F Waters RMZ core zones, sensitive sites, or Type A or B Wetlands except trees which cannot practically and safely be felled outside these areas using techniques in general use. Such felling and removing in Type S or F Waters shall comply with the ((~~hydraulic project approval of the department of fish and wildlife~~)) mitigation measures necessary to achieve no-net-loss of productive capacity of fish and shellfish habitat as follows:

(i) Trees shall not be felled into or across the stream except

where approved by the department.

(ii) Trees or logs that enter a stream during felling shall remain where they enter unless parts or all of the trees or logs are specifically approved by the department.

(iii) If limbs or other small debris enter the stream as a result of felling, they shall be removed concurrently with each change in yarding road or within seventy-two hours after entry into the stream and placed outside the 100-year flood plain. Limbs or other small debris shall be removed from dry streams prior to the normal onset of high flows. Large woody material which was in place prior to felling shall not be disturbed.

(iv) Precautions shall be taken to minimize the release of sediment to waters downstream from the felling activity. See board manual section 5 for technical guidance.

(b) Within RMZ inner and outer zones, and wetland management zones, fell trees favorable to the lead consistent with safety standards to yard or skid away from the waters. The use of directional felling, lining, jacking and staged felling techniques are required.

(c) Trees may be felled into Type Np Water if logs are removed as soon thereafter as practical. See forest practices board manual section 4 guidelines for clearing slash and debris from Type Np and Ns Water.

*(2) **Bucking or limbing along water.**

No bucking or limbing shall be done on trees or portions thereof lying within the bankfull width of Type S, F or Np Waters, in the RMZ core zones, in sensitive sites, or in open water areas of Type A Wetlands, except as necessary to remove the timber from the water, or unless it is part of a proposal to remove or reposition large wood debris per WAC 222-30-062. Such bucking or limbing in Type S or F Waters shall comply with the ((~~hydraulic project approval of the department of fish and wildlife~~)) mitigation measures in subsection (1)(a) of this section.

*(3) **Felling near riparian management zones, wetland management zones and setting boundaries.** Reasonable care shall be taken to avoid felling trees into riparian management zones, wetland management zones and areas outside the harvest unit.

(4) **Felling in selective and partial cuts.** Reasonable care shall be taken to fell trees in directions that minimize damage to residual trees.

(5) **Disturbance avoidance for northern spotted owls.** Felling and bucking within a SOSEA boundary shall not be allowed within 0.25 mile of a northern spotted owl site center between March 1st and August 31st provided that, this restriction shall not apply if:

(a) The landowner demonstrates that the owls are not actively nesting during the current nesting season; or

(b) The forest practice is operating in compliance with a plan or agreement developed for the protection of the northern spotted owl under WAC 222-16-080 (6)(a), (e), or (f).

(6) **Disturbance avoidance for marbled murrelets.** Felling and bucking shall not be allowed within 0.25 mile of an occupied marbled murrelet site during the daily peak activity periods within

the critical nesting season, provided that, this restriction shall not apply if the forest practice is operating in compliance with a plan or agreement developed for the protection of the marbled murrelet under WAC 222-16-080 (6)(a) or (c).

AMENDATORY SECTION (Amending WSR 08-24-011, filed 11/21/08, effective 12/22/08)

WAC 222-30-060 Cable yarding. *(1) **Type S and F Waters and sensitive sites.** No timber shall be cable yarded in or across Type S or F Waters except where the logs will not materially damage the bed of waters, banks of sensitive sites, or riparian management zones. If yarding across Type S or F Waters is permitted, then yarding is limited to cable or other aerial logging methods. Any work in or above Type S or F Waters requires ((~~a hydraulics project approval (HPA)~~)) an approved forest practices application. Logs must be fully suspended above the water unless otherwise allowed in the applicable ((~~HPA~~)) forest practices application. Yarding corridors must be no wider or more numerous than necessary to accommodate safe and efficient transport of logs. Generally, yarding corridors should be located no closer to each other than ((~~150~~)) one hundred fifty feet (measured edge to edge) and should be no wider than ((~~30~~)) thirty feet. Safety is a prime consideration in the location of yarding corridors. Total openings resulting from yarding corridors must not exceed ((~~20%~~)) twenty percent of the stream length associated with the forest practices application. When changing cable locations, care must be taken to move cables around or clear of the riparian vegetation to avoid damage to riparian vegetation.

*(2) **Type A or B Wetlands.** No timber shall be cable yarded in or across Type A or B Wetlands without ((~~written approval from the department and may require a hydraulic project approval from the department of fish and wildlife~~)) an approved forest practices application.

*(3) **Deadfalls.** Logs which are firmly embedded in the bed or bank of Type S or F Waters shall not be removed or disturbed without ((~~hydraulic project approval from the department of fish and wildlife~~)) an approved forest practices application.

*(4) **Yarding in riparian management zones, sensitive sites, and wetland management zones.** Where timber is yarded from or across a riparian management zone, sensitive site, or wetland management zone reasonable care shall be taken to minimize damage to the vegetation providing shade to the stream or open water areas and to minimize disturbance to understory vegetation, stumps and root systems. Where practical and consistent with good safety practices, logs shall be yarded in the direction in which they lie and away from Type A or B Wetlands or Type S, F or Np Waters until clear of the wetland management zone or riparian management zone.

(5) **Trees or logs that enter a stream during yarding** shall remain where they enter unless parts or all of the trees or logs are specifically authorized to be removed in an approved forest practices application.

*(6) **Logs transported across Type S, F, or flowing waters** shall be suspended so no portion of the logs or limbs can enter the watercourse or damage the bed and banks.

*(7) Yarding corridors or full suspension shall be required to prevent damage to riparian vegetation.

*(8) **If limbs or other small debris enter the stream** as a result of yarding of timber, they shall be removed concurrently with each change in yarding road or within seventy-two hours after entry into the stream, and placed outside the 100-year flood plain. Limbs or other small debris shall be removed from dry streams prior to the normal onset of high flows. Large woody material which was in place prior to yarding of timber shall not be disturbed.

*(9) **Precautions shall be taken to minimize the release of sediment** to waters downstream from the yarding activity. See board manual section 5 for technical guidance.

(10) **Direction of yarding.**

(a) Uphill yarding is preferred.

(b) Where downhill yarding is used, reasonable care shall be taken to lift the leading end of the log to minimize downhill movement of slash and soils.

*(c) When yarding parallel to a Type S or F Water channel below the 100-year flood level or within the riparian management zone, reasonable care shall be taken to minimize soil disturbance and to prevent logs from rolling into the stream, lake, pond, or riparian management zone.

((~~(6)~~)) (11) **Disturbance avoidance for northern spotted owls.** The operation of heavy equipment within a SOSEA boundary shall not be allowed within 0.25 mile of a northern spotted owl site center between March 1st and August 31st provided that, this restriction shall not apply if:

(a) The landowner demonstrates that the owls are not actively nesting during the current nesting season; or

(b) The forest practice is operating in compliance with a plan or agreement developed for the protection of the northern spotted owl under WAC 222-16-080 (6)(a), (e), or (f).

((~~(7)~~)) (12) **Disturbance avoidance for marbled murrelets.** Yarding or operation of heavy equipment shall not be allowed within 0.25 mile of an occupied marbled murrelet site during the daily peak activity periods within the critical nesting season, provided that, this restriction shall not apply if the forest practice is operating in compliance with a plan or agreement developed for the protection of the marbled murrelet under WAC 222-16-080 (6)(a) or (c).

NEW SECTION

WAC 222-30-062 *Large woody debris removal or repositioning. Large woody debris removal or repositioning projects shall incorporate mitigation measures as necessary to achieve no-net-loss of productive capacity of fish and shellfish habitat. The following shall apply to large woody debris removal or repositioning:

(1) Large woody debris removal from streams shall only be approved where necessary to address safety considerations, or where its removal would not diminish the fish habitat quality of the watercourse. The department may approve the repositioning of large woody debris within the watercourse to protect life and property or as needed to conduct a forest practices hydraulic project. Repositioned large woody material shall be placed or anchored to provide stable, functional fish habitat.

(2) Large woody debris removal shall be conducted by equipment stationed on the bank, bridge, or other approved methods.

(3) Unless otherwise authorized, large woody debris shall be suspended during its removal so no portion of the large woody debris or limbs can damage the bed or banks. Yarding corridors or full suspension shall be required to avoid damage to riparian vegetation. It may be necessary to cut the large woody debris in place, to a size that allows suspension during removal.

(4) Smaller limb and bark debris associated with the large woody material shall be removed and disposed of so as not to reenter the typed water.

(5) Large woody debris embedded in a bank or bed shall be left undisturbed and intact except where authorized for removal.

(6) Large woody debris removal or repositioning shall be accomplished in a manner which minimizes the release of bedload, logs, or debris downstream.

(7) Depressions created in gravel bars shall be filled, smoothed over, and sloped upwards toward the bank on a minimum two percent gradient.

AMENDATORY SECTION (Amending WSR 08-24-011, filed 11/21/08, effective 12/22/08)

WAC 222-30-070 Ground-based logging systems. *(1) **Typed waters and wetlands.**

(a) Ground-based equipment shall not be used in Type S or F Water, except with approval by the department ((~~and with a hydraulic project approval issued by the department of fish and wildlife~~)). Yarding across Type S or F Waters is limited to cable or other aerial logging methods.

(b) Ground-based transport of logs across Type Np and Ns Waters shall minimize the potential for damage to public resources.

(i) Skidding logs and driving ground-based equipment through defined channels with flowing water is not allowed.

(ii) Ground-based transport of logs to landings across any Typed Np or Ns Water shall minimize the potential to damage public resources.

(iii) Whenever skidding across Type Np or Ns Waters, the direction of log movement between stream banks shall be designed to minimize sediment delivery to the stream.

(c) In order to maintain wetland water movement and water quality, and to prevent soil compaction, ground-based logging systems shall not be used in Type A or B wetlands.

(d) Where harvest in wetlands is permitted, ground-based logging systems shall be limited to low impact harvest systems. Ground-based logging systems operating in wetlands shall only be allowed during periods of low soil moisture or frozen soil conditions.

(e) Locations of temporary stream crossings to Np Waters shall be shown on the base map of the forest practices application. Whenever skidding in or across Type Np or Ns Waters, the direction of log movement between stream banks shall be designed to minimize sediment delivery to the stream. BMPs for stream crossings can be found in ((~~the~~)) board manual section ((~~3~~)) 5.

*(2) **Riparian management zone.**

(a) Logging will be permitted within the riparian management zone subject to riparian management zone protection in chapter 222-30 WAC. However, any use of ground-based yarding machines within the zone must be as described in an approved forest practices application or otherwise approved in writing by the department.

(b) When transporting logs in or through the riparian management zone with ground-based equipment, the number of routes through the zone shall be minimized.

(c) Logs shall be transported so as to minimize damage to leave trees and vegetation in the riparian management zone, to the extent practical and consistent with good safety practices.

*(3) **Wetlands management zones.**

(a) Logging will be permitted within wetland management zones subject to restrictions in WAC 222-30-020((~~(7)~~)) (8).

(b) Where feasible logs shall be skidded with at least one end suspended from the ground so as to minimize soil disturbance and damage to leave trees and vegetation in the wetland management zone.

(c) Ground-based harvesting systems shall not be used within the minimum WMZ width unless described in an approved forest practices application or otherwise approved in writing by the department.

*(4) **Deadfalls.** Logs firmly embedded in the bed or bank of Type S or F Waters shall not be removed or disturbed without ((~~hydraulic project~~)) approval from the department ((~~of fish and wildlife~~)).

*(5) **Moisture conditions.**

(a) Ground-based logging systems shall not be used on exposed erodible soils or saturated soils if sediment delivery is likely to

disturb a wetland, stream, lake or pond.

(b) When soil moisture is high and unrestricted operation of ground-based equipment would result in unreasonable soil compaction, operations shall be restricted to methods that minimized widespread soil compaction or, operations postponed until site conditions improve such that yarding may proceed without causing unreasonable soil compaction and the long-term impacts to soil productivity and moisture absorption capacity that can result.

(6) **Protection of residual timber.** Reasonable care shall be taken to minimize damage from skidding to the stems and root systems of residual timber and to young reproduction.

*(7) **Skid trail location and construction.**

(a) Skid trails shall be kept to the minimum width.

(b) Reasonable care shall be taken to minimize the amount of sidecast required and shall only be permitted above the 100-year flood level.

(c) Skid trails shall be outsloped where practical, but be insloped where necessary to prevent logs from sliding or rolling downhill off the skid trail.

(d) Skid trails running parallel or near parallel to streams shall be located outside the no-harvest zone of all typed waters and at least ((~~30~~)) thirty feet from the outer edge of the bankfull width of the unbuffered portions of Type Np or Ns Water unless approved in writing by the department.

(e) Skid trails shall cross the drainage point of swales at an angle to minimize the potential for delivering sediment to a typed water or where channelization is likely to occur. See board manual section 3.

*(8) **Skid trail maintenance.**

(a) Upon completion of use and termination of seasonal use, skid trails on slopes in exposed soils shall be water barred where necessary to prevent soil erosion.

(b) Skid trails located within ((~~200~~)) two hundred feet horizontal distance of any typed water that directly delivers to the stream network shall use water bars, grade breaks, and/or slash to minimize sediment delivery to the stream. Water bars shall be placed at a frequency to minimize gullying and soil erosion. In addition to water barring, skid trails with exposed soil that is erodible and may be reasonably expected to cause damage to a public resource shall be seeded with a noninvasive plant species (preferably a species native to the state) and adapted for rapid revegetation of disturbed soil, or treated with other erosion control measures acceptable to the department.

*(9) **Slope restrictions.** Ground-based systems shall not be used on slopes where in the opinion of the department this method of operation would cause actual or potential material damage to a public resource.

(10) **Disturbance avoidance for northern spotted owls.** The operation of heavy equipment within a SOSEA boundary shall not be allowed within 0.25 mile of a northern spotted owl site center between March 1st and August 31st, provided that, this restriction shall not apply if:

(a) The landowner demonstrates that the owls are not actively nesting during the current nesting season; or

(b) The forest practice is operating in compliance with a plan or agreement developed for the protection of the northern spotted owl under WAC 222-16-080 (6)(a), (e), or (f).

(11) **Disturbance avoidance for marbled murrelets.** Operation of heavy equipment shall not be allowed within 0.25 mile of an occupied marbled murrelet site during the daily peak activity periods within the critical nesting season, provided that, this restriction shall not apply if the forest practice is operating in compliance with a plan or agreement developed for the protection of the marbled murrelet under WAC 222-16-080 (6)(a) or (c).

AMENDATORY SECTION (Amending WSR 01-12-042, filed 5/30/01, effective 7/1/01)

WAC 222-30-100 Slash disposal or prescribed burning. (1) **Slash disposal or prescribed burning are prohibited in the core zone.**

(2) **Slash disposal** techniques:

*(a) Any conventional method of slash disposal may be used, except in Type A or B Wetlands, wetland management zones, and RMZ core and inner zones, Type Np RMZs, sensitive sites, and on sites where the department determines that a particular method would cause unreasonable risk to leave trees, public resources or site productivity. Conventional methods of slash disposal include the following: Controlled broadcast burning; pile or windrow and burn; pile or windrow without burning; mechanical scatter and compaction; scarification; chip, mulch or lop and scatter; burying; and physical removal from the forest lands: Provided, That on land shown to have low productivity potential the landowner or operator shall obtain the department's approval of its regeneration plan prior to utilizing controlled broadcast burning as a slash disposal technique. In riparian management inner zones, slash disposal shall be by hand, unless approved by the department. Slash disposal methods that employ machine piling, mechanical scatter and/or compaction, scarification or other techniques that result in soil disturbance shall not be allowed in equipment limitation zones. Scarification shall not be allowed within wetlands. Machine piling is not allowed in Type A and B Wetlands. Department approval, through a burning permit, is required for burning within an equipment limitation zone.

(b) All slash burning requires a burning permit from the department which provides for compliance with the smoke management plan and reasonable care to protect Type A and B Wetlands, wetland management zones, riparian management zones, equipment limitation zones, soil, residual timber, public resources, and other property.

(3) **Slash isolation, reduction, or abatement** is required when

the department determines there is an extreme fire hazard according to law (see chapter 332-24 WAC).

(4) **Slash disposal** is required where the forest landowner has applied for and been granted an extension of time for reforestation on the grounds that slash disposal is necessary or desirable before reforestation.

*(5) **Removing slash and** debris from streams.

"Slash" or "debris" which can reasonably be expected to cause significant damage to the public resource shall be removed from Type S, F or Np Waters, to above the 100-year flood level and left in a location or manner minimizing risk of re-entry into the stream, lake or pond and if substantial accumulations of slash exist below the 100-year flood level of Type S, F or Np Waters, slash disposal is required. See ((~~the forest practices~~)) WAC 222-16-025, Fish protection standards for general provisions for all forest practices hydraulic projects, and board manual section 4 for ((~~"~~))guidelines for clearing slash and debris from Type Np and Ns Waters.((~~"~~))

*(6) **Fire trails.**

(a) Construct drainage structures as needed to control erosion.

(b) Reasonable care shall be taken to minimize excavation during fire trail construction and sidecast shall only be permitted above the 100-year flood level.

(c) Fire trails shall not be located within Type A or B Wetlands, wetland management zones, equipment limitation zones or riparian zones without prior written approval of the department. Hand constructed fire trails are preferred within forested wetlands. When machine built fire trails are necessary for control of burning, trail width and excavation shall be minimized.

(7) **Disturbance avoidance for northern spotted owls.** Burning within a SOSEA boundary shall not be allowed within 0.25 mile of a northern spotted owl site center between March 1st and August 31st, provided that, this restriction shall not apply if:

(a) The landowner demonstrates that the owls are not actively nesting during the current nesting season; or

(b) The forest practice is operating in compliance with a plan or agreement developed for the protection of the northern spotted owl under WAC 222-16-080 (6)(a), (e), or (f).

(8) **Disturbance avoidance for marbled murrelets.** Slash disposal or prescribed burning shall not be allowed within 0.25 mile of an occupied marbled murrelet site during the critical nesting season, provided that, this restriction shall not apply if the forest practice is operating in compliance with a plan or agreement developed for the protection of the marbled murrelet under WAC 222-16-080 (6)(a) or (c).