



TIMBER NOTICE OF SALE

SALE NAME: JOHNNY'S SHACK

AGREEMENT NO: 30-99246

AUCTION: January 29, 2020 starting at 10:00 a.m., Olympic Region Office, Forks, WA

COUNTY: Clallam

SALE LOCATION: Sale located approximately 14 miles northwest of Forks, WA

PRODUCTS SOLD AND SALE AREA:

All timber, except trees marked with blue paint or bounded out by leave tree area boundary tags; bounded by timber sale boundary tags in Units 1, 2, 3, 4, 5 and 6; all timber bounded by right of way boundary tags (Unit 7)); on part(s) of Sections 25, 26 and 35 all in Township 30 North, Range 14 West, W.M., containing 112 acres, more or less.

CERTIFICATION: This sale is certified under the Sustainable Forestry Initiative® program Standard (cert no: PwC-SFIFM-513)

ESTIMATED SALE VOLUMES AND QUALITY:

Table with columns: Species, Avg DBH, Ring Count, Total MBF, and MBF by Grade (1P, 2P, 3P, SM, 1S, 2S, 3S, 4S, UT). Rows include Hemlock, Spruce, Douglas fir, Red alder, and Sale Total.

MINIMUM BID: \$771,000.00

BID METHOD: Sealed Bids

PERFORMANCE SECURITY:

\$100,000.00

SALE TYPE: Lump Sum

EXPIRATION DATE: September 30, 2023

ALLOCATION: Export Restricted

BID DEPOSIT: \$77,100.00 or Bid Bond. Said deposit shall constitute an opening bid at the appraised price.

HARVEST METHOD: Ground - 100%. No rubber tire skidders allowed unless skidding and rutting requirements can be met and a harvest plan is submitted and approved. 30' Equipment Limitation zones on all typed waters.

ROADS: 16.70 stations of optional construction. 204.95 stations of optional prehaul maintenance. 26.75 stations of decommissioning. All road activities Road construction will not be permitted from October 1 to June 30 unless authorized in writing by the Contract Administrator on the D-2093 (stations 0+00 - 14+75), D-2093.1 (stations 0+00 - 2+50), and the D-5201 (stations 11+75 - 21+25); and the culvert removal on the D-2980 (station 9+30). Temporary fish culvert must be installed and removed in one hydraulic season. The hauling of forest products will not be permitted from October 31 to June 1 unless authorized in writing by the Contract Administrator on the D-2093 (stations 0+00 - 14+75), D-2093.1 (stations 0+00 - 12+50), and the D-5201 (stations 11+75 - 21+25)

ACREAGE DETERMINATION

CRUISE METHOD: Sale acreage was 100% GPS'd. Sale units were cruised using a variable plot sample.



## TIMBER NOTICE OF SALE

---


**FEES:** Within seven days of auction, Purchaser must provide the Department of Natural Resources - Olympic Region, with a check, made payable to Rayonier Operating Company LLC in the amount of \$3,764.73 (\$2,363.73 for a road use permit and \$1,401.00 for right of way timber). \$73,355.00 is due on day of sale. \$9.00 per MBF is due upon removal. These are in addition to the bid price.

**SPECIAL REMARKS:** There are locked gates on the RY-9009 Road and the Loop Pit - contact the Olympic Region Dispatch Center at 360-374-2811 to obtain a AA-1 key.

# TIMBER SALE MAP

**SALE NAME:** JOHNNY'S SHACK  
**AGREEMENT #:** 30-099246  
**TOWNSHIP(S):** T30R14W  
**TRUST(S):** Capitol Grant (7)

**REGION:** Olympic Region  
**COUNTY(S):** Clallam  
**ELEVATION RGE:** 320' -780'



All State Unless Otherwise Noted

## Legend


- |                               |                    |                              |
|-------------------------------|--------------------|------------------------------|
| Variable Retention Harvest    | Stream Type        | Survey Monument              |
| Leave Tree Area               | Stream Type Break  | Public Land Survey Townships |
| Riparian Mgt Zone             | Sale Boundary Tags | Public Land Survey Sections  |
| Existing Roads                | Leave Tree Tags    | DNR Managed Lands            |
| Optional Pre-Haul Maintenance | Right of Way Tags  |                              |
| Streams                       |                    |                              |



# TIMBER SALE MAP

**SALE NAME:** JOHNNY'S SHACK  
**AGREEMENT #:** 30-099246  
**TOWNSHIP(S):** T30R14W  
**TRUST(S):** Capitol Grant (7)

**REGION:** Olympic Region  
**COUNTY(S):** Clallam  
**ELEVATION RGE:** 320' -780'



## Legend


- |                            |                               |                    |                              |
|----------------------------|-------------------------------|--------------------|------------------------------|
| Variable Retention Harvest | Existing Roads                | Stream Type Break  | Public Land Survey Townships |
| Leave Tree Area            | Optional Pre-Haul Maintenance | Sale Boundary Tags | Public Land Survey Sections  |
| Riparian Mgt Zone          | Optional Construction         | Leave Tree Tags    | DNR Managed Lands            |
| Forested Wetland           | Streams                       | Right of Way Tags  |                              |
| Wetland Mgt Zone           | Stream Type                   | Survey Monument    |                              |



# DRIVING MAP

**SALE NAME:** JOHNNY'S SHACK  
**AGREEMENT#:** 30-099246  
**TOWNSHIP(S):** T29R14W, T30R14W, T29R13W  
**TRUST(S):** Capitol Grant (7)

**REGION:** Olympic Region  
**COUNTY(S):** Clallam  
**ELEVATION RGE:** 320' -780'



Map may not be to scale

**Legend**

- Distance Indicator
- Highway Shield (101)
- Gate
- Highway
- ⚡ Rock Pit
- Open Water
- Milepost Markers
- Haul Route
- Other Road
- Timber Sale Unit

**DIRECTIONS**

From Forks, drive N on HWY 101 for 3.6 miles then at MP 195, turn Left onto the D-2000. Continue 10 miles on the D-2000. To access Unit 1, turn Left onto the D-5200 and continue for 0.10 miles onto the D-2090, drive 0.5 miles to Unit 1. To access Unit 2 from the D-2000/D-5200 junction, turn right (NE) on the D-5200 and continue for 0.6 miles, turn onto the D-5201 and continue 0.45 miles to Unit 2. To access Unit 3, from the D-5200, continue past the D-5201 for 0.2 miles, turn right onto the D-2900, continue 1.25 miles to Unit 3. To access Unit 5 starting from the D-5200/ D-2900 junction, continue east turning right onto the RY-9000, drive 0.4 miles, turn left onto the RY-9009 and continue 0.35 miles to Unit 5. For Unit 4, continue 0.6 miles past RY-9009, on the RY-9000. Unit 4 is on both sides of the road. Unit 7 ROW begins immediately past Unit 4 on the RY-9000. For Unit 6 drive 0.7 miles past Unit 4 on the RY-9000 and turn left on the RY-9000.61, drive 0.05 miles for Unit 6 on the left side of the road.

Loop Pit: from Forks drive 8 miles north on HWY 101. Turn right on the Loop Pit access road.



**STATE OF WASHINGTON  
DEPARTMENT OF NATURAL RESOURCES**

**BILL OF SALE AND CONTRACT FOR  
FOREST PRODUCTS**

**Export Restricted Lump Sum AGREEMENT NO. 30-099246**

**SALE NAME: JOHNNY'S SHACK**

**THE STATE OF WASHINGTON DEPARTMENT OF NATURAL  
RESOURCES, HEREINAFTER ACTING SOLELY, IN ITS PROPRIETARY  
CAPACITY, STATE, AND PURCHASER, AGREE AS FOLLOWS:**

Section G: General Terms

G-001 Definitions

The following definitions apply throughout this contract;

Bill of Sale and Contract for Forest Products: Contract between the Purchaser and the State, which sets forth the procedures and obligations of the Purchaser in exchange for the right to remove forest products from the sale area. The Bill of Sale and Contract for Forest Products may include a Road Plan for any road construction or reconstruction, where applicable.

Contract Administrator: Region Manager's designee responsible for assuring that the contractual obligations of the Purchaser are met.

Forest Product: Any material derived from the forest for commercial use.

Purchaser: The company or individual that has entered into a Bill of Sale and Contract for Forest Products with the State for the right to harvest and remove forest products from the timber sale area.

Road Construction: Includes building new and maintaining existing forest roads and associated work that may be optional or required as described in the Road Plan.

State: The Washington State Department of Natural Resources, landowner and seller of Forest Products from the timber sale area. The State is represented by the Region Manager as designated on the contract signature page. Contractual obligations to the State are enforced by the Region Manager or the designated Contract Administrator.

Subcontractor: Individual or company employed by the Purchaser to perform a portion or all of the services required by The Bill of Sale and Contract for Forest Products. The Purchaser is responsible for independently negotiating, procuring and paying for all subcontracted services rendered.

G-011 Right to Remove Forest Products and Contract Area

Purchaser was the successful bidder on January 29, 2020 and the sale was confirmed on \_\_\_\_\_. The State, as owner, agrees to sell to Purchaser, and Purchaser agrees to purchase as much of the following forest products as can be cut and removed during the term of this contract: All timber, except trees marked with blue paint or bounded out by leave tree area boundary tags; bounded by timber sale boundary tags in Units 1, 2, 3, 4, 5 and 6; all timber bounded by right of way boundary tags (Unit 7));, located on approximately 112 acres on part(s) of Sections 25, 26, and 35 all in Township 30 North, Range 14 West W.M. in Clallam County(s) as designated on the sale area and as shown on the attached timber sale map.

All forest products described above from the bole of the tree that meet or exceed 2 inches diameter inside bark on the small end are eligible for removal. Above ground components of a tree that remain as by-products after the manufacture of logs, including but not limited to tree tops, branches, limbs, needles, leaves, stumps, are not eligible for removal under the terms of this contract.

Forest products purchased under a contract that is designated as export restricted shall not be exported until processed. Forest products purchased under a contract that is designated as exportable may be exported prior to processing.

G-020 Inspection By Purchaser

Purchaser hereby warrants to the State that they have had an opportunity to fully inspect the sale area and the forest products being sold. Purchaser further warrants to the State that they enter this contract based solely upon their own judgment of the value of the forest products, formed after their own examination and inspection of both the timber sale area and the forest products being sold. Purchaser also warrants to the State that they enter this contract without any reliance upon the volume estimates, acreage estimates, appraisals, pre-bid documentation, or any other representations by the State Department of Natural Resources.

G-025 Schedules

The following attached schedules are hereby incorporated by reference:

Schedule	Title
A	SLASH PILING SPECIFICATIONS
B	GREEN TREE RETENTION PLAN

G-031 Contract Term

Purchaser shall complete all work required by this contract prior to September 30, 2023.

G-040 Contract Term Adjustment - No Payment

Purchaser may request an adjustment in the contract term. A claim must be submitted in writing and received by the State within 30 days after the start of interruption or delay. The claim must also indicate the actual or anticipated length of interruption or delay. The State may grant an adjustment without charge only if the cause for contract term adjustment is beyond Purchaser's control. The cause must be one of the following and the adjustment may be granted only if operations or planned operations under this contract are actually interrupted or delayed:

- a. Road and bridge failures which deny access.
- b. Access road closures imposed by road owner.
- c. Excessive suspensions as provided in clause G-220.
- d. Regulatory actions not arising from Purchaser's failure to comply with this contract which will prevent timber harvest for a period less than 6 months.

G-051 Contract Term Extension - Payment

Extensions of this contract term may be granted only if, in the judgment of the State, Purchaser is acting in good faith and is endeavoring to remove the forest products conveyed. The term of this contract may be extended for a reasonable time by the State if all of the following conditions are satisfied:

- a. A written request for extension of the contract term must be received prior to the expiration date of the contract.
- b. Completion of all required roads and compliance with all contract and regulatory requirements.
- c. For the first extension, not to exceed 1 year, payment of at least 25 percent of the total contract price.

For the second extension, not to exceed 1 year, payment of at least 90 percent of the total contract price.

The payments shall not include the initial deposit which shall be held according to the provisions of RCW 79.15.100.

- d. Payment of an amount based on 12 percent interest per annum on the unpaid portion of the total contract price.

All payments, except the initial deposit, will be deducted from the total contract price to determine the unpaid portion of the contract.

- e. Payment of \$727.00 per acre per annum for the acres on which an operating release has not been issued .
- f. In no event will the extension charge be less than \$200.00.
- g. Extension payments are non-refundable.

G-053 Surveys - Sensitive, Threatened, Endangered Species

Whenever the State determines that a survey for sensitive, threatened, or endangered species is prudent, or when Purchaser determines a survey is prudent and the State agrees, Purchaser shall perform such surveys at Purchaser's expense and to the standards required by the State. The survey information shall be supplied to the State.

G-060 Exclusion of Warranties

The PARTIES AGREE that the IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE and ALL OTHER WARRANTIES EXPRESSED OR IMPLIED ARE EXCLUDED from this transaction and shall not apply to the goods sold. For example, THE FOLLOWING SPECIFIC MATTERS ARE NOT WARRANTED, and are EXCLUDED from this transaction:

- a. The MERCHANTABILITY of the forest products. The use of the term "merchantable" in any document is not intended to vary the foregoing.
- b. The CONDITION of the forest products. The forest products will be conveyed "AS IS."
- c. The ACREAGE contained within any sale area. Any acreage descriptions appearing in the timber notice of sale, timber sale contract, or other documents are estimates only, provided solely for administrative and identification purposes.
- d. The VOLUME, QUALITY, OR GRADE of the forest products. The State neither warrants nor limits the amount of timber to be harvested. The descriptions of the forest products to be conveyed are estimates only, made solely for administrative and identification purposes.
- e. The CORRECTNESS OF ANY SOIL OR SURFACE CONDITIONS, PRE-SALE CONSTRUCTION APPRAISALS, INVESTIGATIONS, AND ALL OTHER PRE-BID DOCUMENTS PREPARED BY OR FOR THE STATE. These documents have been prepared for the State's appraisal purposes only.

- f. THAT THE SALE AREA IS FREE FROM THREATENED OR ENDANGERED SPECIES or their habitat. The State is not responsible for any interference with forestry operations that result from the presence of any threatened or endangered species, or the presence of their habitat, within the sale area.
- g. THAT THE FORESTRY OPERATIONS to be performed under this contract WILL BE FREE FROM REGULATORY ACTIONS by governmental agencies. The State is not responsible for actions to enforce regulatory laws, such as the Washington Forest Practices Act (chapter 76.09 RCW), taken by the Department of Natural Resources or any other agency that may affect the operability of this timber sale.
- h. Items contained in any other documents prepared for or by the State.

G-062 Habitat Conservation Plan

The State has entered into a Habitat Conservation Plan (HCP) with the U.S. Fish and Wildlife Service and the National Marine Fisheries Service (the Services) to address state trust land management issues relating to compliance with the Federal Endangered Species Act. The activities to be carried out under this contract are located within the State's HCP area and are subject to the terms and conditions of the HCP, and the Services' Incidental Take Permit Nos. 812521 and 1168 (collectively referred to as ITP), or as amended hereafter by the Services. The ITP authorizes the incidental take of certain federally listed threatened and endangered species, as specified in the ITP conditions. All HCP materials, including the ITP, are available for review at the State's Regional Offices and the administrative headquarters in Olympia, Washington.

By signing this contract, Purchaser agrees to comply with the terms and conditions of the ITP, and the HCP, which shall become terms of this contract. The State agrees to authorize the lawful activities of the Purchaser carried out pursuant to this contract, PROVIDED the Purchaser remains in compliance with the terms and conditions of both the HCP and ITP. The requirements set forth in this contract are intended to comply with the terms and conditions of the HCP and ITP. Accordingly, non-compliance with the terms and conditions of the HCP and ITP will render the authorization provided in this paragraph void, be deemed a breach of the contract and may subject Purchaser to liability for violation of the Endangered Species Act.

Any modifications to the contract shall be proposed in writing by Purchaser, shall continue to meet the terms and conditions of the HCP and ITP, and shall require the prior written approval of the Region Manager before taking effect.

G-063 Incidental Take Permit Notification Requirements

- a. Purchaser shall immediately notify the Contract Administrator of new locations of permit species covered by the Incidental Take Permits (ITP) that are discovered within the area covered by the State's Habitat Conservation Plan (HCP), including, but not limited to: locations of occupied murrelet habitat; spotted owl nest sites; wolves; grizzly bears; nests, communal roosts,

or feeding concentrations of bald eagles; peregrine falcon nests; Columbian white-tailed deer; Aleutian Canada geese; Oregon silverspot butterflies; and additional stream reaches found to contain bull trout. Purchaser is required to notify the Contract Administrator upon discovery of any fish species found in streams or bodies of water classified as non-fish bearing. In all circumstances, notification must occur within a 24 hour time period.

- b. Upon locating any live, dead, injured, or sick specimens of any permit species covered by the ITP, Purchaser shall immediately notify the Contract Administrator. Purchaser shall notify the Contract Administrator if there is any doubt as to the identification of a discovered permit species. Purchaser may be required to take certain actions to help the Contract Administrator safeguard the well-being of any live, injured or sick specimens of any permit species discovered, until the proper disposition of such specimens can be determined by the Contract Administrator. Any such requirements will be explained to Purchaser by the Contract Administrator during the Pre-Work Conference. In all circumstances, notification must occur within a 24 hour time period.
- c. Purchaser shall refer to a specific ITP number, PRT-812521 or ITP 1168 (copies which are located in the region office) in all correspondence and reports concerning permit activities.
- d. Provisions and requirements of the ITP shall be clearly presented and explained to Purchaser by Contract Administrator during the Pre-Work Conference as per contract clause G-330. All applicable provisions of the ITP and this schedule must be presented and clearly explained by Purchaser to all authorized officers, employees, contractors, or agents of Purchaser conducting authorized activities in the timber sale area. Any questions Purchaser may have about the ITP should be directed to the Contract Administrator.

#### G-064 Permits

Purchaser is responsible for obtaining any permits not already obtained by the State that relate to Purchaser's operation. Forest Practice Application / Hydraulic Project Approval permits obtained by the State shall be transferred to Purchaser. Purchaser is responsible for all permits, amendments and renewals.

#### G-065 Regulatory Disclaimer

The State disclaims any responsibility for, or liability relating to, regulatory actions by any government agency, including actions pursuant to the Forest Practices Act, Ch. 76.09 RCW that may affect the operability of the timber sale.

#### G-066 Governmental Regulatory Actions

- a. Risk

Purchaser shall be responsible for any increased operational costs arising from any applicable foreign or domestic governmental regulation or order that does

not cause contract performance to become commercially impracticable or that does not substantially frustrate the purpose of the contract. If impracticability or frustration results from Purchaser's failure to comply with this contract, Purchaser shall remain responsible for payment of the total contract price notwithstanding the impracticability or frustration.

b. Sale Area

When portions of the sale area become subject to a foreign or domestic governmental regulation or order that will likely prevent timber harvest for a period that will exceed the expiration date of this contract, and Purchaser has complied with this contract, the following shall apply:

- i. RCW 79.15.140 shall govern all adjustments to the contract area.

c. Adjustment of Price

The State shall adjust the total contract price by subtracting from the total contract price an amount determined in the following manner: The State shall cause the timber sale area subject to governmental regulation or order to be measured. The State shall calculate the percentage of the total sale area subject to the governmental regulation or order. The State shall reduce the total contract price by that calculated percentage. However, variations in species, value, costs, or other items pertaining to the affected sale area will be analyzed and included in the adjustment if deemed appropriate by the State. The State will further reduce the total contract price by the reasonable cost of unamortized roads Purchaser constructed but was unable to fully use for removing timber. A reduction in total contract price terminates all of the Purchaser's rights to purchase and remove the timber and all other interest in the affected sale area.

G-070 Limitation on Damage

In the event of a breach of any provision of this contract by the State, the exclusive remedy available to Purchaser will be limited to a return of the initial deposit, unapplied payments, and credit for unamortized improvements made by Purchaser. The State shall not be liable for any damages, whether direct, incidental or consequential.

G-080 Scope of State Advice

No advice by any agent, employee, or representative of the State regarding the method or manner of performing shall constitute a representation or warranty that said method, manner or result thereof will conform to the contract or be suitable for Purchaser's purposes under the contract. Purchaser's reliance on any State advice regarding the method or manner of performance shall not relieve Purchaser of any risk or obligation under the contract. Purchaser retains the final responsibility for its operations under this contract and State shall not be liable for any injuries resulting from Purchaser's reliance on any State advice regarding the method or manner of performance.

**G-091 Sale Area Adjustment**

The Parties may agree to adjustments in the sale area boundary. The cumulative changes to the sale area during the term of the contract shall not exceed more than four percent of the original sale area. If the sale area is increased, the added forest products become a part of this contract. The State shall determine the volume added and shall calculate the increase to the total contract price using the rates set forth in clause G-101, G-102, or G-103. If the sale area is reduced, the State shall determine the volume to be reduced. The State shall calculate the reduction to the total contract price using the rates set forth in clause G-101, G-102, or G-103.

**G-101 Forest Products Not Designated**

Any forest products not designated for removal, which must be removed in the course of operations authorized by the State, shall be approved and designated by the Contract Administrator. Added forest products become a part of this contract and the Scribner log scale volume, as defined by the Northwest Log Rules Advisory Group, shall be determined by the Contract Administrator. Added forest products shall be paid for at the following contract payment rates per Mbf Scribner log scale.

The pricing schedule has not been set for the sale.

**G-106 Adding Naturally Damaged Forest Products**

Any forest products not designated for removal that are seriously damaged by disease, insects or wind, or that may contribute seriously to the spread of insect or disease damage may be added to this sale by the State's Contract Administrator. Additions must be in unlogged areas of the sale and added volume shall not exceed an amount equal to 10 percent of the original advertised volume. Added forest products become a part of this contract and shall be paid for at the rate set forth in clause G-101, G-102 or G-103.

**G-111 Title and Risk of Loss**

Title to the forest products under this contract passes to the Purchaser after they are removed from the sale area, if adequate advance payment or payment security has been provided to the State under this contract. Purchaser bears all risk of loss of, or damage to, and has an insurable interest in, the forest products described in this contract from the time the sale is confirmed under RCW 79.15.120. Breach of this contract shall have no effect on this provision.

**G-116 Sustainable Forestry Initiative® (SFI) Certification**

Forest products purchased under this contract are certified as being in conformance with the Sustainable Forestry Initiative program Standard under certificate number: BV-SFIS-US09000572.

Purchaser shall have at least one person regularly on-site during active operations that have completed training according to the requirements outlined within the SFI® program Standard. Purchaser shall designate in writing the name(s) of the individual(s) who will be on-site and provide proof of their successful completion of an approved training program prior to active operations.

## G-120 Responsibility for Work

All work, equipment, and materials necessary to perform this contract shall be the responsibility of Purchaser. Any damage to improvements, except as provided in clause G-121 or unless the State issues an operating release pursuant to clause G-280, shall be repaired promptly to the satisfaction of the State and at Purchaser's expense.

## G-121 Exceptions

Exceptions to Purchaser's responsibility in clause G-120 shall be limited exclusively to the following. These exceptions shall not apply where road damage occurs due to Purchaser's failure to take reasonable precautions or to exercise sound forest engineering and construction practices.

Road is defined as the road bed, including but not limited to its component parts, such as subgrade, ditches, culverts, bridges, and cattle guards.

For the purposes of this clause, damage will be identified by the State and is defined as:

1. Failure of (a) required improvements or roads designated in clause C-050, or (b) required or optional construction completed to the point that authorization to haul has been issued;
2. Caused by a single event from forces beyond the control of Purchaser, its employees, agents, or invitees, including independent contractors; and
3. Includes, but is not limited to natural disasters such as earthquakes, volcanic eruptions, landslides, and floods.

The repair work identified by the State shall be promptly completed by Purchaser at an agreed price. The State may elect to accomplish repairs by means of State-provided resources. The State will bear the cost to repair damages caused by a third party. In all other cases, the Purchaser shall bear responsibility for the costs as described below.

For each event, Purchaser shall be solely responsible for the initial \$5,000 in repairs. For repairs in excess of \$5,000, the parties shall share equally the portion of costs between \$5,000 and \$15,000. The State shall be solely responsible for the portion of the cost of repairs that exceed \$15,000.

Nothing contained in clauses G-120 and G-121 shall be construed as relieving Purchaser of responsibility for, or damage resulting from, Purchaser's operations or negligence, nor shall Purchaser be relieved from full responsibility for making good any defective work or materials. Authorization to haul does not warrant that Purchaser built roads are free from material defect and the State may require additional work, at Purchaser's expense regardless of cost, to remedy deficiencies at any time.

## G-140 Indemnity

To the fullest extent permitted by law, Purchaser shall indemnify, defend and hold harmless State, agencies of State and all officials, agents and employees of State, from and against all claims arising out of or resulting from the performance of the contract. "Claim" as used in this contract means any financial loss, claim, suit, action, damage, or expense, including but not limited to attorneys' fees, attributable for bodily injury, sickness, disease or death, or injury to or destruction of tangible property including loss of use resulting therefrom. Purchasers' obligations to indemnify, defend, and hold harmless includes any claim by Purchasers' agents, employees, representatives, or any subcontractor or its employees. Purchaser expressly agrees to indemnify, defend, and hold harmless State for any claim arising out of or incident to Purchasers' or any subcontractors' performance or failure to perform the contract. Purchasers' obligation to indemnify, defend, and hold harmless State shall not be eliminated or reduced by any actual or alleged concurrent negligence of State or its agents, agencies, employees and officials. Purchaser waives its immunity under Title 51 RCW to the extent it is required to indemnify, defend and hold harmless State and its agencies, officials, agents or employees.

## G-150 Insurance

Purchaser shall, at its cost and expense, buy and maintain insurance of the types and amounts listed below. Failure to buy and maintain the required insurance may result in a breach and/or termination of the contract at State's option. State may suspend Purchaser operations until required insurance has been secured.

All insurance and surety bonds should be issued by companies admitted to do business within the State of Washington and have a rating of A-, Class VII or better in the most recently published edition of Best's Reports. If an insurer is not admitted, all insurance policies and procedures for issuing the insurance policies must comply with Chapter 48.15 RCW and 284-15 WAC.

The State of Washington, Department of Natural Resources region office of sale origin shall be provided written notice before cancellation or non-renewal of any insurance referred to therein, in accord with the following specifications:

1. Insurers subject to Chapter 48.18 RCW (admitted and regulated by the Insurance Commissioner): The insurer shall give the State 45 days advance notice of cancellation or non-renewal. If cancellation is due to non-payment of premium, the State shall be given 10 days advance notice of cancellation.
2. Insurers subject to Chapter 48.15 RCW (surplus lines): The State shall be given 20 days advance notice of cancellation. If cancellation is due to non-payment of premium, the State shall be given 10 days advance notice of cancellation.

Before starting work, Purchaser shall furnish State of Washington, Department of Natural Resources with a certificate(s) of insurance, executed by a duly authorized

representative of each insurer, showing compliance with the insurance requirements specified in the contract. Insurance coverage shall be obtained by the Purchaser prior to operations commencing and continually maintained in full force until all contract obligations have been satisfied or an operating release has been signed by the State.

Purchaser shall include all subcontractors as insured under all required insurance policies, or shall furnish separate certificates of insurance and endorsements for each subcontractor. Subcontractor(s) must comply fully with all insurance requirements stated herein. Failure of subcontractor(s) to comply with insurance requirements does not limit Purchaser's liability or responsibility.

The State of Washington, Department of Natural Resources, its elected and appointed officials, agents and employees shall be named as an additional insured via endorsement on all general liability, excess, umbrella, and property insurance policies.

All insurance provided in compliance with this contract shall be primary as to any other insurance or self-insurance programs afforded to or maintained by State. Purchaser waives all rights against State for recovery of damages to the extent these damages are covered by general liability or umbrella insurance maintained pursuant to this contract.

By requiring insurance herein, State does not represent that coverage and limits will be adequate to protect Purchaser and such coverage and limits shall not limit Purchaser's liability under the indemnities and reimbursements granted to State in this contract.

The limits of insurance, which may be increased as deemed necessary by State of Washington, Department of Natural Resources, shall not be less than as follows:

Commercial General Liability (CGL) Insurance. Purchaser shall maintain general liability (CGL) insurance, and, if necessary, commercial umbrella insurance with a limit of not less than \$1,000,000.00 per each occurrence. If such CGL insurance contains aggregate limits, the General Aggregate limit shall be at least twice the "each occurrence" limit. CGL insurance shall have products-completed operations aggregate limit of at least two times the "each occurrence" limit. CGL coverage shall include a Logging and Lumbering Endorsement (i.e. Logger's Broad-Form) to cover the events that include, but are not limited to, fire suppression expenses, accidental timber trespasses, and wildfire property damage with limits of not less than \$2,000,000.00 each occurrence.

CGL insurance shall be written on Insurance Services Office (ISO) occurrence form CG 00 01 (or a substitute form providing equivalent coverage). All insurance shall cover liability arising out of premises, operations, independent contractors, products completed operations, personal injury and advertising injury, and liability assumed under an insured contract (including the tort liability of another party assumed in a business contract), and contain separation of insured (cross liability) condition.

Employer's Liability "Stop Gap" Insurance. Purchaser shall buy employers liability insurance, and, if necessary, commercial umbrella liability insurance with limits not less than \$1,000,000.00 each accident for bodily injury by accident or \$1,000,000.00 each employee for bodily injury by disease.

Workers' Compensation Coverage. Purchaser shall comply with all State of Washington workers' compensation statutes and regulations. Workers' compensation coverage shall be provided for all employees of Purchaser and employees of any subcontractor or sub-subcontractor. Coverage shall include bodily injury (including death) by accident or disease, which exists out of or in connection with the performance of this contract. Except as prohibited by law, Purchaser waives all rights of subrogation against State for recovery of damages to the extent they are covered by workers' compensation, employer's liability, commercial general liability, or commercial umbrella liability insurance.

If Purchaser, subcontractor or sub-subcontractor fails to comply with all State of Washington workers' compensation statutes and regulations and State incurs fines or is required by law to provide benefits to or obtain coverage for such employees, Purchaser shall indemnify State. Indemnity shall include all fines, payment of benefits to Purchaser or subcontractor employees, or their heirs or legal representatives, and the cost of effecting coverage on behalf of such employees.

Business Auto Policy (BAP). Purchaser shall maintain business auto liability and, if necessary, commercial umbrella liability insurance with a limit not less than \$1,000,000.00 per accident. Such insurance shall cover liability arising out of "Any Auto". Business auto coverage shall be written on ISO form CA 00 01, or substitute liability form providing equivalent coverage. If necessary the policy shall be endorsed to provide contractual liability coverage and cover a "covered pollution cost or expense" as provided in the 1990 or later editions of CA 00 01. Purchaser waives all rights against State for the recovery of damages to the extent they are covered by business auto liability or commercial umbrella liability insurance.

#### G-160 Agents

The State's rights and duties will be exercised by the Region Manager at Forks, Washington. The Region Manager will notify Purchaser in writing who is responsible for administering the contract. The Region Manager has sole authority to waive, modify, or amend the terms of this contract in the manner prescribed in clause G-180. No agent, employee, or representative of the State has any authority to bind the State to any affirmation, representation, or warranty concerning the forest products conveyed beyond the terms of this contract.

Purchaser is required to have a person on site during all operations who is authorized to receive instructions and notices from the State. Purchaser shall inform the State in writing who is authorized to receive instructions and notices from the State, and any limits to this person's authority.

**G-170 Assignment and Delegation**

No rights or interest in this contract shall be assigned by Purchaser without prior written permission of the State. Any attempted assignment shall be void and ineffective for all purposes unless made in conformity with this paragraph. Purchaser may perform any duty through a delegate, but Purchaser is not thereby relieved of any duty to perform or any liability. Any assignee or delegate shall be bound by the terms of the contract in the same manner as Purchaser.

**G-180 Modifications**

Waivers, modifications, or amendments of the terms of this contract must be in writing signed by Purchaser and the State.

**G-190 Contract Complete**

This contract is the final expression of the Parties' agreement. There are no understandings, agreements, or representations, expressed or implied, which are not specified in this contract.

**G-200 Notice**

Notices required to be given under the following clauses shall be in writing and shall be delivered to Purchaser's authorized agent or sent by certified mail to Purchaser's address of record:

G-210 Violation of Contract

G-220 State Suspends Operations

All other notices required to be given under this contract shall be in writing and delivered to the authorized agent or mailed to the Party's post office address. Purchaser agrees to notify the State of any change of address.

**G-210 Violation of Contract**

- a. If Purchaser violates any provision of this contract, the Contract Administrator, by written notice, may suspend those operations in violation. If the violation is capable of being remedied, Purchaser has 30 days after receipt of a suspension notice to remedy the violation. If the violation cannot be remedied (such as a violation of WAC 240-15-015) or Purchaser fails to remedy the violation within 30 days after receipt of a suspension notice, the State may terminate the rights of Purchaser under this contract and collect damages.
- b. If the contract expires pursuant to clause G-030 or G-031 without Purchaser having performed all its duties under this contract, Purchaser's right to operate is terminated and Purchaser shall not have the right to remedy the breach. This provision shall not relieve Purchaser of any payment obligations.
- c. The State has the right to remedy the breach in the absence of any indicated attempt by Purchaser or if Purchaser is unable, as determined by the State, to

remedy the breach. Any expense incurred by the State shall be charged to Purchaser and shall be paid within 30 days of receipt of billing.

- d. If Purchaser's violation is a result of a failure to make a payment when due, in addition to a. and b. above, interest shall accrue on the unpaid balance at 12 percent per annum, beginning the date payment was due.

#### G-220 State Suspends Operation

The Contract Administrator may suspend any operation of Purchaser under this contract when the State is suffering, or there is a reasonable expectation the State will suffer environmental, monetary, or other damage if the operation is allowed to continue.

Purchaser shall be in breach of this contract if the operation continues after the suspension notice or if the operation resumes without prior approval and notice from the Contract Administrator.

Purchaser may request a modification of a suspension within 30 days of the start of suspension through the dispute resolution process in clause G-240. If this process results in a finding that the suspension exceeded the time reasonably necessary to stop or prevent damage to the State, Purchaser is entitled to request a contract term adjustment under clause G-040.

If it reasonably appears that the damage that the State is suffering, or can reasonably be expected to suffer if the operation is allowed to continue, will prevent harvest for a period that will exceed 6 months, and Purchaser has complied with this contract, the provisions of clause G-066 shall govern just as if the harvest was prevented by an applicable foreign or domestic governmental regulation or order.

#### G-230 Unauthorized Activity

Any cutting, removal, or damage of forest products by Purchaser, its employees, agents, or invitees, including independent contractors, in a manner inconsistent with the terms of this contract or State law, is unauthorized. Such activity may subject Purchaser to liability for triple the value of said forest products under RCW 79.02.320 or RCW 79.02.300 and may result in prosecution under RCW 79.02.330 or other applicable statutes.

#### G-240 Dispute Resolution

The following procedures apply in the event of a dispute regarding interpretation or administration of this contract and the parties agree that these procedures must be followed before a lawsuit can be initiated.

- a. In the event of a dispute, Purchaser must make a written request to the Region Manager for resolution prior to seeking other relief.
- b. The Region Manager will issue a written decision on Purchaser's request within ten business days.

- c. Within ten business days of receipt of the Region Manager's decision, Purchaser may make a written request for resolution to the Deputy Supervisor - Uplands of the Department of Natural Resources.
- d. Unless otherwise agreed, a conference will be held by the Deputy Supervisor - Uplands within 30 calendar days of the receipt of Purchaser's request for review of the Region Manager's written decision. Purchaser and the Region Manager will have an opportunity to present their positions. The Deputy Supervisor - Uplands will issue a decision within a reasonable time of being presented with both Parties' positions.

G-250 Compliance with All Laws

Purchaser shall comply with all applicable statutes, regulations and laws, including, but not limited to; chapter 27.53 RCW, chapter 68.50 RCW, WAC 240-15 and WAC 296-54. Failure to comply may result in forfeiture of this contract.

G-260 Venue

This contract shall be governed by the laws of the State of Washington. In the event of a lawsuit involving this contract, venue shall be proper only in Thurston County Superior Court.

G-270 Equipment Left on State Land

All equipment owned or in the possession of Purchaser, its employees, agents, or invitees, including independent contractors, shall be removed from the sale area and other State land by the termination date of this contract. Equipment remaining unclaimed on State land 60 days after the expiration of the contract period is subject to disposition as provided by law. Purchaser shall pay to the State all costs of moving, storing, and disposing of such equipment. The State shall not be responsible for any damages to or loss of the equipment or damage caused by the moving, storing or disposal of the equipment.

G-280 Operating Release

An operating release is a written document, signed by the State and Purchaser, indicating that Purchaser has been relieved of certain rights or responsibilities with regard to the entire or a portion of the timber sales contract. Purchaser and State may agree to an operating release for this sale, or portion of this sale, prior to the contract expiration, when all contract requirements pertaining to the release area have been satisfactorily completed. Upon issuance of a release, Purchaser's right to cut and remove forest products on the released area will terminate.

G-310 Road Use Authorization

Purchaser is authorized to use the following State roads and roads for which the State has acquired easements and road use permits; D-2000, D-2090, D-2093, D-2093.1, D-5200, D-5201, D-2900, D-2980, D-2990, RY-9000, RY- 9000.6, RY-9000.61, RY-9009, 1+00 Spur, 2+50 Spur, 4+00 Spur, 6+00 Spur, 6+90 Spur, 7+00 Spur, Loop Pit

Access Road and Thunder Pit Access Road. The State may authorize in writing the use of other roads subject to fees, restrictions, and prior rights.

G-330 Pre-work Conference

Purchaser shall arrange with the Contract Administrator to review this contract and to examine the sale area before beginning any operations. A plan of operations shall be developed and agreed upon by the Contract Administrator and Purchaser before beginning any operations. To the extent that the plan of operations is inconsistent with the contract, the terms of the contract shall prevail. State's acceptance and approval of Purchaser's plan of operations shall not be construed as any statement or warranty that the plan of operations is adequate for Purchaser's purposes or complies with applicable laws.

G-340 Preservation of Markers

Any legal land subdivision survey corners and witness objects are to be preserved. If such are destroyed or disturbed, the Purchaser shall, at the Purchaser's own expense, re-establish them through a licensed land surveyor in accordance with U.S. General Land Office standards. Corners and/or witness objects that must be disturbed or destroyed in the process of road construction or logging shall be adequately referenced and/or replaced in accordance with RCW 58.24.040(8). Such references must be approved by the Contract Administrator prior to removal of said corners and/or witness objects.

G-360 Road Use Reservation

The State shall have the right to use, without charge, all existing roads and any road constructed or reconstructed on State lands by Purchaser under this contract. The State may extend such rights to others. If the State grants such rights to others, the State shall require performance or payment, as directed by the State, for their proportionate share of maintenance based on their use.

G-370 Blocking Roads

Purchaser shall not block the D-2000, D-5200 or the RY-9000 Roads, unless authority is granted in writing by the Contract Administrator.

G-380 Road Easement and Road Use Permit Requirements

Purchaser agrees to comply with the terms and conditions of the attached:

Easement #55-000050 with Rayonier

RUP #55-098892 with Rayonier

G-430 Open Fires

Purchaser shall not set, or allow to be set by Purchaser's employees, agents, invitees and independent contractors, any open fire at any time of the year without first obtaining permission, in writing, from the Contract Administrator.

G-450 Encumbrances

This contract and Purchaser's activities are subject to the following:

## DATA MISSING

## Section P: Payments and Securities

## P-011 Initial Deposit

Purchaser paid DATA MISSING initial deposit, which will be maintained pursuant to RCW 79.15.100(3). If the operating authority on this contract expires without Purchaser's payment of the full amount specified in Clause P-020, the initial deposit will be immediately forfeited to the State, and will be offset against Purchaser's remaining balance due. Any excess initial deposit funds not needed to ensure full payment of the contract price, or not needed to complete any remaining obligations of the Purchaser existing after contract expiration, will be refunded to the Purchaser.

## P-020 Payment for Forest Products

Purchaser agrees to pay the total, lump sum contract price of \$112,190.00. The total contract price consists of a \$0.00 contract bid price plus \$112,190.00 in fees. Fees collected shall be retained by the state unless the contract is adjusted via the G-066 clause. Purchaser shall be liable for the entire purchase price, and will not be entitled to any refunds or offsets unless expressly stated in this contract.

THE PURCHASE PRICE SHALL NOT BE AFFECTED BY ANY FACTORS, INCLUDING: the amount of forest products actually present within the contract area, the actual acreage covered by the contract area, the amount or volume of forest products actually cut or removed by purchaser, whether it becomes physically impossible or uneconomic to remove the forest products, and whether the subject forest products have been lost or damaged by fire or any other cause. The only situations Purchaser may not be liable for the full purchase price are governed by clause G-066, concerning governmental regulatory actions taken during the term of the contract.

## P-045 Guarantee of Payment

Purchaser will pay for forest products prior to cutting or will guarantee payment by posting an approved payment security. The amount of cash or payment security shall be determined by the State and shall equal or exceed the value of the cutting proposed by Purchaser.

## P-050 Billing Procedure

The State will compute and forward to Purchaser statements of charges provided for in the contract. Purchaser shall deliver payment to the State on or before the date shown on the billing statement.

## P-080 Payment Account Refund

Advance payments made under P-045 or P-045.2 remaining on account above the value for the charges shall be returned to Purchaser within 30 days following the final report of charges. Refunds not made within the 30 day period will accrue interest at the interest rate, as established by WAC 332-100-030, computed on a daily basis until paid.

## P-090 Performance Security

Purchaser agrees to furnish, within 30 days of the confirmation date, security acceptable to the State in the amount of \$100,000.00. The Security provided shall guarantee performance of all provisions of this contract and payment of any damages caused by operations under this contract or resulting from Purchaser's noncompliance with any rule or law. Acceptable performance security may be in the form of a performance bond, irrevocable letter of credit, cash, savings or certificate of deposit account assignments, and must name the State as the obligee or beneficiary. A letter of credit must comply with Title 62A RCW, Article 5. Performance security must remain in full force over the duration of the contract length. Surety bonds issued shall conform to the issuance and rating requirements in clause G-150. The State shall retain the performance security pursuant to RCW 79.15.100. Purchaser shall not operate unless the performance security has been accepted by the State. If at any time the State decides that the security document or amount has become unsatisfactory, Purchaser agrees to suspend operations and, within 30 days of notification, to replace the security with one acceptable to the State or to supplement the amount of the existing security.

## P-100 Performance Security Reduction

The State may reduce the performance security after an operating release has been issued if the State determines that adequate security exists for any remaining obligations of Purchaser.

## Section H: Harvesting Operations

## H-001 Operations Outside the Sale Boundaries

No operations shall occur outside the sale boundaries, as described within the contract, unless approved in writing by the State.

## H-013 Reserve Tree Damage Definition

Reserve trees are trees required and designated for retention within the sale boundary. Purchaser shall protect reserve trees from being cut, damaged, or removed during operations.

Reserve tree damage exists when one or more of the following criteria occur as a result of Purchaser's operation, as determined by the Contract Administrator:

- a. A reserve tree has one or more scars on its trunk exposing the cambium layer, which in total exceeds 100 square inches.
- b. A reserve tree top is broken or the live crown ratio is reduced below 30 percent.
- c. A reserve tree has more than 1/3 of the circumference of its root system injured such that the cambium layer is exposed.

If the Contract Administrator determines that a reserve tree has been cut or damaged, the Purchaser shall provide a replacement reserve tree of like condition, size, and

species within the sale unit containing the damaged leave tree, as approved by the Contract Administrator. Purchaser may be required to pay liquidated damages for Excessive Reserve Tree Damage as detailed in clause D-041.

Removal of designated reserve trees from the sale area is unauthorized, and may invoke the use of the G-230 'Trespass and Unauthorized Activity' clause. Purchaser is required to leave all cut or damaged reserve trees on site.

H-017 Preventing Excessive Soil Disturbance

Operations may be suspended when soil rutting exceeds 12 inches as measured from the natural ground line. To reduce soil damage, the Contract Administrator may require water bars to be constructed, grass seed to be placed on exposed soils, or other mitigation measures. Suspended operations shall not resume unless approval to do so has been given, in writing, by the Contract Administrator.

H-035 Fall Trees Into Sale Area

Trees shall be felled into the sale area unless otherwise approved by the Contract Administrator.

H-040 Purchaser Harvest Plan

Purchaser shall, as part of the plan of operations, prepare an acceptable harvest plan for utilizing rubber tire skidders in sale area. The plan shall address the location and timing of desired use, which are part(s) of this contract. The harvest plan shall be approved by the Contract Administrator prior to beginning the harvest operation. Purchaser shall not deviate from the harvest plan without prior written approval by the Contract Administrator.

H-051 Branding and Painting

Purchaser shall provide a State of Washington registered log brand, acceptable to the State, unless the State agrees to furnish the brand. All purchased timber shall be branded in a manner that meets the requirements of WAC 240-15-030(2)(a)(i). All timber purchased under a contract designated as export restricted shall also be painted in a manner that meets the requirements of WAC 240-15-030(2)(a)(ii).

For pulp loads purchased under a contract designated as export restricted, Purchaser shall brand at least 3 logs with legible brands at one end. Also, 10 logs shall be painted at one end with durable red paint.

H-080 Snags Not to be Felled

Snags not required to be felled for safety reasons may be left standing. Snags felled for safety reasons shall not be removed and must remain where felled.

H-120 Harvesting Equipment

Forest products sold under this contract shall be harvested and removed using ground based methods, with rubber tire skidders allowed only if rutting and skidding requirements can be met and a harvest plan is submitted and approved. Authority to use

other equipment or to operate outside the equipment specifications detailed above must be approved in writing by the State.

#### H-130 Hauling Schedule

The hauling of forest products will not be permitted on the D-2093 (stations 0+00 - 14+75), D-2093.1 (stations 0+00 - 12+50), and the D-5201 (stations 11+75 - 21+25) from October 31 to June 1 unless authorized in writing by the Contract Administrator.

#### H-140 Special Harvest Requirements

Purchaser shall accomplish the following during the harvest operations:

1. Purchaser shall immediately repair all gate damage resulting from operations to an equal or better condition than existed at the time of the sale.
2. While felling timber, two warning signs must be posted on the RY-9000.
3. Yarding equipment shall not cross live streams without an FPHP.
4. The Purchaser shall notify all employees and contractors working on this sale that any danger tree, marked or unmarked, may be felled. Any felled danger shall be replaced with a suitable tree of similar size and species as approved by the Contract Administrator.

Permission to do otherwise must be granted in writing by the Contract Administrator.

#### H-190 Completion of Settings

Operations begun on any setting of the sale area shall be completed before any operation begins on subsequent settings unless authorized in writing by the Contract Administrator.

#### H-220 Protection of Residual or Adjacent Trees

Unless otherwise specified by this contract, the Contract Administrator shall identify damaged adjacent or leave trees that shall be paid for according to clause G-230.

#### H-230 Tops and Limbs Outside the Sale Boundary

Tops and limbs outside the sale boundary as a result of Purchaser's operation shall be removed concurrently with the yarding operation unless otherwise directed by the Contract Administrator.

### Section C: Construction and Maintenance

#### C-040 Road Plan

Road construction and associated work provisions of the Road Plan for this sale, dated 8/30/2019 are hereby made a part of this contract.

#### C-050 Purchaser Road Maintenance and Repair

Purchaser shall perform work at their own expense on the D-2090, D-2093, D-2093.1, D-5201, D-2900, D-2980, D-2990, RY- 9000.6, RY-9000.61, RY-9009, 1+00 Spur,

2+50 Spur, 4+00 Spur, 6+00 Spur, 6+90 Spur, and the 7+00 Spur. All work shall be completed to the specifications detailed in the Road Plan.

C-060 Designated Road Maintainer

If required by the State, Purchaser shall perform maintenance and replacement work as directed by the Contract Administrator on the D-2000, D-5200, RY-9000, Thunder Pit Access Road and Loop Pit access road. Purchaser shall furnish a statement in a form satisfactory to the State showing the costs incurred while performing this work. Costs shall be based on the rates set forth in the equipment rate schedule on file at the Region office or Engineering Division in Olympia. The State shall reimburse Purchaser for said costs within 30 days of receipt and approval of the statement.

C-140 Water Bars

Purchaser shall, as directed by the Contract Administrator, construct water bars across haul roads, skid trails and fire trails as necessary to control soil erosion and water pollution.

Section S: Site Preparation and Protection

S-001 Emergency Response Plan

An Emergency Response Plan (ERP) shall be provided to the Contract Administrator containing but not limited to, valid contact numbers and procedures for medical emergencies, fire, hazardous spills, forest practice violations and any unauthorized or unlawful activity on or in the vicinity of the sale area. The Contract Administrator and the State shall be promptly notified whenever an incident occurs requiring an emergency response.

The ERP must be presented for inspection at the prework meeting and kept readily available to all personnel, including subcontractors, on site during active operations.

S-010 Fire Hazardous Conditions

Purchaser acknowledges that operations under this Contract may increase the risk of fire. Purchaser shall conduct all operations under this agreement following the requirements of WAC 332-24-005 and WAC 332-24-405 and further agrees to use the highest degree of care to prevent uncontrolled fires from starting.

In the event of an uncontrolled fire, Purchaser agrees to provide equipment and personnel working at the site to safely and effectively engage in first response fire suppression activity.

Purchaser's failure to effectively engage in fire-safe operations is considered a breach and may result in suspension of operations.

S-030 Landing Debris Clean Up

Landing debris shall be disposed of in a manner approved in writing by the Contract Administrator.

## S-035 Logging Debris Clean Up

Slash and debris created from harvest activities shall be treated in a manner approved in writing by the Contract Administrator.

## S-050 Cessation of Operations for Low Humidity

When the humidity is 30 percent or lower on the sale area, all operations must cease unless authority to continue is granted by the State in writing.

## S-060 Pump Truck or Pump Trailer

Purchaser shall provide a fully functional pump truck or pump trailer equipped to meet the specifications of WAC 332-24-005 and WAC 332-24-405 during the "closed season" or as extended by the State and shall provide trained personnel to operate this equipment on the sale area during all operating periods.

## S-100 Stream Cleanout

Slash or debris which enters any typed waters as a result of operations under this contract and which is identified by the Contract Administrator shall be removed and deposited in a stable position. Removal of slash or debris shall be accomplished in a manner that avoids damage to the natural stream bed and bank vegetation.

## S-110 Resource Protection

No equipment may operate within 30' of any typed waters, unless authority is granted in writing by the Contract Administrator.

## S-130 Hazardous Materials

## a. Hazardous Materials and Waste - Regulatory Compliance

Purchaser is responsible for understanding and complying with all applicable local, state, and federal hazardous material/waste laws and regulations for operations conducted under this contract. Such regulations pertain to, but may not be limited to, hazardous material storage, handling and transport, personnel protection, release notification and emergency response, cleanup and waste disposal. Purchaser shall be responsible for restoring the site in the event of a spill.

## b. Hazardous Materials Spill Prevention

All operations shall be conducted in a manner that avoids the release of hazardous materials, including petroleum products, into the environment (water, air or land).

## c. Hazardous Materials Spill Containment, Control and Cleanup

If safe to do so, Purchaser shall take immediate action to contain and control all hazardous material spills. Purchaser shall ensure that enough quick response spill kits capable of absorbing 10 gallons of oil, coolant, solvent or contaminated water are available on site to quickly address potential spills

from any piece of equipment at all times throughout active operations. If large quantities of bulk fuel/other hazardous materials are stored on site, Purchaser must be able to effectively control a container leak and contain & recover a hazmat spill equal to the largest single on site storage container volume. (HAZWOPER reg. 29CFR 1910.120 (j) (1) (vii)).

d. Hazardous Material Release Reporting

Releases of oil or hazardous materials to the environment must be reported according to the State Department of Ecology (ECY). It is the responsibility of the Purchaser to have all emergency contact information readily available and a means of remote communication for purposes of quick notification. In the event of a spill, the Purchaser is responsible for notifying the following:

Appropriate Department of Ecology regional office (contact information below).

DNR Contract Administrator

ECY - Northwest Region:

1-425-649-7000

(Island, King, Kitsap, San Juan, Skagit, Snohomish, and Whatcom counties)

ECY - Southwest Region:

1-360-407-6300

(Clallam, Clark, Cowlitz, Grays Harbor, Jefferson, Mason, Lewis, Pacific, Pierce, Skamania, Thurston, and Wahkiakum counties)

ECY - Central Region:

1-509-575-2490

(Benton, Chelan, Douglas, Kittitas, Klickitat, Okanogan, and Yakima counties)

ECY - Eastern Region:

1-509-329-3400

(Adams, Asotin, Columbia, Ferry, Franklin, Garfield, Grant, Lincoln, Pend Oreille, Spokane, Stevens, Walla Walla, and Whitman counties)

S-131 Refuse Disposal

As required by RCW 70.93, All Purchaser generated refuse shall be removed from state lands for proper disposal prior to termination of this contract. No refuse shall be burned, buried or abandoned on state forest lands. All refuse shall be transported in a manner such that it is in compliance with RCW 70.93 and all loads or loose materials shall be covered/secured such that these waste materials are properly contained during transport.

Section D: Damages

D-013 Liquidated Damages or Failure to Perform

The following clauses provide for payments by Purchaser to the State for breaches of the terms of this contract other than failure to perform. These payments are agreed to as liquidated damages and not as penalties. They are reasonable estimates of anticipated harm to the State, which will be caused by Purchaser's breach. These liquidated damages provisions are agreed to by the State and Purchaser with the understanding of the difficulty of proving loss and the inconvenience or infeasibility of obtaining an adequate remedy. These liquidated damages provisions provide greater certainty for the Purchaser by allowing the Purchaser to better assess its responsibilities under the contract.

Clause P-020 governs Purchaser's liability in the event Purchaser fails to perform any of the contract requirements other than the below liquidated damage clauses without written approval by the State. Purchaser's failure to pay for all or part of the forest products sold in this contract prior to expiration of the contract term results in substantial injury to the State. Therefore, Purchaser agrees to pay the State the full lump sum contract price in P-020 in the event of failure to perform.

D-041 Reserve Tree Excessive Damage

When Purchaser's operations exceed the damage limits set forth in clause H-013, Reserve Tree Damage Definition, and when the Contract Administrator determines that a suitable replacement for a damaged reserve tree is not possible, the damaged trees result in substantial injury to the State. The value of the damaged reserve trees at the time of the breach is not readily ascertainable. Therefore, the Purchaser agrees to pay the State as liquidated damages at the rate of \$1,000.00 per tree for all damaged reserve trees that are not replaced in all units.

IN WITNESS WHEREOF, the Parties hereto have entered into this contract.

STATE OF WASHINGTON  
DEPARTMENT OF NATURAL RESOURCES

\_\_\_\_\_  
Purchaser

\_\_\_\_\_  
Mona Griswold

\_\_\_\_\_  
Print Name

Olympic Region Manager

Date: \_\_\_\_\_

Date: \_\_\_\_\_

Address:

CORPORATE ACKNOWLEDGEMENT  
(Required for both LLC and Inc. Entities)

STATE OF \_\_\_\_\_ )

COUNTY OF \_\_\_\_\_ )

On this \_\_\_\_\_ day of \_\_\_\_\_, 20\_\_\_\_, before me personally  
appeared \_\_\_\_\_

\_\_\_\_\_ to me known to be the  
\_\_\_\_\_ of the corporation  
that executed the within and foregoing instrument and acknowledged said instrument to be the  
free and voluntary act and deed of the corporation, for the uses and purposes therein mentioned,  
and on oath stated that (he/she was) (they were) authorized to execute said instrument.

IN WITNESS WHEREOF, I have hereunto set my hand and affixed my official seal the day and  
year first above written.

\_\_\_\_\_  
Notary Public in and for the State of

\_\_\_\_\_

My appointment expires \_\_\_\_\_

**Schedule A**  
**SLASH PILING SPECIFICATIONS**

The areas shall be piled by creating circular piles of slash and brush conforming to the following specifications:

- A. Piles shall be a minimum of 12 feet tall by 8 feet wide to a maximum of 30 feet tall and 16 feet wide. Piles shall be cone shaped and stable.
- B. Piles shall be free of topsoil, large rotten logs and large stumps. No material larger than 8 inches in diameter shall be piled. Any burnable material shall be well scattered.
- C. Piles shall not be placed on large stumps or logs.
- D. Piles shall be stacked a minimum of 50 feet from all unit boundaries, Riparian Management Zones, leave trees, and any standing timber; a minimum of 100 feet from any public roads and highways; and a minimum of 200 feet from any structures.
- E. Piling shall be completed using an approved hydraulic shovel and grapples.
- F. Slash and displaced soil shall be removed from swales, irrigation ditches, natural drainage channels, and access roads concurrent with yarding.
- G. Slash shall be placed in skid roads or ahead of machinery. Slash which accumulates on landings and/or roads shall be lopped and scattered within the harvest area or designated by the Contract Administrator.

**Schedule B**  
**GREEN TREE RETENTION PLAN**

Leave the following as directed by the Contract Administrator:

1. All trees marked with a blue band of paint and all leave tree area clumps shall remain standing.

The perimeter of the leave tree clumps are designated by Leave Tree Area tags. The tags face outward from the leave tree clumps.

Unit #	# of Individually Marked Trees	# of Clumps	# of Trees Clumped	Total # of Leave Trees
1	23	1	177	200
2	24	1	240	264
3	20	1	100	120
4	5	1	35	40
5	26	1	200	226
6	10	1	118	128



## WASHINGTON STATE DEPARTMENT OF NATURAL RESOURCES

### FOREST EXCISE TAX ROAD SUMMARY SHEET

**Region:**

**Timber Sale Name:**

**Application Number:**

#### EXCISE TAX APPLICABLE ACTIVITIES

**Construction:** **linear feet**  
*Road to be constructed (optional and required) but not abandoned*

**Reconstruction:** **linear feet**  
*Road to be reconstructed (optional and required) but not abandoned*

**Abandonment:** **linear feet**  
*Abandonment of existing roads not reconstructed under the contract*

**Decommission:** **linear feet**  
*Road to be made undriveable but not officially abandoned.*

**Pre-Haul Maintenance:** **linear feet**  
*Existing road to receive maintenance work (optional and required) prior to haul*

#### EXCISE TAX EXEMPT ACTIVITIES

**Temporary Construction:** **linear feet**  
*Roads to be constructed (optional and required) and then abandoned*

**Temporary Reconstruction:** **linear feet**  
*Roads to be reconstructed (optional and required) and then abandoned*

All parties must make their own assessment of the taxable or non-taxable status of any work performed under the timber sale contract. The Department of Revenue bears responsibility for determining forest road excise taxes. The Department of Natural Resources developed this form to help estimate the impact of forest excise taxes. However, the information provided may not precisely calculate the actual amount of taxes due. The Department of Revenue is available for consultation by calling 1.800.548.8829.  
(Revised 9/18)

## Cruise Narrative

<b>Sale Name:</b> Johnny's Shack	<b>Region:</b> Olympic
<b>Agree. #:</b> 30-099246	<b>District:</b> Coast
<b>Lead cruiser:</b> Dakota Truitt	<b>Completion date:</b> 05/08/19
<b>Other cruisers on sale:</b> Jason Michaud	

**Unit acreage specifications:**

Unit #	Cruised acres	Cruised acres agree with sale acres? Yes/No	If acres do not agree explain why.
1	24	yes	
2	31	yes	
3	12	yes	
4	4.7	yes	
5	23.5	yes	
6	14.5	yes	
7 ROW	2.3	yes	
<b>Total</b>	<b>112</b>	<b>yes</b>	

**Unit cruise specifications:**

Unit #	Sample type (VP, FP, ITS,100%)	Expansion factor (BAF, full/ half)	Sighting height (4.5 ft, 16 ft.)	Grid size (Plot spacing or % of area)	Plot ratio (cruise:coun t)	Total number of plots
1	VP	54.45/ 40	4.5 ft	300x300	1:1	12
2	VP	62.50/ 40	4.5 ft	300x300	1:1	16
3	VP	62.50/ 40	4.5 ft	300x300	1:1	7
4	VP	62.50/ 40	4.5 ft	325x325	1:1	2
5	VP	71.11/ 40	4.5 ft	300x300	1:1	13
6	VP	54.45/ 40	4.5 ft	300x300	1:1	8
7 ROW	100%	SS=1/10 WH=1/5 RA=1/10	N/A	100%	1:10	2

**Sale/Cruise Description:**

<b>Minor species cruise intensity:</b>	Minor species sampled using same cruise plots. Red cedar and Red alder were cruised at a 40 BAF						
<b>Minimum cruise spec:</b>	40% of Form Factor at 16 ft. D.O.B. or 5 inch top or merchantable top						
<b>Avg ring count by sp:</b>	<table style="width: 100%; border: none;"> <tr> <td style="border: none;"><b>DF =</b></td> <td style="border: none;">5</td> <td style="border: none;"><b>WH =</b></td> <td style="border: none;">5</td> <td style="border: none;"><b>SS =</b></td> <td style="border: none;">3</td> </tr> </table>	<b>DF =</b>	5	<b>WH =</b>	5	<b>SS =</b>	3
<b>DF =</b>	5	<b>WH =</b>	5	<b>SS =</b>	3		

<b>Leave/take tree description:</b>	Leave tree areas are bounded out with yellow 'Leave Tree Area' tags, red flashers, and blue paint. Individual leave trees are marked with blue bands and two blue butt marks.
<b>Other conditions</b>	Timber sale boundaries are marked with white tags, red flashers, blue paint, and pink flagging.

**Field observations:**

Johnny's Shack is a 7 unit sale with 6 units of VRH and 1 unit of ROW, located in the Dickodochtedar admin unit. The net harvest acres for the sale are 112 acres and has a total net volume of 4315 mbf.

The volume is comprised of 42% Western hemlock (WH), 15% Douglas-fir (DF), 41% Sitka Spruce (SS), and 3% Red alder (RA) with small amounts of Western Red Cedar (RC) throughout the sale. Peeler spec western hemlock was observed throughout the stand. The average WH has a DBH of 16.7" and a bole height of 73', major defects were butt rot. High quality Douglas-fir was observed throughout the stand. The average DF has a DBH of 19.3" and a bole height of 72', major defects were spike knots, double tops and butt rot. The average SS has a DBH of 21.8" and a bole height of 80', major defect were double tops. The average RA has a DBH of 14.6" and a bole height of 74', major defects were double tops and spike knots.

This sale is 100% ground-based harvest. Access to all units is very good.

**Prepared by: Dakota Truitt**

**Title: State Lands Forester/ Timber Cruiser**

**CC:**

TC PSTATS		<b>PROJECT STATISTICS</b>							PAGE	1	
		<b>PROJECT JOHN</b>							DATE	5/16/2019	
TWP	RGE	SC	TRACT	TYPE		ACRES	PLOTS	TREES	CuFt	BdFt	
030	14	25	JOHN	ROW	THR	112.00	60	287	S	W	
030	14W	35	JOHN	U1							
				TREES		ESTIMATED	PERCENT				
		PLOTS	TREES	PER PLOT		TOTAL	SAMPLE				
						TREES	TREES				
TOTAL		60	287	4.8							
CRUISE		31	150	4.8		16,499	.9				
DBH COUNT											
REFOREST											
COUNT		29	137	4.7							
BLANKS											
100 %											
<b>STAND SUMMARY</b>											
SAMPLE		TREES	AVG	BOLE	REL	BASAL	GROSS	NET	GROSS	NET	
TREES		/ACRE	DBH	LEN	DEN	AREA	BF/AC	BF/AC	CF/AC	CF/AC	
WHEMLOCK		56	76.0	16.7	73	28.2	115.0	17,417	16,006	4,329	
S SPRUCE		51	38.6	21.8	80	21.4	100.1	16,825	15,698	4,186	
DOUG FIR		18	23.6	19.3	72	10.9	47.8	6,305	5,707	1,618	
R ALDER		25	9.1	14.6	59	2.8	10.7	1,224	1,115	307	
<b>TOTAL</b>		<i>150</i>	<i>147.3</i>	<i>18.4</i>	<i>74</i>	<i>63.7</i>	<i>273.5</i>	<i>41,771</i>	<i>38,526</i>	<i>10,441</i>	
CONFIDENCE LIMITS OF THE SAMPLE											
68.1 TIMES OUT OF 100 THE VOLUME WILL BE WITHIN THE SAMPLE ERROR											
CL	68.1	COEFF		TREES/ACRE			# OF PLOTS REQ.		INF. POP.		
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10		
WHEMLOCK		125.2	16.2	64	76	88					
S SPRUCE		109.4	14.1	33	39	44					
DOUG FIR		188.3	24.3	18	24	29					
R ALDER		252.3	32.6	6	9	12					
<b>TOTAL</b>		<i>64.8</i>	<i>8.4</i>	<i>135</i>	<i>147</i>	<i>160</i>	<i>168</i>	<i>86</i>	<i>42</i>		
CL	68.1	COEFF		BASAL AREA/ACRE			# OF PLOTS REQ.		INF. POP.		
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10		
WHEMLOCK		105.4	13.6	99	115	131					
S SPRUCE		88.8	11.5	89	100	112					
DOUG FIR		174.4	22.5	37	48	59					
R ALDER		277.6	35.8	7	11	14					
<b>TOTAL</b>		<i>41.3</i>	<i>5.3</i>	<i>259</i>	<i>273</i>	<i>288</i>	<i>68</i>	<i>35</i>	<i>17</i>		
CL	68.1	COEFF		NET BF/ACRE			# OF PLOTS REQ.		INF. POP.		
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10		
WHEMLOCK		110.0	14.2	13,733	16,006	18,278					
S SPRUCE		91.4	11.8	13,845	15,698	17,551					
DOUG FIR		180.1	23.2	4,380	5,707	7,034					
R ALDER		301.4	38.9	681	1,115	1,550					
<b>TOTAL</b>		<i>48.1</i>	<i>6.2</i>	<i>36,133</i>	<i>38,526</i>	<i>40,920</i>	<i>93</i>	<i>47</i>	<i>23</i>		

TC		PSPCSTGR		Species, Sort Grade - Board Foot Volumes (Project)																	
T030 R14W S25 TyROW THRU T030 R14W S35 TyU1				Project:		JOHN											Page		1		
				Acres		112.00											Date		5/16/2019		
																	Time		7:47:48AM		
Spp	S T	So rt	Gr ad	% Net BdFt	Bd. Ft. per Acre			Total Net MBF	Percent of Net Board Foot Volume								Average Log				Logs Per /Acre
					Def%	Gross	Net		Log Scale Dia.				Log Length				Ln Ft	Dia In	Bd Ft	CF/ Lf	
									5-7	8-11	12-15	16+	12-20	21-30	31-35	36-99					
RA	D	3S		42	9.9	524	472	53		14	74	12		88	12	32	12	162	1.25	2.9	
RA	D	4S		46	10.0	570	513	57	39	58	3		96	4	30	8	60	0.62	8.5		
RA	D	UT		12		130	130	15	45	7		49	27	73	16	6	23	0.33	5.7		
<b>RA Totals</b>				3	8.9	1,224	1,115	125	23	33	33	11	3	90	7	26	8	65	0.70	17.2	
SS	D	2S		73	6.8	12,420	11,571	1,296		2	27	71		100	39	16	401	2.63	28.8		
SS	D	3S		21	7.0	3,568	3,318	372	11	89	0		1	8	2	89	35	9	102	0.86	
SS	D	4S		5	4.0	708	679	76	80	20			17	26	13	44	29	6	35	0.41	
SS	D	UT		1		130	130	15	100				65	35			17	5	19	0.28	
<b>SS Totals</b>				41	6.7	16,825	15,698	1,758	7	21	20	53	2	3	1	94	34	10	179	1.42	87.8
WH	D	2S		43	14.4	8,208	7,030	787			67	33		100	39	14	260	1.90	27.1		
WH	D	3S		34	2.6	5,591	5,447	610	30	70			1	99	36	8	90	0.67	60.6		
WH	D	4S		7	5.7	1,068	1,007	113	96	4			6	27	32	35	30	5	35	0.32	
WH	D	UT		6	2.8	1,021	993	111	35		30	35	28	17	55	15	6	33	0.52	30.4	
WH	PL	2S		7		1,116	1,116	125			100			100			34	12	187	1.16	
WH	PL	3S		3		412	412	46		100				100			34	9	94	0.63	
<b>WH Totals</b>				42	8.1	17,417	16,006	1,793	18	27	38	17	2	2	13	83	31	8	102	0.88	157.4
DF	D	2S		47	10.7	3,008	2,685	301			33	67		100	39	15	341	2.27	7.9		
DF	D	3S		34	9.9	2,165	1,952	219	16	84			2	98	36	9	94	0.85	20.9		
DF	D	4S		6	14.5	424	362	41	85	15			7	77	16	26	6	28	0.38	12.9	
DF	D	UT		5		272	272	30	26	74			17	9	74	18	6	35	0.53	7.8	
DF	H	2S		8		436	436	49			100			100			36	13	220	1.16	
<b>DF Totals</b>				15	9.5	6,305	5,707	639	12	33	23	31	2	5	93	31	9	111	1.01	51.4	
<b>Totals</b>					7.8	41,771	38,526	4,315	13	26	28	33	2	5	6	87	32	9	123	1.05	313.8

TC TSTATS				STATISTICS				PAGE	1	
				PROJECT	JOHN			DATE	5/16/2019	
TWP	RGE	SECT	TRACT	TYPE	ACRES	PLOTS	TREES	CuFt	BdFt	
030	14W	35	JOHN	U1	24.00	12	56	S	W	
				TREES	ESTIMATED	PERCENT				
				PER PLOT	TOTAL	SAMPLE				
				TREES	TREES	TREES				
TOTAL		12	56	4.7						
CRUISE		5	21	4.2	4,039		.5			
DBH COUNT										
REFOREST										
COUNT		7	35	5.0						
BLANKS										
100 %										
<b>STAND SUMMARY</b>										
	SAMPLE	TREES	AVG	BOLE	REL	BASAL	GROSS	NET	GROSS	NET
	TREES	/ACRE	DBH	LEN	DEN	AREA	BF/AC	BF/AC	CF/AC	CF/AC
DOUG FIR	12	74.7	17.7	70	30.2	127.0	14,094	12,744	4,015	4,013
S SPRUCE	5	23.7	25.1	75	16.3	81.7	10,130	9,646	3,063	3,063
WHEMLOCK	3	58.3	10.7	57	11.1	36.3	3,866	3,653	896	896
R ALDER	1	11.5	10.3	51	2.1	6.7	461	346	128	128
<b>TOTAL</b>	<b>21</b>	<b>168.3</b>	<b>16.6</b>	<b>65</b>	<b>61.8</b>	<b>251.6</b>	<b>28,551</b>	<b>26,388</b>	<b>8,102</b>	<b>8,100</b>
CONFIDENCE LIMITS OF THE SAMPLE										
68.1 TIMES OUT OF 100 THE VOLUME WILL BE WITHIN THE SAMPLE ERROR										
CL:	68.1 %	COEFF	TREES/ACRE			# OF PLOTS REQ.		INF. POP.		
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10	
DOUG FIR	74.6	22.5		58	75	92				
S SPRUCE	105.5	31.8		16	24	31				
WHEMLOCK	99.0	29.8		41	58	76				
R ALDER	233.5	70.4		3	12	20				
<b>TOTAL</b>	<b>39.2</b>	<b>11.8</b>		<b>148</b>	<b>168</b>	<b>188</b>	<b>67</b>	<b>34</b>	<b>17</b>	
CL:	68.1 %	COEFF	BASAL AREA/ACRE			# OF PLOTS REQ.		INF. POP.		
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10	
DOUG FIR	64.2	19.3		102	127	152				
S SPRUCE	104.4	31.5		56	82	107				
WHEMLOCK	97.7	29.4		26	36	47				
R ALDER	233.5	70.4		2	7	11				
<b>TOTAL</b>	<b>34.2</b>	<b>10.3</b>		<b>226</b>	<b>252</b>	<b>278</b>	<b>51</b>	<b>26</b>	<b>13</b>	
CL:	68.1 %	COEFF	NET BF/ACRE			# OF PLOTS REQ.		INF. POP.		
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10	
DOUG FIR	60.5	18.2		10,419	12,744	15,070				
S SPRUCE	103.4	31.2		6,639	9,646	12,652				
WHEMLOCK	94.2	28.4		2,615	3,653	4,690				
R ALDER	233.5	70.4		102	346	589				
<b>TOTAL</b>	<b>34.8</b>	<b>10.5</b>		<b>23,620</b>	<b>26,388</b>	<b>29,155</b>	<b>53</b>	<b>27</b>	<b>13</b>	

T030 R14W S35 TU1										T030 R14W S35 TU1				
Twp	Rge	Sec	Tract	Type	Acres	Plots	Sample Trees	CuFt	BdFt					
030	14W	35	JOHN	U1	24.00	12	21	S	W					

Spp	So	Gr	% Net BdFt	Bd. Ft. per Acre			Total Net MBF	Percent Net Board Foot Volume								Average Log				Logs Per /Acre	
				Def%	Gross	Net		Log Scale Dia.				Log Length				Ln Ft	Dia In	Bd Ft	CF/ Lf		
								5-7	8-11	12-15	16+	12-20	21-30	31-35	36-99						
DF	D	2S	30	11.1	4,316	3,837	92			68	32					100	38	14	250	1.85	15.4
DF	D	3S	50	9.5	7,089	6,415	154	23	77							100	36	9	91	0.86	70.5
DF	D	4S	11	12.0	1,634	1,438	35	100					81		19		27	5	28	0.33	51.9
DF	D	UT	9		1,055	1,055	25	11	89					11		89	30	8	90	0.84	11.7
<b>DF</b>	<b>Totals</b>		48	9.6	14,094	12,744	306	24	46	21	10			10		90	33	8	85	0.82	149.5
SS	D	2S	82	5.3	8,363	7,917	190			54	46					100	37	15	334	2.68	23.7
SS	D	3S	16		1,611	1,611	39	44	56							100	37	8	81	0.87	19.8
SS	D	4S	2	25.0	156	117	3	100					100				23	7	30	0.59	3.9
<b>SS</b>	<b>Totals</b>		37	4.8	10,130	9,645	231	9	9	44	38			1		99	36	12	203	1.80	47.4
WH	D	3S	60		2,220	2,220	53	100								100	36	6	60	0.42	37.0
WH	D	4S	29	16.7	1,279	1,066	26	100								100	36	6	50	0.37	21.3
WH	D	UT	11		367	367	9	100					100				10	5	6	0.09	58.3
<b>WH</b>	<b>Totals</b>		14	5.5	3,866	3,653	88	100					10			90	23	6	31	0.33	116.6
RA	D	4S	100	25.0	461	346	8	100					100				30	6	30	0.37	11.5
RA	D	UT															11	5		0.00	11.5
<b>RA</b>	<b>Totals</b>		1	25.0	461	346	8	100					100				21	6	15	0.27	23.0
<b>Type Totals</b>				7.6	28,551	26,388	633	30	26	26	18		1	7		92	29	7	78	0.83	336.6

TC TSTATS				STATISTICS				PAGE	1	
				PROJECT	JOHN			DATE	5/16/2019	
TWP	RGE	SECT	TRACT	TYPE	ACRES	PLOTS	TREES	CuFt	BdFt	
030	14W	26	JOHN	U2	31.00	16	65	S	W	
				TREES	ESTIMATED	PERCENT				
				PER PLOT	TOTAL	SAMPLE				
				PLOTS	TREES	TREES	TREES			
TOTAL		16	65	4.1						
CRUISE		7	26	3.7	3,255		.8			
DBH COUNT										
REFOREST										
COUNT		9	39	4.3						
BLANKS										
100 %										
<b>STAND SUMMARY</b>										
	SAMPLE	TREES	AVG	BOLE	REL	BASAL	GROSS	NET	GROSS	NET
	TREES	/ACRE	DBH	LEN	DEN	AREA	BF/AC	BF/AC	CF/AC	CF/AC
WHEMLOCK	11	44.6	19.6	81	21.2	93.8	15,598	13,356	3,662	3,663
S SPRUCE	9	33.1	21.8	70	18.4	85.9	13,117	12,051	3,251	3,252
DOUG FIR	6	27.3	22.3	76	15.7	74.2	11,868	10,753	2,739	2,741
<b>TOTAL</b>	<b>26</b>	<b>105.0</b>	<b>21.1</b>	<b>76</b>	<b>55.3</b>	<b>253.9</b>	<b>40,583</b>	<b>36,160</b>	<b>9,652</b>	<b>9,656</b>
CONFIDENCE LIMITS OF THE SAMPLE										
68.1 TIMES OUT OF 100 THE VOLUME WILL BE WITHIN THE SAMPLE ERROR										
CL:	68.1 %	COEFF	<b>TREES/ACRE</b>				# OF PLOTS REQ.		INF. POP.	
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10	
WHEMLOCK	96.0	24.8		34	45	56				
S SPRUCE	92.6	23.9		25	33	41				
DOUG FIR	130.4	33.7		18	27	36				
<b>TOTAL</b>	<b>33.5</b>	<b>8.6</b>		<b>96</b>	<b>105</b>	<b>114</b>	<b>48</b>	<b>24</b>	<b>12</b>	
CL:	68.1 %	COEFF	<b>BASAL AREA/ACRE</b>				# OF PLOTS REQ.		INF. POP.	
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10	
WHEMLOCK	94.3	24.3		71	94	117				
S SPRUCE	87.6	22.6		67	86	105				
DOUG FIR	127.6	32.9		50	74	99				
<b>TOTAL</b>	<b>22.9</b>	<b>5.9</b>		<b>239</b>	<b>254</b>	<b>269</b>	<b>22</b>	<b>11</b>	<b>6</b>	
CL:	68.1 %	COEFF	<b>NET BF/ACRE</b>				# OF PLOTS REQ.		INF. POP.	
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10	
WHEMLOCK	100.4	25.9		9,895	13,356	16,817				
S SPRUCE	80.7	20.8		9,539	12,051	14,564				
DOUG FIR	130.9	33.8		7,118	10,753	14,388				
<b>TOTAL</b>	<b>26.6</b>	<b>6.9</b>		<b>33,676</b>	<b>36,160</b>	<b>38,644</b>	<b>30</b>	<b>15</b>	<b>8</b>	

T030 R14W S26 TU2										T030 R14W S26 TU2				
Twp	Rge	Sec	Tract	Type	Acres	Plots	Sample Trees	CuFt	BdFt					
030	14W	26	JOHN	U2	31.00	16	26	S	W					

Spp	So	Gr	% Net BdFt	Bd. Ft. per Acre			Total Net MBF	Percent Net Board Foot Volume								Average Log				Logs Per /Acre
								Log Scale Dia.				Log Length				Ln	Dia	Bd	CF/	
								5-7	8-11	12-15	16+	12-20	21-30	31-35	36-99	Ft	In	Ft	Lf	
WH	D	2S	71	18.0	11,610	9,522	295			74	26				100	39	14	236	1.59	40.3
WH	D	3S	26	4.3	3,599	3,445	107	19	81						100	36	8	92	0.74	37.6
WH	D	4S	3		389	389	12	87	13			13	34	53		27	6	28	0.41	13.8
WH	D	UT														7	7		0.00	13.5
<b>WH</b>	<b>Totals</b>		37	14.4	15,598	13,356	414	7	21	53	18	0	1	2	97	32	10	127	1.08	105.2
SS	D	2S	66	4.6	8,357	7,971	247			6	94				100	39	19	562	3.58	14.2
SS	D	3S	28	16.1	4,078	3,421	106		100			3	3		94	35	10	111	0.96	30.9
SS	D	4S	4	4.1	541	519	16	87	13			13	48	40		29	6	30	0.42	17.3
SS	D	UT	2		140	140	4	100				100				17	5	20	0.34	7.0
<b>SS</b>	<b>Totals</b>		33	8.1	13,117	12,051	374	5	29	4	62	2	3	2	93	32	10	174	1.46	69.4
DF	D	2S	62	10.6	7,526	6,731	209			18	82				100	40	16	406	2.56	16.6
DF	D	3S	19	10.7	2,335	2,085	65		100			5			95	34	9	100	0.83	20.8
DF	D	4S	2	26.5	266	195	6		100			46	54			21	8	30	0.77	6.5
DF	D	UT	2		167	167	5	100				100				13	5	9	0.19	19.0
DF	H	2S	15		1,575	1,575	49			100					100	36	13	220	1.16	7.2
<b>DF</b>	<b>Totals</b>		30	9.4	11,868	10,753	333	2	21	26	51	3	1		96	29	10	154	1.36	70.0
<b>Type Totals</b>				10.9	40,583	36,160	1,121	5	24	29	43	2	2	1	95	31	10	148	1.26	244.6

TC TSTATS				STATISTICS				PAGE	1		
				PROJECT JOHN				DATE	5/16/2019		
TWP	RGE	SECT	TRACT	TYPE	ACRES	PLOTS	TREES	CuFt	BdFt		
030	14W	25	JOHN	U3	12.00	7	36	S	W		
				TREES	ESTIMATED	PERCENT					
				PER PLOT	TOTAL	SAMPLE					
				TREES	TREES	TREES					
TOTAL		7	36	5.1							
CRUISE		4	16	4.0	2,287		.7				
DBH COUNT											
REFOREST											
COUNT		3	20	6.7							
BLANKS											
100 %											
STAND SUMMARY											
	SAMPLE	TREES	AVG	BOLE	REL	BASAL	GROSS	NET	GROSS	NET	
	TREES	/ACRE	DBH	LEN	DEN	AREA	BF/AC	BF/AC	CF/AC	CF/AC	
WHEMLOCK	10	116.3	18.0	81	48.4	205.4	30,522	28,853	8,008	8,001	
S SPRUCE	4	56.8	17.8	86	23.3	98.2	19,283	18,189	4,361	4,352	
R ALDER	2	17.5	10.9	52	3.5	11.4	1,149	1,085	283	289	
<b>TOTAL</b>	<i>16</i>	<i>190.6</i>	<i>17.4</i>	<i>80</i>	<i>75.5</i>	<i>315.0</i>	<i>50,954</i>	<i>48,127</i>	<i>12,652</i>	<i>12,643</i>	
CONFIDENCE LIMITS OF THE SAMPLE											
68.1 TIMES OUT OF 100 THE VOLUME WILL BE WITHIN THE SAMPLE ERROR											
CL:	68.1 %	COEFF	TREES/ACRE				# OF PLOTS REQ.		INF. POP.		
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10		
WHEMLOCK	56.0	22.8		90	116	143					
S SPRUCE	114.2	46.5		30	57	83					
R ALDER	179.3	73.0		5	18	30					
<b>TOTAL</b>	<i>54.0</i>	<i>22.0</i>		<i>149</i>	<i>191</i>	<i>233</i>	<i>136</i>	<i>69</i>	<i>34</i>		
CL:	68.1 %	COEFF	BASAL AREA/ACRE				# OF PLOTS REQ.		INF. POP.		
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10		
WHEMLOCK	42.0	17.1		170	205	240					
S SPRUCE	109.3	44.5		54	98	142					
R ALDER	170.8	69.6		3	11	19					
<b>TOTAL</b>	<i>47.7</i>	<i>19.4</i>		<i>254</i>	<i>315</i>	<i>376</i>	<i>106</i>	<i>54</i>	<i>26</i>		
CL:	68.1 %	COEFF	NET BF/ACRE				# OF PLOTS REQ.		INF. POP.		
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10		
WHEMLOCK	41.8	17.0		23,944	28,853	33,762					
S SPRUCE	110.2	44.9		10,025	18,189	26,352					
R ALDER	174.6	71.1		314	1,085	1,856					
<b>TOTAL</b>	<i>52.7</i>	<i>21.5</i>		<i>37,803</i>	<i>48,127</i>	<i>58,450</i>	<i>129</i>	<i>66</i>	<i>32</i>		

<b>T030 R14W S25 TU3</b>										<b>T030 R14W S25 TU3</b>				
<b>Twp</b>	<b>Rge</b>	<b>Sec</b>	<b>Tract</b>	<b>Type</b>	<b>Acres</b>	<b>Plots</b>	<b>Sample Trees</b>	<b>CuFt</b>	<b>BdFt</b>					
<b>030</b>	<b>14W</b>	<b>25</b>	<b>JOHN</b>	<b>U3</b>	<b>12.00</b>	<b>7</b>	<b>16</b>	<b>S</b>	<b>W</b>					

Spp	So	Gr	% Net BdFt	Bd. Ft. per Acre			Total Net MBF	Percent Net Board Foot Volume								Average Log				Logs Per /Acre
								Log Scale Dia.				Log Length				Ln Ft	Dia In	Bd Ft	CF/ Lf	
								5-7	8-11	12-15	16+	12-20	21-30	31-35	36-99					
WH	D	2S	42	10.3	13,503	12,118	145			28	72				100	40	16	377	2.68	32.1
WH	D	3S	41	2.0	12,148	11,901	143	8	92						100	37	9	114	0.84	104.4
WH	D	4S	10	1.3	2,902	2,866	34	96	4			14		67	19	30	5	33	0.30	87.3
WH	D	UT	1		255	255	3	100							100	13	7	20	0.41	12.7
WH	PL	3S	6		1,714	1,714	21		100						100	34	8	70	0.57	24.5
<b>WH</b>	<b>Totals</b>		<b>60</b>	<b>5.5</b>	<b>30,522</b>	<b>28,853</b>	<b>346</b>	<b>14</b>	<b>44</b>	<b>12</b>	<b>30</b>	<b>2</b>		<b>13</b>	<b>85</b>	<b>33</b>	<b>9</b>	<b>111</b>	<b>0.92</b>	<b>261.0</b>
SS	D	2S	56	9.6	11,411	10,317	124			27	73				100	40	15	330	1.86	31.3
SS	D	3S	32		5,758	5,758	69		100						100	36	10	140	0.93	41.1
SS	D	4S	12		2,114	2,114	25	78	22			22		78		31	6	37	0.37	56.8
<b>SS</b>	<b>Totals</b>		<b>38</b>	<b>5.7</b>	<b>19,283</b>	<b>18,189</b>	<b>218</b>	<b>9</b>	<b>34</b>	<b>15</b>	<b>41</b>	<b>3</b>		<b>97</b>		<b>35</b>	<b>9</b>	<b>141</b>	<b>0.97</b>	<b>129.1</b>
RA	D	3S	47	11.1	576	512	6		100						100	40	8	80	0.58	6.4
RA	D	4S	41		445	445	5	100						100		30	6	40	0.33	11.1
RA	D	UT	12		128	128	2	100						100		20	5	20	0.24	6.4
<b>RA</b>	<b>Totals</b>		<b>2</b>	<b>5.6</b>	<b>1,149</b>	<b>1,085</b>	<b>13</b>	<b>53</b>	<b>47</b>			<b>12</b>	<b>41</b>	<b>47</b>		<b>30</b>	<b>6</b>	<b>45</b>	<b>0.40</b>	<b>23.9</b>
<b>Type Totals</b>				<b>5.5</b>	<b>50,954</b>	<b>48,127</b>	<b>578</b>	<b>13</b>	<b>40</b>	<b>13</b>	<b>34</b>	<b>3</b>	<b>1</b>	<b>8</b>	<b>89</b>	<b>34</b>	<b>9</b>	<b>116</b>	<b>0.91</b>	<b>414.1</b>

TC TSTATS				STATISTICS				PAGE	1	
				PROJECT	JOHN			DATE	5/16/2019	
TWP	RGE	SECT	TRACT	TYPE	ACRES	PLOTS	TREES	CuFt	BdFt	
030	14W	25	JOHN	U4	4.70	2	8	S	W	
		PLOTS	TREES	TREES PER PLOT	ESTIMATED TOTAL TREES	PERCENT SAMPLE TREES				
TOTAL		2	8	4.0						
CRUISE		2	8	4.0	551	1.5				
DBH COUNT										
REFOREST COUNT										
BLANKS										
100 %										
STAND SUMMARY										
	SAMPLE TREES	TREES /ACRE	AVG DBH	BOLE LEN	REL DEN	BASAL AREA	GROSS BF/AC	NET BF/AC	GROSS CF/AC	NET CF/AC
S SPRUCE	5	39.0	27.1	105	30.0	156.3	39,582	35,955	8,099	8,104
WHEMLOCK	3	78.3	14.8	80	24.4	93.8	15,772	15,772	3,492	3,492
<b>TOTAL</b>	<b>8</b>	<b>117.3</b>	<b>19.8</b>	<b>89</b>	<b>56.2</b>	<b>250.0</b>	<b>55,354</b>	<b>51,727</b>	<b>11,591</b>	<b>11,596</b>
CONFIDENCE LIMITS OF THE SAMPLE										
68.1 TIMES OUT OF 100 THE VOLUME WILL BE WITHIN THE SAMPLE ERROR										
CL:	68.1 %	COEFF	TREES/ACRE				# OF PLOTS REQ.		INF. POP.	
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10	
S SPRUCE	33.8	31.7		27	39	51				
WHEMLOCK	69.8	65.4		27	78	130				
<b>TOTAL</b>	<b>35.4</b>	<b>33.1</b>		<b>78</b>	<b>117</b>	<b>156</b>	<b>88</b>	<b>45</b>	<b>22</b>	
CL:	68.1 %	COEFF	BASAL AREA/ACRE				# OF PLOTS REQ.		INF. POP.	
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10	
S SPRUCE	28.3	26.5		115	156	198				
WHEMLOCK	47.1	44.2		52	94	135				
<b>TOTAL</b>				<b>250</b>	<b>250</b>	<b>250</b>				
CL:	68.1 %	COEFF	NET BF/ACRE				# OF PLOTS REQ.		INF. POP.	
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10	
S SPRUCE	21.1	19.8		28,830	35,955	43,080				
WHEMLOCK	38.3	35.9		10,107	15,772	21,437				
<b>TOTAL</b>	<b>3.0</b>	<b>2.8</b>		<b>50,267</b>	<b>51,727</b>	<b>53,187</b>	<b>1</b>	<b>0</b>	<b>0</b>	

<b>T030 R14W S25 TU5</b>										<b>T030 R14W S25 TU5</b>				
<b>Twp</b>	<b>Rge</b>	<b>Sec</b>	<b>Tract</b>	<b>Type</b>	<b>Acres</b>	<b>Plots</b>	<b>Sample Trees</b>	<b>CuFt</b>	<b>BdFt</b>					
<b>030</b>	<b>14W</b>	<b>25</b>	<b>JOHN</b>	<b>U4</b>	<b>4.70</b>	<b>2</b>	<b>8</b>	<b>S</b>	<b>W</b>					

Spp	S	So	Gr	%	Bd. Ft. per Acre			Total	Percent Net Board Foot Volume								Average Log				Logs Per /Acre	
									Net BdFt	Def%	Gross	Net	Log Scale Dia.				Log Length					Ln
					5-7	8-11	12-15						16+	12-20	21-30	31-35	36-99	Ft	In	Ft		
SS	D		2S	88	9.9	35,291	31,790	149			13	87			100	40	18	480	2.63	66.2		
SS	D		3S	11	3.2	3,937	3,809	18		100				11	39	50	28	10	98	0.94	39.0	
SS	D		4S	1		355	355	2	100					100		21	7	30	0.46	11.8		
<b>SS</b>	<b>Totals</b>			70	9.2	39,582	35,955	169	1	11	11	77	1	5	94	34	14	307	2.03	117.0		
WH	D		3S	64		10,188	10,188	48	14	86					100	36	9	101	0.65	101.3		
WH	D		4S	9		1,421	1,421	7	100					100		33	5	40	0.29	35.5		
WH	PL		2S	27		4,163	4,163	20		100				100		34	13	210	1.16	19.8		
<b>WH</b>	<b>Totals</b>			30		15,772	15,772	74	18	56	26			35	65	35	8	101	0.64	156.6		
<b>Type Totals</b>					6.6	55,354	51,727	243	6	24	16	54	1	4	11	85	35	11	189	1.22	273.6	

TC TSTATS				STATISTICS				PAGE	1		
				PROJECT	JOHN			DATE	5/16/2019		
TWP	RGE	SECT	TRACT	TYPE	ACRES	PLOTS	TREES	CuFt	BdFt		
030	14W	25	JOHN	U5	23.50	13	63	S	W		
				TREES	ESTIMATED	PERCENT					
				PER PLOT	TOTAL	SAMPLE					
				PLOTS	TREES	TREES	TREES				
TOTAL		13	63	4.8							
CRUISE		7	37	5.3	4,632		.8				
DBH COUNT											
REFOREST											
COUNT		6	26	4.3							
BLANKS											
100 %											
<b>STAND SUMMARY</b>											
	SAMPLE	TREES	AVG	BOLE	REL	BASAL	GROSS	NET	GROSS	NET	
	TREES	/ACRE	DBH	LEN	DEN	AREA	BF/AC	BF/AC	CF/AC	CF/AC	
WHEMLOCK	21	133.9	15.5	67	44.5	175.0	24,734	22,802	6,337	6,339	
S SPRUCE	12	48.2	21.9	83	26.9	125.8	22,008	20,804	5,541	5,538	
R ALDER	4	15.0	17.3	65	5.9	24.6	2,785	2,571	732	733	
<b>TOTAL</b>	<b>37</b>	<b>197.1</b>	<b>17.4</b>	<b>71</b>	<b>78.0</b>	<b>325.5</b>	<b>49,527</b>	<b>46,177</b>	<b>12,609</b>	<b>12,610</b>	
CONFIDENCE LIMITS OF THE SAMPLE											
68.1 TIMES OUT OF 100 THE VOLUME WILL BE WITHIN THE SAMPLE ERROR											
CL:	68.1 %	COEFF	<b>TREES/ACRE</b>				# OF PLOTS REQ.		INF. POP.		
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10		
WHEMLOCK	129.3	37.3		84	134	184					
S SPRUCE	88.9	25.7		36	48	61					
R ALDER	205.3	59.2		6	15	24					
<b>TOTAL</b>	<b>80.8</b>	<b>23.3</b>		<b>151</b>	<b>197</b>	<b>243</b>	<b>283</b>	<b>144</b>	<b>71</b>		
CL:	68.1 %	COEFF	<b>BASAL AREA/ACRE</b>				# OF PLOTS REQ.		INF. POP.		
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10		
WHEMLOCK	100.4	29.0		124	175	226					
S SPRUCE	65.9	19.0		102	126	150					
R ALDER	204.9	59.1		10	25	39					
<b>TOTAL</b>	<b>51.7</b>	<b>14.9</b>		<b>277</b>	<b>325</b>	<b>374</b>	<b>116</b>	<b>59</b>	<b>29</b>		
CL:	68.1 %	COEFF	<b>NET BF/ACRE</b>				# OF PLOTS REQ.		INF. POP.		
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10		
WHEMLOCK	105.0	30.3		15,898	22,802	29,707					
S SPRUCE	65.2	18.8		16,892	20,804	24,715					
R ALDER	205.0	59.1		1,050	2,571	4,092					
<b>TOTAL</b>	<b>56.9</b>	<b>16.4</b>		<b>38,601</b>	<b>46,177</b>	<b>53,753</b>	<b>140</b>	<b>71</b>	<b>35</b>		

T030 R14W S25 TU6										T030 R14W S25 TU6				
Twp	Rge	Sec	Tract	Type	Acres	Plots	Sample Trees	CuFt	BdFt					
030	14W	25	JOHN	U5	23.50	13	37	S	W					

Spp	So	Gr	% Net BdFt	Bd. Ft. per Acre			Total Net MBF	Percent Net Board Foot Volume								Average Log				Logs Per /Acre	
				Def%	Gross	Net		Log Scale Dia.				Log Length				Ln Ft	Dia In	Bd Ft	CF/ Lf		
								5-7	8-11	12-15	16+	12-20	21-30	31-35	36-99						
WH	D	2S	43	12.2	11,351	9,961	234			78	22					100	39	13	229	1.78	43.5
WH	D	3S	35	4.2	8,342	7,988	188	40	60							100	36	8	84	0.63	95.3
WH	D	4S	7	3.5	1,502	1,450	34	96	4				77		23		29	5	31	0.27	46.7
WH	D	UT	5	9.5	1,434	1,298	31	63		37		53		47			20	6	29	0.37	44.3
WH	PL	2S	5		1,015	1,015	24			100						100	34	12	170	1.01	6.0
WH	PL	3S	5		1,090	1,090	26			100						100	34	10	130	0.73	8.4
<b>WH</b>	<b>Totals</b>		49	7.8	24,734	22,802	536	24	26	41	9	3	5	12	80		32	8	93	0.80	244.2
SS	D	2S	75	5.8	16,664	15,698	369		7	23	71					100	39	16	424	2.82	37.1
SS	D	3S	19	5.0	4,126	3,918	92	7	93					16	7	77	35	9	98	0.79	40.1
SS	D	4S	4	3.3	906	876	21	83	17					15	17	68	34	6	42	0.42	20.8
SS	D	UT	2		312	312	7	100				30	70				19	5	20	0.26	15.6
<b>SS</b>	<b>Totals</b>		45	5.5	22,008	20,804	489	6	23	17	53	0	5	2	93		34	10	183	1.44	113.5
RA	D	3S	43	8.1	1,227	1,128	27			100						100	30	13	178	1.45	6.4
RA	D	4S	51	8.1	1,410	1,295	30	14	86							100	30	9	86	0.89	15.0
RA	D	UT	6		148	148	3	100				19	81				21	5	22	0.38	6.8
<b>RA</b>	<b>Totals</b>		6	7.7	2,785	2,571	60	13	43	44		1	99				28	9	91	0.93	28.2
<b>Type Totals</b>				6.8	49,527	46,177	1,085	15	26	30	29	2	10	7	81		32	9	120	1.01	385.9

TC TSTATS				STATISTICS				PAGE	1		
				PROJECT	JOHN			DATE	5/16/2019		
TWP	RGE	SECT	TRACT	TYPE	ACRES	PLOTS	TREES	CuFt	BdFt		
030	14W	25	JOHN	U6	14.50	8	37	S	W		
				TREES	ESTIMATED	PERCENT					
				PER PLOT	TOTAL	SAMPLE					
				TREES	TREES	TREES					
TOTAL		8	37	4.6							
CRUISE		4	20	5.0	1,525		1.3				
DBH COUNT											
REFOREST											
COUNT		4	17	4.3							
BLANKS											
100 %											
<b>STAND SUMMARY</b>											
	SAMPLE	TREES	AVG	BOLE	REL	BASAL	GROSS	NET	GROSS	NET	
	TREES	/ACRE	DBH	LEN	DEN	AREA	BF/AC	BF/AC	CF/AC	CF/AC	
WHEMLOCK	6	56.2	21.6	95	30.8	142.9	24,280	23,039	6,084	6,083	
S SPRUCE	14	49.0	20.2	83	24.2	108.9	18,518	17,406	4,634	4,632	
<b>TOTAL</b>	<b>20</b>	<b>105.2</b>	<b>21.0</b>	<b>90</b>	<b>55.0</b>	<b>251.8</b>	<b>42,798</b>	<b>40,444</b>	<b>10,718</b>	<b>10,715</b>	
CONFIDENCE LIMITS OF THE SAMPLE											
68.1 TIMES OUT OF 100 THE VOLUME WILL BE WITHIN THE SAMPLE ERROR											
CL:	68.1 %	COEFF	<b>TREES/ACRE</b>				# OF PLOTS REQ.		INF. POP.		
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10		
WHEMLOCK	107.6	40.6		33	56	79					
S SPRUCE	142.7	53.8		23	49	75					
<b>TOTAL</b>	<b>54.5</b>	<b>20.6</b>		<b>84</b>	<b>105</b>	<b>127</b>	<b>135</b>	<b>69</b>	<b>34</b>		
CL:	68.1 %	COEFF	<b>BASAL AREA/ACRE</b>				# OF PLOTS REQ.		INF. POP.		
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10		
WHEMLOCK	107.6	40.6		85	143	201					
S SPRUCE	116.5	44.0		61	109	157					
<b>TOTAL</b>	<b>46.1</b>	<b>17.4</b>		<b>208</b>	<b>252</b>	<b>296</b>	<b>97</b>	<b>49</b>	<b>24</b>		
CL:	68.1 %	COEFF	<b>NET BF/ACRE</b>				# OF PLOTS REQ.		INF. POP.		
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10		
WHEMLOCK	107.6	40.6		13,681	23,039	32,396					
S SPRUCE	111.3	42.0		10,096	17,406	24,715					
<b>TOTAL</b>	<b>47.6</b>	<b>18.0</b>		<b>33,182</b>	<b>40,444</b>	<b>47,706</b>	<b>103</b>	<b>53</b>	<b>26</b>		

T030 R14W S25 TU7										T030 R14W S25 TU7				
Twp	Rge	Sec	Tract	Type	Acres	Plots	Sample Trees	CuFt	BdFt					
030	14W	25	JOHN	U6	14.50	8	20	S	W					

Spp	So	Gr	% Net BdFt	Bd. Ft. per Acre			Total Net MBF	Percent Net Board Foot Volume								Average Log				Logs Per /Acre	
								Log Scale Dia.				Log Length				Ln	Dia	Bd	CF/		
								5-7	8-11	12-15	16+	12-20	21-30	31-35	36-99	Ft	In	Ft	Lf		
WH	D	2S	33	13.8	9,009	7,768	113		74	26				100	40	15	299	2.40	26.0		
WH	D	3S	21		4,897	4,897	71	20	80			6		94	35	9	94	0.67	51.9		
WH	D	UT	21		4,744	4,744	69	11		32	57		4	7	89	28	10	179	1.54	26.4	
WH	PL	2S	25		5,629	5,629	82			100				100	34	12	188	1.20	30.0		
<b>WH</b>	<b>Totals</b>		57	5.1	24,280	23,039	334	7	17	56	20		1	1	26	72	34	11	171	1.31	134.4
SS	D	2S	76	6.5	14,276	13,342	193		46	54				100	39	14	310	2.02	43.0		
SS	D	3S	19	3.9	3,366	3,233	47	35	65				3	5	91	36	8	80	0.70	40.4	
SS	D	4S	3	6.7	678	633	9	60	40			49	51		22	7	30	0.38	21.2		
SS	D	UT	2		198	198	3	100				100			14	5	14	0.26	13.7		
<b>SS</b>	<b>Totals</b>		43	6.0	18,518	17,406	252	10	14	36	41		3	2	1	94	32	10	147	1.22	118.4
<b>Type Totals</b>				5.5	42,798	40,444	586	8	15	47	29		2	2	15	81	33	10	160	1.27	252.7

TC TSTATS				STATISTICS				PAGE	1	
				PROJECT	JOHN			DATE	5/16/2019	
TWP	RGE	SECT	TRACT	TYPE	ACRES	PLOTS	TREES	CuFt	BdFt	
030	14W	25	JOHN	U7 ROW	2.30	2	22	S	W	
				TREES	ESTIMATED	PERCENT				
				PER PLOT	TOTAL	SAMPLE				
				PLOTS	TREES	TREES	TREES			
TOTAL		2	22	11.0						
CRUISE		2	22	11.0	210		10.5			
DBH COUNT										
REFOREST										
COUNT										
BLANKS										
100 %										
STAND SUMMARY										
	SAMPLE	TREES	AVG	BOLE	REL	BASAL	GROSS	NET	GROSS	NET
	TREES	/ACRE	DBH	LEN	DEN	AREA	BF/AC	BF/AC	CF/AC	CF/AC
R ALDER	18	78.3	18.0	69	32.6	138.2	20,348	18,783	4,677	4,669
S SPRUCE	2	8.7	35.5	103	10.0	59.8	13,696	10,696	2,924	2,924
WHEMLOCK	2	4.3	13.0	52	1.1	4.0	283	283	96	96
<b>TOTAL</b>	<b>22</b>	<b>91.3</b>	<b>20.1</b>	<b>71</b>	<b>45.0</b>	<b>201.9</b>	<b>34,326</b>	<b>29,761</b>	<b>7,697</b>	<b>7,688</b>
CONFIDENCE LIMITS OF THE SAMPLE										
68.1 TIMES OUT OF 100 THE VOLUME WILL BE WITHIN THE SAMPLE ERROR										
CL:	68.1 %	COEFF	TREES/ACRE				# OF PLOTS REQ.		INF. POP.	
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10	
R ALDER		31.4	29.5	55	78	101				
S SPRUCE		.0	.0	9	9	9				
WHEMLOCK		.0	.0	4	4	4				
<b>TOTAL</b>		<b>26.9</b>	<b>25.3</b>	<b>68</b>	<b>91</b>	<b>114</b>	<b>51</b>	<b>26</b>	<b>13</b>	
CL:	68.1 %	COEFF	BASAL AREA/ACRE				# OF PLOTS REQ.		INF. POP.	
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10	
R ALDER		46.2	43.3	78	138	198				
S SPRUCE		4.0	3.7	58	60	62				
WHEMLOCK		1.1	1.0	4	4	4				
<b>TOTAL</b>		<b>30.4</b>	<b>28.5</b>	<b>144</b>	<b>202</b>	<b>260</b>	<b>65</b>	<b>33</b>	<b>16</b>	
CL:	68.1 %	COEFF	NET BF/ACRE				# OF PLOTS REQ.		INF. POP.	
SD:	1.0	VAR.%	S.E.%	LOW	AVG	HIGH	5	7	10	
R ALDER		58.3	54.6	8,523	18,783	29,042				
S SPRUCE		26.4	24.8	8,044	10,696	13,347				
WHEMLOCK		10.9	10.2	254	283	311				
<b>TOTAL</b>		<b>27.2</b>	<b>25.5</b>	<b>22,181</b>	<b>29,761</b>	<b>37,340</b>	<b>52</b>	<b>26</b>	<b>13</b>	

<b>T030 R14W S25 TROW</b>										<b>T030 R14W S25 TROW</b>				
<b>Twp</b>	<b>Rge</b>	<b>Sec</b>	<b>Tract</b>	<b>Type</b>	<b>Acres</b>	<b>Plots</b>	<b>Sample Trees</b>	<b>CuFt</b>	<b>BdFt</b>					
030	14W	25	JOHN	U7 ROW	2.30	2	22	S	W					

Spp	So	Gr	% Net BdFt	Bd. Ft. per Acre			Total Net MBF	Percent Net Board Foot Volume								Average Log				Logs Per /Acre	
								Log Scale Dia.				Log Length				Ln	Dia	Bd	CF/		
								5-7	8-11	12-15	16+	12-20	21-30	31-35	36-99	Ft	In	Ft	Lf		
RA	D	3S	46	11.8	9,957	8,783	20		6	62	32		100				30	14	202	1.64	43.5
RA	D	4S	31	6.3	6,217	5,826	13	35	51	14			81		19		31	8	71	0.69	82.6
RA	D	UT	23		4,174	4,174	10	16	10		74		19	81			18	7	74	0.75	56.5
<b>RA</b>	<b>Totals</b>		63	7.7	20,348	18,783	43	14	21	34	31		4	90	6		27	9	103	0.96	182.6
SS	D	2S	94	21.8	12,957	10,130	23			12	88			100			40	20	583	3.92	17.4
SS	D	3S	4	18.2	478	391	1			100				100			23	12	90	1.28	4.3
SS	D	4S	2	33.3	261	174	0	100					100				17	10	40	0.89	4.3
<b>SS</b>	<b>Totals</b>		36	21.9	13,696	10,696	25		2	15	83		2	4	95		33	17	410	3.36	26.1
WH	D	3S	92		261	261	1	100						100			36	7	60	0.58	4.3
WH	D	UT	8		22	22	0	100					100				12	5	10	0.20	2.2
<b>WH</b>	<b>Totals</b>		1		283	283	1	100					8		92		28	6	43	0.52	6.5
<b>Type Totals</b>				13.3	34,326	29,761	68	10	14	27	50		3	58	39		27	10	138	1.30	215.2

**Species Summary - Trees, Logs, Tons, CCF, MBF**


T030 R14W S25 TyRO	2.3
T030 R14W S25 TyU3	12.0
T030 R14W S35 TyU1	24.0

**Project JOHN**  
**Acres 112.00**

**Page No 1**  
**Date: 5/16/2019**  
**Time 4:20:29PM**


Species	Total	Total	Total	Net Cubic Ft/		CF/	Total CCF		Total MBF	
	Trees	Logs	Tons	Tree	Log	LF	Gross	Net	Gross	Net
WHEMLOCK	8,516	17,630	15,517	56.94	27.50	0.88	4,849	4,849	1,951	1,793
S SPRUCE	4,324	9,834	12,189	108.40	47.66	1.44	4,688	4,687	1,884	1,758
DOUG FIR	2,639	5,757	5,166	68.69	31.49	1.02	1,813	1,813	706	639
R ALDER	1,020	1,923	947	33.82	17.95	0.70	344	345	137	125
<b>Totals</b>	16,499	35,143	33,819	70.87	33.27	1.06	11,694	11,693	4,678	4,315

Wood Type Species	Total	Total	Total	Net Cubic Ft/		CF/	Total CCF		Total MBF	
	Trees	Logs	Tons	Tree	Log	LF	Gross	Net	Gross	Net
A	1,020	1,923	947	33.82	17.95	0.70	344	345	137	125
B	8,516	17,630	15,517	56.94	27.50	0.88	4,849	4,849	1,951	1,793
D	2,639	5,757	5,166	68.69	31.49	1.02	1,813	1,813	706	639
O	4,324	9,834	12,189	108.40	47.66	1.44	4,688	4,687	1,884	1,758
<b>Totals</b>	16,499	35,143	33,819	70.87	33.27	1.06	11,694	11,693	4,678	4,315



**Cruiser Sample Point Locations**


LAYER NAME:	u1	Township:	T30R14W
POLY ID:	1	Total Sample Points:	12
Acres:	24	Spacing Between Points:	300
		Point Rotation Degrees:	30



Scale 1:3,100


**Legend**

- Sample Points
- Unit
- Public Land Survey Sections
- Contours 40-foot



**Cruiser Sample Point Locations**


LAYER NAME:	u2	Township:	T30R14W
POLY ID:	1	Total Sample Points:	16
Acres:	31	Spacing Between Points:	300
		Point Rotation Degrees:	0



Scale 1:2,700


**Legend**

- Sample Points
- Unit
- Public Land Survey Sections
- Contours 40-foot



**Cruiser Sample Point Locations**


LAYER NAME:	u3	Township:	T30R14W
POLY ID:	1	Total Sample Points:	7
Acres:	12	Spacing Between Points:	300
		Point Rotation Degrees:	0



Scale 1:2,700


**Legend**

- Sample Points
- Unit
- Public Land Survey Sections
- Contours 40-foot





**Cruiser Sample Point Locations**

LAYER NAME:	U4	Township:	T30R14W
POLY ID:	1	Total Sample Points:	2
Acres:	4.7	Spacing Between Points:	325
		Point Rotation Degrees:	0




Scale 1:1,100





**Cruiser Sample Point Locations**


LAYER NAME:	U5	Township:	T30R14W
POLY ID:	1	Total Sample Points:	13
Acres:	23.5	Spacing Between Points:	300
		Point Rotation Degrees:	0



Scale 1:2,400

**Legend**

- Sample Points
- Unit
- Public Land Survey Sections
- Contours 40-foot



**Cruiser Sample Point Locations**

LAYER NAME:	U6	Township:	T30R14W
POLY ID:	1	Total Sample Points:	8
Acres:	14.5	Spacing Between Points:	300
		Point Rotation Degrees:	0



Scale 1:1,600

**Legend**

- Sample Points
- Unit
- Public Land Survey Sections
- Contours 40-foot



**Appeal Information**

You have thirty (30) days to appeal this Decision and any related State Environmental Policy Act determinations to the Pollution Control Hearings Board in writing at the following addresses:

**Physical address: 1111 Israel Rd. SW, Ste 301, Tumwater, WA 98501**

**Mailing address: P.O. BOX 40903, OLYMPIA, WA 98504-0903**

Information regarding the Pollution Control Hearings Board can be found at: <http://www.eluho.wa.gov/>

At the same time you file an appeal with the Pollution Control Hearings Board, also send a copy of the appeal to the Department of Natural Resources' region office and the Office of the Attorney General at the following addresses:

Office of the Attorney General  
Natural Resources Division  
1125 Washington Street SE  
PO Box 40100  
Olympia, WA 98504-0100

And

Department Of Natural Resources  
Olympic Region  
411 Tillicum Lane  
Forks, WA 98331

**Other Applicable Laws**

Operating as described in this application/notification does not ensure compliance with the Endangered Species Act, or other federal, state, or local laws.

**Transfer of Forest Practices Application/Notification (WAC 222-20-010)**

Use the "Notice of Transfer of Approved Forest Practices Application/Notification" form. This form is available at region offices and on the Forest Practices website: <http://www.dnr.wa.gov/businesspermits/forestpractices>. Notify DNR of new Operators within 48 hours.

**Continuing Forest Land Obligations (RCW 76.09.060, RCW 76.09.070, RCW 76.09.390, and WAC 222-20-055)**

Obligations include reforestation, road maintenance and abandonment plans, conversions of forest land to non-forestry use and/or harvest strategies on perennial non-fish habitat (Type Np) waters in Eastern Washington.

Before the sale or transfer of land or perpetual timber rights subject to continuing forest land obligations, the seller must notify the buyer of such an obligation on a form titled "Notice of Continuing Forest Land Obligation". The seller and buyer must both sign the "Notice of Continuing Forest Land Obligation" form and send it to the DNR Region Office for retention. This form is available at DNR region offices.

If the seller fails to notify the buyer about the continuing forest land obligation, the seller must pay the buyer's costs related to continuing forest land obligations, including all legal costs and reasonable attorneys' fees incurred by the buyer in enforcing the continuing forest land obligation against the seller.

Failure by the seller to send the required notice to the DNR at the time of sale will be prima facie evidence in an action by the buyer against the seller for costs related to the continuing forest land obligation prior to sale.

**DNR affidavit of mailing:**

On this day _____,	I placed in the United States mail at _____,	WA,
(date)	(post office location)	
postage paid, a true and accurate copy of this document. Notice of Decision FPA # <u>2616223</u>		
_____ (Printed name)	_____ (Signature)	

STATE OF WASHINGTON  
DEPARTMENT OF NATURAL RESOURCES


JOHNNY'S SHACK TIMBER SALE ROAD PLAN  
CLALLAM COUNTY  
COAST DISTRICT

AGREEMENT NO.: 30-099246

DISTRICT ENGINEER: BILL MEHL

DATE: 10 OCTOBER 2019

DRAWN & COMPILED BY: JED NOWAK



# Johnny's Shack


34 T30R14W


**Legend**


- Spot Patch
- Landing
- Turn-Around
- Ditch Out
- Stream Protection
- Culvert Installation
- Gate
- Construction
- Pre-Haul Maintenance
- Existing
- Harvest Units

N


0 400 800 Feet









# Johnny's Shack








# Decommissioning

34 T30R14W




**Legend**

- Culvert Removal
- Decommissioning
- Existing
- Harvest Units

0 400 800 Feet

N



## SECTION 0 – SCOPE OF PROJECT

### 0-1 ROAD PLAN SCOPE

Clauses in this road plan apply to all road related work, including landings and rock source development, unless otherwise noted.

### 0-3 OPTIONAL ROADS

The specified work on the following roads is not required. Any optional roads built by the Purchaser must meet all the specifications in the road plan.

<u>Road</u>	<u>Stations</u>	<u>Type</u>
D-2090	0+00 – 25+00	Pre-Haul Maintenance
D-2093	0+00 – 14+75	Pre-Haul Maintenance
D-2093.1	0+00 – 2+50	Pre-Haul Maintenance
D-5201	0+00 – 21+25	Pre-Haul Maintenance
D-2900	0+00 – 65+00	Pre-Haul Maintenance
D-2990	0+00 – 32+00	Pre-Haul Maintenance
7+00 SPUR	0+00 – 7+00	Pre-Haul Maintenance
2+50 SPUR	0+00 – 2+50	Pre-Haul Maintenance
D-2980	0+00 – 9+30	Pre-Haul Maintenance
4+00 SPUR	0+00 – 4+00	Construction
1+00 SPUR	0+00 – 1+00	Construction
RY-9009	0+00 – 18+75	Pre-Haul Maintenance
6+90 SPUR	0+00 – 1+20	Pre-Haul Maintenance
6+90 SPUR	1+20 – 6+90	Construction
6+00 SPUR	0+00 – 6+00	Construction
RY-9000.6	0+00 – 2+50	Pre-Haul Maintenance
RY-9000.61	0+00 – 7+00	Pre-Haul Maintenance

### 0-4 CONSTRUCTION

This project includes, but is not limited to the following construction requirements:

<u>Road</u>	<u>Stations</u>	<u>Requirements</u>
4+00 SPUR	0+00 – 4+00	See Below
1+00 SPUR	0+00 – 1+00	See Below
6+90 SPUR	1+20 – 6+90	See Below. Cut slope shall be 1:1 or greater.
6+00 SPUR	0+00 – 6+00	See Below. Cut slope shall be 1:1 or greater.
<b>Total:</b>	<b>16.70 STAs</b>	

Construction includes, but is not limited to:

Clearing, grubbing, right-of-way debris disposal, excavation and/or embankment to subgrade, end hauling material for construction, compacting road surfaces, constructing ditchlines, constructing ditchouts, constructing turnouts and turnarounds, curve widening, acquisition and installation of drainage structures, application of rock, spreading grass seed and hay.

**0-6 PRE-HAUL MAINTENANCE**

This project includes, but is not limited to the following pre-haul maintenance requirements:

<u>Road</u>	<u>Stations</u>	<u>Requirements</u>
D-2090	0+00 – 25+00	Grade and shape road in accordance with Clause 2-5. Compact surface in accordance with Compaction List.
D-2093	0+00 – 14+75	Grade and shape road in accordance with Clause 2-5. Inslope road from 10+00 to 12+50. Construct and/or clean ditches in accordance with Clause 2-7, 4-37, and 4-38. Remove all vegetative material with a minimum loss of rock in accordance with Clause 2-9 and 3-23. Construct ditch outs in accordance with Clause 4-29 and 4-38. Install culvert in accordance with Culvert List. Apply rock in accordance with Rock List. Compact rock in accordance with Compaction List. Follow FPHP requirements in accordance with Clause 1-11 and approved FPHP.
D-2093.1	0+00 – 2+50	Grade and shape road in accordance with Clause 2-5. Remove all vegetative material with a minimum loss of rock in accordance with Clause 2-9 and 3-23. Install culvert in accordance with Culvert List. Apply rock in accordance with Rock List. Compact rock in accordance with Compaction List.
D-5201	0+00 – 21+25	Grade and shape road in accordance with Clause 2-5. Brush road in accordance with Clause 3-1 and Brushing Detail. Remove all vegetative material with a minimum loss of rock in accordance with Clause 2-9 and 3-23. Install culverts in accordance with Culvert List. Apply rock in accordance with Rock List. Compact rock in accordance with Compaction List. Follow FPHP requirements in accordance with Clause 1-11 and approved FPHP.
D-2900	0+00 – 65+00	Grade and shape road in accordance with Clause 2-5. Compact surface in accordance with Compaction List. Brush road in accordance with Clause 3-1 and Brushing Detail.
D-2990	0+00 – 32+00	Grade and shape road in accordance with Clause 2-5. Compact surface in accordance with Compaction List. Brush road in accordance with Clause 3-1 and Brushing Detail.

7+00 SPUR	0+00 – 7+00	Grade and shape road in accordance with Clause 2-5. Construct and/or clean ditches in accordance with Clause 2-7, 4-37, and 4-38. Remove all vegetative material with a minimum loss of rock in accordance with Clause 2-9 and 3-23. Apply rock in accordance with Rock List. Compact rock in accordance with Compaction List.
2+50 SPUR	0+00 – 2+50	Grade and shape road in accordance with Clause 2-5. Construct and/or clean ditches in accordance with Clause 2-7, 4-37, and 4-38. Remove all vegetative material with a minimum loss of rock in accordance with Clause 2-9 and 3-23. Apply rock in accordance with Rock List. Compact rock in accordance with Compaction List.
D-2980	0+00 – 9+30	Grade and shape road in accordance with Clause 2-5. Compact surface in accordance with Compaction List. Brush road in accordance with Clause 3-1 and Brushing Detail. Remove culvert in accordance with Attached Drawings.
RY-9009	0+00 – 18+75	Grade and shape road in accordance with Clause 2-5. Compact surface in accordance with Compaction List.
6+90 SPUR	0+00 – 1+20	Grade and shape road in accordance with Clause 2-5. Construct and/or clean ditches in accordance with Clause 2-7, 4-37, and 4-38. Remove all vegetative material with a minimum loss of rock in accordance with Clause 2-9 and 3-23. Install culvert in accordance with Culvert List. Apply rock in accordance with Rock List. Compact rock in accordance with Compaction List.
RY-9000.6	0+00 – 2+50	Grade and shape road in accordance with Clause 2-5. Compact surface in accordance with Compaction List.
RY-9000.61	0+00 – 7+00	Grade and shape road in accordance with Clause 2-5. Remove all vegetative material with a minimum loss of rock in accordance with Clause 2-9 and 3-23. Install culvert in accordance with Culvert List. Apply rock in accordance with Rock List. Compact rock in accordance with Compaction List.
<b>Total:</b>	<b>208.75 STAs</b>	

Maintenance includes, but is not limited to:

Brushing right-of-way, right-of-way debris disposal, cleaning ditches, constructing ditches, installing additional culverts, widening road segments, constructing headwalls, cleaning culvert inlets and outlets, cross drain culvert replacement, installing erosion

control materials and sediment removal structures, spot rocking, grading and shaping existing road surface and turnouts, constructing additional turnouts, compaction of road surface, application of rock, acquisition and application of grass seed and hay.

**0-7 POST-HAUL MAINTENANCE**

This project includes post-haul road maintenance listed in Clause 9-5 POST-HAUL MAINTENANCE.

**0-9 DECOMMISSIONING**

This project includes, but is not limited to decommissioning listed in Clause 9-20 ROAD DECOMMISSIONING.

**0-13 STRUCTURES**

The Purchaser shall acquire and install all structures. Requirements for these structures are listed in Section 7 Structures.

SECTION 1 – GENERAL

**1-1 ROAD PLAN CHANGES**

If the Purchaser desires a change from this Road Plan including, but not limited to relocation, extension, change in design, or adding roads; a revised road plan shall be submitted, in writing, to the Contract Administrator for consideration. The State must approve the submitted plans before road work begins.

**1-2 UNFORESEEN CONDITIONS**

Quantities established in this road plan are minimum acceptable values. Additional quantities required by the state due to unforeseen conditions, or Purchaser's choice of construction season or techniques will be at the Purchaser's expense. Unforeseen conditions include, but are not limited to, solid subsurface rock, subsurface springs, saturated ground, and unstable soils.

**1-3 ROAD DIMENSIONS**

Unless controlled by construction stakes or design data (plan, profile, and cross-sections), road work shall be performed in accordance with the dimensions shown on the Typical Section Sheet and the specifications within this Road Plan.

**1-5 DESIGN DATA**

Design data is available upon request at the Department of Natural Resources Olympic Region Office in Forks, WA.

**1-6 ORDER OF PRECEDENCE**

Any conflict or inconsistency in this Road Plan shall be resolved by giving the documents precedence in the following order:

1. Addenda.
2. Designs or Plans. On designs and plans, figured dimensions shall take precedence over scaled dimensions.
3. Road Plan Clauses.
4. Typical Section Sheet.
5. Standard Lists.
6. Standard Details.

In case of any ambiguity or dispute over interpreting the Road Plan, the Contract Administrator's or designee's decision will be final.

**1-7 TEMPORARY ROAD CLOSURE**

The Purchaser shall notify the Contract Administrator a minimum of 5 calendar days before the closure of any road. Road work shall not close any road for more than 3 consecutive days.

<u>Road</u>	<u>Number of Allowable Closed Days</u>
RY-9000 Unit 7 ROW	3

**1-8 REPAIR OR REPLACEMENT OF DAMAGED MATERIALS**

The Purchaser is responsible for the repair or replacement of all materials, roadway infrastructure, and road components damaged during roadwork or operation activities. Repairs and replacements shall be directed by the Contract Administrator. Repairs to structural materials will be made according to the manufacturer's recommendation, and shall not begin without written approval from the Contract Administrator.

**1-9 DAMAGED METALLIC COATING**

Any damaged galvanized or aluminized coating on existing or new bridge components, culverts, downspouts, and flumes must be cleaned and treated with a minimum of two coats of zinc rich paint.

**1-10 WSDOT STANDARD SPECIFICATION REFERENCE**

References in this road plan to "WSDOT Standard Specifications" mean the Washington State Department of Transportation's Standard Specifications for Road, Bridge, and Municipal Construction 2018 (M41-10).

**1-11 FPHP REQUIREMENTS**

The following work is subject to requirements under a Forest Practice Hydraulics Project Approval issued by the State of Washington. Temporary fish stream culverts are subject to "Fish Stream Work Provisions" and shall be installed and removed between July 1 and September 30 of the same year.

<u>FPA Crossing Identifier</u>	<u>Road</u>	<u>Stations</u>	<u>Work Type</u>
C1	D-2093	0+90	Temp Fish Culvert Install and Removal
C3	D-5201	11+75	Temp Fish Culvert Install and Removal
C4	D-5201	14+50	Temp Fish Culvert Install and Removal
C7	D-2980	9+30	Culvert Removal

**1-12 SURVEY MONUMENTS**

At no time during construction, reconstruction, or maintenance shall survey monuments, witness trees, or bearing trees be disturbed or damaged. If damaged or disturbed, Purchaser shall hire a licensed land surveyor to repair, replace, and/or reset them.

**1-13 LOGGING DEBRIS**

During right-of-way logging in Unit 7, the RY-9000 shall be kept clear and free of logging debris from harvest operations and truck loading.

## SUBSECTION ROAD MARKING

### 1-15 ROAD MARKING

Road work must be in accordance with the State's marked location. All road work is marked as follows:

- Orange ribbon and paint for construction centerlines.
- Construction stakes for everything else.

### 1-16 CONSTRUCTION STAKES SET BY STATE

Purchaser shall perform work on the following road(s) in accordance with the construction stakes and reference points set in the field for grade and alignment.

<u>Road</u>	<u>Stations</u>	<u>Type</u>
D-2093	0+90	Temp Fish Culvert
D-5201	11+75, 14+50	Temp Fish Culverts
D-2980	9+30	Culvert Removal

### 1-18 REFERENCE POINT DAMAGE

Purchaser shall reset reference points (RPs) that were moved or damaged at any time during construction to their original locations. Excavation and embankment may not proceed on road segments controlled by said RPs until Purchaser resets all moved or damaged RPs.

## SUBSECTION TIMING

### 1-20 COMPLETE BY DATE

Purchaser shall complete pre-haul road work before the start of timber haul.

### 1-21 HAUL APPROVAL

The Purchaser shall not use roads under this Road Plan without written approval from the Contract Administrator.

### 1-22 WORK NOTIFICATIONS

On all roads, the Purchaser shall notify the Contract Administrator a minimum of 3 calendar days before work begins.

### 1-23 ROAD WORK PHASE APPROVAL

Written approval by Contract Administrator needs to be given at these phases of road work:

- Subgrade approval
- Drainage installation
- Subgrade compaction
- Rock application
- Rock compaction

## SUBSECTION RESTRICTIONS

### 1-25 ACTIVITY TIMING RESTRICTION

On the following road(s), the specified activities are not permitted during the listed closure period(s) unless authorized in writing by the Contract Administrator.

<u>Road</u>	<u>Stations</u>	<u>Activity</u>	<u>Closure Period</u>
D-2093	0+00 – 14+75	All	October 1 <sup>st</sup> – June 30 <sup>th</sup>
D-2093.1	0+00 – 2+50	All	October 1 <sup>st</sup> – June 30 <sup>th</sup>
D-5201	11+75 – 21+25	All	October 1 <sup>st</sup> – June 30 <sup>th</sup>
D-2980	9+30	Culvert Removal	October 1 <sup>st</sup> – June 30 <sup>th</sup>

### 1-26 OPERATING DURING CLOSURE PERIOD

If permission is granted to operate during a closure period listed in Clause 1-25 Activity Timing Restriction, the Purchaser shall provide a maintenance plan to include further protection of State resources. The Contract Administrator must approve the maintenance plan in writing, and preventative measures shall be put in place, before operation in the closure period. The Purchaser shall be required to maintain all haul roads at their own expense including those listed in Contract Clause C-060 Designated Road Maintainer. If other operators are using, or desire to use these designated maintainer roads, a joint operating plan shall be developed. All parties shall follow this plan.

### 1-29 SEDIMENT RESTRICTION

Purchaser shall not allow silt-bearing runoff to enter any streams.

### 1-30 CLOSURE TO PREVENT DAMAGE

In accordance with Contract Clause G-220 State Suspends Operation, the Contract Administrator shall suspend road work or hauling of right-of-way timber, forest products, or rock under the following conditions:

- In the opinion of the Contract Administrator excessive road damage or rutting may occur.

Operations must stop unless authority to continue working or hauling is granted, in writing, by the Contract Administrator. In the event that surface or base stability problems persist, the Purchaser will be required to cease operations, or perform corrective maintenance or repairs, subject to specifications within this Road Plan. Before and during any suspension, the Purchaser shall protect the work from damage or deterioration.

### 1-32 BRIDGE AND ASPHALT SURFACE RESTRICTION

The use of metal tracked equipment is not allowed on bridge or asphalt surfaces at any time. If Purchaser must run equipment on bridge or asphalt surfaces, then rubber tired equipment or other methods, as approved in writing by Contract Administrator, shall be used.

If tracked equipment is used on bridge or asphalt surfaces, Purchaser shall immediately cease all road work and hauling operations. Any dirt, rock, or other material tracked or spilled on bridge or asphalt surface(s) shall be removed immediately. Any damage to the

surface(s) shall be repaired at the Purchaser's expense as directed by the Contract Administrator.

**1-33 SNOW PLOWING RESTRICTION**

On all roads, snow plowing shall be permitted only after the execution of a Snow Plowing Agreement, which is available from the Contract Administrator upon request. Purchaser shall request a Snow Plowing Agreement each time plowing occurs. If damage occurs while plowing, further permission to plow may be revoked by the Contract Administrator.

SUBSECTION OTHER INFRASTRUCTURE

**1-40 ROAD APPROACHES TO COUNTY ROADS AND STATE HIGHWAYS**

At existing road approaches to county roads and state highways, any mud, dirt, rock or other material tracked or spilled on the asphalt surface shall be removed immediately by the Purchaser.

If additional damage to the surface, signs, guardrails, etc. occurs then the damage shall be repaired, at the Purchaser's expense, as directed by the Contract Administrator when authorized by the county or WSDOT.

The following county roads and state highways are affected by this sale:

<u>Road Name</u>
HWY 101

**1-41 REQUIREMENTS FOR PAVED ROAD APPROACHES**

Requirements for the paved road approaches:

Purchaser shall build up approaches to allow a smooth grade transition. The top of the rock road surfacing must be kept level with the surface of the paved roads at all times.

SECTION 2 – MAINTENANCE

**2-1 GENERAL ROAD MAINTENANCE**

Purchaser shall maintain all roads used under this contract in accordance with the FOREST ACCESS ROAD MAINTENANCE SPECIFICATIONS for the entire term of this contract. Maintenance is required even during periods of inactivity.

**2-2 ROAD MAINTENANCE – PURCHASER MAINTENANCE**

Purchaser shall perform maintenance on roads listed in Contract Clause C-050 PURCHASER ROAD MAINTENANCE AND REPAIR in accordance with FOREST ACCESS ROAD MAINTENANCE SPECIFICATIONS.

**2-3 ROAD MAINTENANCE – DESIGNATED MAINTAINER**

Purchaser may be required to perform maintenance on roads listed in Contract Clause C-060 DESIGNATED ROAD MAINTAINER as directed by the Contract Administrator. Purchaser shall maintain roads in accordance with FOREST ACCESS ROAD MAINTENANCE SPECIFICATIONS.

**C-060 Designated Roads**

<u>Road</u>	<u>Stations</u>
D-2000	All
D-5200	All
RY-9000	All
Loop Pit Road	All
Thunder Pit Road	All

**2-4 PASSAGE OF LIGHT VEHICLES**

Purchaser shall maintain the following road(s) in a condition that will allow the passage of light administrative vehicles.

<u>Road</u>	<u>Stations</u>
D-2000	All
D-5200	All
RY-9000	All

**2-5 MAINTENANCE GRADING – EXISTING ROAD**

On the following road(s), a grader shall be used to shape the existing surface.

<u>Road</u>	<u>Stations</u>	<u>Requirements</u>
D-2090	0+00 – 25+00	Grade, shape, compact, and remove shoulder and surface vegetation.
D-2093	0+00 – 14+75	Grade, shape, compact, and remove shoulder and surface vegetation. Inslope road from 10+00 to 12+50.
D-2093.1	0+00 – 2+50	Grade, shape, compact, and remove shoulder and surface vegetation.
D-5201	0+00 – 21+25	Grade, shape, compact, and remove shoulder and surface vegetation.
D-2900	0+00 – 65+00	Grade, shape, compact, and remove shoulder and surface vegetation.
D-2990	0+00 – 32+00	Grade, shape, compact, and remove shoulder and surface vegetation.
7+00 SPUR	0+00 – 7+00	Grade, shape, compact, and remove shoulder and surface vegetation.
2+50 SPUR	0+00 – 2+50	Grade, shape, compact, and remove shoulder and surface vegetation.
D-2980	0+00 – 5+50	Grade, shape, compact, and remove shoulder and surface vegetation.
RY-9009	0+00 – 18+75	Grade, shape, compact, and remove shoulder and surface vegetation.
6+90 SPUR	0+00 – 1+20	Grade, shape, compact, and remove shoulder and surface vegetation.

RY-9000.6	0+00 – 2+50	Grade, shape, compact, and remove shoulder and surface vegetation.
RY-9000.61	0+00 – 7+00	Grade, shape, compact, and remove shoulder and surface vegetation.

**2-7 CLEANING DITCHES, HEADWALLS, AND CATCH BASINS**

On the following road(s), Purchaser shall clean and/or construct the ditches, headwalls, and catch basins. Work shall be completed before the start of timber haul and shall be done in accordance with the Typical Section Sheet. Pulling ditch material across the road or mixing in with the road surface will not be allowed. Ditchlines, headwalls, and catch basins shall not encroach into the existing road.

<u>Road</u>	<u>Stations</u>	<u>Left or Right</u>	<u>Comments</u>
D-2093	1+40 – 5+00	Left	Ditching
D-2093	1+40	Left	2x Catch Basins with Silt Fence
D-2093	7+50 – 9+00	Left	Ditching
D-2093	11+00 – 14+00	Left	Ditching
7+00 SPUR	0+00 – 7+00	Left	Ditching
2+50 SPUR	0+00 – 2+50	Right	Ditching
RY-9000.61	0+60	Right	2x Catch Basins with Silt Fence
RY-9000.61	0+60	Left	2x Catch Basins with Silt Fence
6+90 SPUR	0+00 – 1+20	Left	Ditching

**2-8 MAINTAINING EROSION CONTROL STRUCTURES**

On the following road(s), Purchaser shall clean and maintain all erosion control devices. Work shall be completed before the start of timber haul and shall be done in accordance with all pertaining clauses contained in this Road Plan. Excavated material shall be disposed of in accordance with Clause 4-35 through Clause 4-38.

<u>Road</u>	<u>Stations</u>	<u>Work Needed</u>
D-2000	All	As Directed by C/A

**2-9 REMOVING VEGETATIVE MATERIAL**

On the following road(s), Purchaser shall remove all vegetative material, dirt, mud, and other debris on the existing road surface with a minimum loss of rock. Material removed shall be disposed of in accordance with Clause 3-21 through Clause 3-25 and Clause 4-36 through Clause 4-38.

<u>Road</u>	<u>Stations</u>
D-2093	0+00 – 14+75
D-2093.1	0+00 – 2+50
D-5201	6+00 – 21+25
7+00 SPUR	0+00 – 7+00
2+50 SPUR	0+00 – 2+50
RY-9000.61	0+00 – 7+00
6+90 SPUR	0+00 – 1+20

## SECTION 3 – CLEARING, GRUBBING, AND DISPOSAL

### SUBSECTION BRUSHING

#### 3-1 BRUSHING

On the following road(s), vegetative material up to 5 inches in diameter, including limbs, shall be cut as shown on the Brushing Detail. Brushing shall be achieved by mechanical cutting of brush, trees, and branches. Root systems and stumps of cut vegetation shall not be disturbed unless directed by the Contract Administrator.

<u>Road</u>	<u>Stations</u>
D-5201	0+00 – 6+00
D-2900	0+00 – 65+00
D-2990	0+00 – 32+00
D-2980	0+00 – 5+50

#### 3-2 BRUSHING RESTRICTION

Pulling, digging, pushing over, and other non-cutting methods used for vegetation removal shall not be used for brushing. Excavator buckets, log loaders and similar equipment shall not be used for brushing.

#### 3-3 BRUSH REMOVAL

Remove brushing debris from the road surface, ditchlines, and culvert inlets and outlets. Brush should be disposed of so that it will not fall back onto the road prism.

### SUBSECTION CLEARING

#### 3-5 CLEARING

Purchaser shall fall all vegetative material larger than 5 inches DBH or over 15 feet high between the marked right-of-way boundaries or if not marked in the field, between the clearing limits specified on the TYPICAL SECTION SHEET. Clearing must be completed before starting excavation and embankment.

#### 3-7 RIGHT-OF-WAY DECKING

Deck all merchantable right-of-way timber. Decks shall be parallel to the road centerline and placed within the cleared right-of-way. Decks shall be free of dirt, limbs and other right-of-way debris, and removable by standard log loading equipment.

#### 3-8 PROHIBITED DECKING AREAS

Right-of-way timber shall not be decked in the following areas:

- Within the grubbing limits.
- Within 50 feet of any stream.
- In locations that interfere with the construction of the road prism.
- In locations that impede drainage.
- On slopes greater than 40%.
- Against standing trees unless approved by the Contract Administrator.

## SUBSECTION GRUBBING

### 3-10 GRUBBING

Remove all stumps between the grubbing limits specified on the Typical Section Sheet. Those stumps outside the grubbing limits but with undercut roots shall also be removed. Stump removal shall be accomplished using a hydraulic mounted excavator unless authorized, in writing, by the Contract Administrator. Grubbing shall be completed before starting excavation and embankment.

### 3-12 STUMP PLACEMENT

Grubbed stumps shall be placed outside of the clearing limits, as directed by the Contract Administrator and in compliance with all other clauses in this road plan. Stumps shall be positioned upright with root wads in contact with the forest floor and on stable locations.

### 3-13 STUMPS FOR PUNCHEON MATERIAL

On the following road(s), stumps from within the grubbing limits may be overturned and driven flush with the ground surface for use as subgrade puncheon material.

Road	Stations
1+00 SPUR	0+00 – 1+00
6+00 SPUR	0+00 – 6+00

## SUBSECTION ORGANIC DEBRIS

### 3-20 ORGANIC DEBRIS DEFINITION

Organic debris is defined as all vegetative material not eligible for removal by Contract Clauses G-010 Products Sold And Sale Area or G-011 Right To Remove Forest Products And Contract Area, that is larger than one cubic foot in volume within the grubbing Typical Section Sheet.

### 3-21 DISPOSAL COMPLETION

All disposal of organic debris, shall be completed before the application of rock.

### 3-23 PROHIBITED DISPOSAL AREAS

Organic debris shall not be deposited in the following areas:

- Within 5 feet of a cross drain culvert.
- Within 50 feet of a live stream, or wetland.
- On road subgrades road prism excavation and embankment slopes.
- On slopes greater than 45%.
- Within the operational area for cable landings where debris may shift or roll.
- On locations where brush will fall into the ditch or onto the road surface.
- Against standing timber.

### 3-24 BURYING ORGANIC DEBRIS RESTRICTED

Organic debris shall not be buried unless otherwise stated in this Road Plan.

**3-25 SCATTERING ORGANIC DEBRIS**

Organic debris shall be scattered outside of the grubbing limits in accordance with Clause 3-23 unless otherwise detailed in this Road Plan and as directed by the Contract Administrator.

SUBSECTION PILE

**3-31 PILING**

Organic debris shall be piled no closer than 20 feet from standing timber and no higher than 20 feet. Piles shall be free of rock and soil.

SECTION 4 – EXCAVATION

**4-1 EXCAVATOR CONSTRUCTION**

All roads shall be constructed, reconstructed, and maintained using a track mounted hydraulic excavator unless stated otherwise within this Road Plan, or permission to do otherwise is granted in writing by the Contract Administrator.

**4-2 PIONEERING**

Pioneering shall not extend past construction that will be completed during the current construction season. Pioneering shall not extend more than 1000 feet beyond completed construction unless approved in writing by the Contract Administrator. In addition, the following actions shall be taken as pioneering progresses:

- Drainage shall be provided on all uncompleted construction.
- Road pioneering operations shall not undercut the final cut slope or restrict drainage.
- Culverts at live stream crossings shall be installed during pioneering operations prior to embankment.

**4-3 ROAD GRADE AND ALIGNMENT STANDARDS**

The following road grade and alignment standards shall be followed:

- Grade and alignment shall have smooth continuity, without abrupt changes in direction.
- Maximum grade shall not exceed 18 percent favorable and 16 percent adverse.
- Minimum curve radius is 60 feet at centerline.
- Sag vertical curves shall not have a grade change greater than 5% in 100 feet.
- Crest vertical curves shall not have a grade change greater than 4% in 100 feet.

**4-4 SWITCHBACK STANDARDS**

A switchback is defined as a curved segment of road between a beginning and end of the same curve, where the change of traffic travel direction is greater than 90 degrees.

The following standards for switchbacks shall be followed:

- Adverse grades on switchbacks shall not exceed 10%.
- Favorable grades through switchbacks shall not exceed 12%.
- Transition grades entering and leaving switchbacks shall not exceed a 5% grade change.
- Transition grades required to meet switchback grade limitations shall be constructed on the tangents preceding and departing from the switchbacks.

**4-5 CUT SLOPE RATIO**

Unless construction staked or designed excavation slopes shall be constructed no steeper than shown on the following table:

<u>Material Type</u>	<u>Excavation Slope Ratio</u>	<u>Excavation Slope Percent</u>
Common Earth (on side slopes up to 55%)	1:1	100
Common Earth (56% to 70% side slopes)	¾:1	133
Common Earth (on slopes over 70%)	½:1	200
Fractured or loose rock	½:1	200
Hardpan or solid rock	¼:1	400

**4-6 EMBANKMENT SLOPE RATIO**

Unless construction staked or designed embankment slopes shall be constructed no steeper than shown on the following table:

<u>Material Type</u>	<u>Embankment Slope Ratio</u>	<u>Embankment Slope Percent</u>
Sandy Soils	2:1	50
Common Earth and Rounded Gravel	1½:1	67
Angular Rock	1¼:1	80

**4-7 SHAPING CUT AND FILL SLOPE**

Excavation and embankment slopes shall be constructed to a uniform line and left rough for easier revegetation.

**4-8 CURVE WIDENING**

The minimum widening placed on the inside of curves is:

- 6 feet for curves of 50 to 79 feet radius.
- 4 feet for curves of 80 to 100 feet radius.

**4-9 EMBANKMENT WIDENING**

The minimum embankment widening is:

- 2 feet for embankment heights at centerline of 2 to 6 feet.
- 4 feet for embankment heights at centerline of greater than 6 feet.

Embankment widening shall be applied equally to both sides of the road to achieve the required width.

**4-12 FULL BENCH CONSTRUCTION**

Where side slopes exceed 45%, Purchaser shall use full bench construction for the entire subgrade width.

**4-14 BEAVER DAM REMOVAL**

A beaver dam is to be removed during the installation and removal of the temporary culvert at crossing C3. The beaver dam removal must occur in a manner that ensures the gradual, slow release of impounded water. After the water level across the dam equalizes, the dam may be carefully modified or removed in a manner that minimizes the release of accumulated sediments. This will prevent damage to the stream bed and

banks from scour and erosion. Any breach of the beaver dam must not be wider than the downstream channel.

#### SUBSECTION INTERSECTIONS, TURNOUTS AND TURNAROUNDS

##### **4-20 SUBGRADE DIMENSIONS FOR INTERSECTIONS**

On the following road(s), the Purchaser shall construct the subgrade to the dimensions shown on the Intersection Detail.

<u>Road</u>
D-2093
4+00 SPUR
1+00 SPUR
6+00 SPUR

##### **4-21 TURNOUTS**

Turnouts shall be intervisible with maximum of 1,000 feet between turnouts unless shown otherwise on drawings. Locations shall be adjusted to fit the final subgrade alignment and sight distances. Turnout locations shall be subject to written approval by the Contract Administrator.

##### **4-22 TURNAROUNDS**

Turnarounds shall be no larger than 50 feet long and 30 feet wide. Locations shall be subject to written approval by the Contract Administrator.

##### **4-23 SUBGRADE FLARE FOR INTERSECTIONS**

The D-2090/D-2093 intersection shall be constructed/reconstructed to include additional intersection flare.

#### SUBSECTION DITCH CONSTRUCTION

##### **4-25 DITCH CONSTRUCTION AND RECONSTRUCTION**

The Purchaser shall construct ditches into the subgrade as specified on the Typical Section Sheet. Excavated slopes shall be consistent with Clause 4-5 Cut Slope Ratio. Ditches shall be constructed concurrently with construction of the subgrade.

##### **4-27 DITCH WORK – MATERIAL USE PROHIBITED**

On all roads, pulling ditch material across the road or mixing in with the road surface will not be allowed. Excavated material shall be disposed of as specified in Clause 4-36 through Clause 4-38.

##### **4-28 DITCH DRAINAGE**

Ditches must drain to cross-drain culverts or ditchouts.

**4-29 DITCHOUTS**

Ditchouts shall be constructed at locations shown on the list below, and as needed to fit as built conditions. Ditchouts shall be constructed in a manner that diverts ditch water onto the forest floor and shall have excavation backslopes no steeper than a 1:1 ratio. L or R denotes ditchout left or ditchout right heading in.

Road	Stations
D-2093	10+00 DOR, 12+50 DOL

**SUBSECTION WASTE MATERIAL (DIRT)**

**4-35 WASTE MATERIAL DEFINITION**

Waste material is defined as all dirt, rock, mud, or related material that is extraneous or unsuitable for construction material. Waste material, as used in Section 4 EXCAVATION, is not organic debris.

**4-36 DISPOSAL OF WASTE MATERIAL**

Purchaser may sidecast waste material on side slopes up to 45% if the waste material is compacted and free of organic debris. On side slopes greater than 45%, all waste material must be end hauled or pushed to the designated embankment sites and waste areas identified in Clause 4-37 WASTE AREA LOCATION.

**4-38 PROHIBITED WASTE DISPOSAL AREAS**

Waste material shall not be deposited in the following areas:

- Within 5 feet of a cross drain culvert.
- Within 50 feet of a live stream or wetland.
- Within a riparian management zone.
- On side slopes steeper than 45%.
- In locations that interfere with the construction of the road prism.
- In locations that impede drainage.
- Within the operational area for cable landings.
- Against standing timber.

**4-39 WASTE AREA COMPACTION**

Excavated material may be deposited adjacent to the road prism on side slopes up to 45% if the waste material is compacted and free of debris. On side slopes of 45% or more, all excavation shall be end hauled or pushed to designated waste areas. All waste material shall be compacted. The minimum acceptable compaction is achieved by placing embankments in 2 foot or shallower lifts and routing excavation equipment over the entire width of the lifts, with the exception of side hill embankments too narrow to accommodate excavation equipment which may be placed by end-dumping or sidecasting until sufficiently wide to support the equipment.

**SUBSECTION SHAPING**

**4-55 ROAD SHAPING**

The road subgrade and surface shall be shaped as shown on the Typical Section Sheet. The subgrade and surface shape shall ensure runoff in an even, un-concentrated manner, and shall be uniform, firm, and rut-free.

**4-56 DRY WEATHER SHAPING**

At any time of year, the Contract Administrator may require the application of water to facilitate shaping activities. The method of water application is subject to written approval by the Contract Administrator.

**SUBSECTION COMPACTION**

**4-60 FILL COMPACTION**

Purchaser shall compact all embankment and waste material in accordance with the Compaction List by routing equipment over the entire width of each lift. A plate compactor must be used for areas specifically requiring keyed embankment construction, and embankment segments too narrow to accommodate equipment.

**4-61 SUBGRADE COMPACTION**

Purchaser shall compact constructed and reconstructed subgrades in accordance with the Compaction List by routing equipment over the entire width, except ditch. Purchaser shall obtain written approval from the Contract Administrator for subgrade compaction before placement of rock.

**4-62 DRY WEATHER COMPACTION**

At any time of the year, the Contract Administrator may require the application of water to facilitate compaction activities. The method of water application is subject to written approval by the Contract Administrator.

**4-63 EXISTING SURFACE COMPACTION**

Purchaser shall compact maintained road surfaces in accordance with the Compaction List by routing equipment over the entire width.

**4-64 WASTE MATERIAL COMPACTION**

All waste material shall be compacted by running equipment over it or bucket tamping.

**4-65 CULVERT BACKFILL COMPACTION**

Culvert backfills shall be accomplished by using a jumping jack compactor, performing at least 2 passes per lift, in lifts not to exceed 8 inches.

**4-66 COMPACTION BY METHOD**

Compaction shall consist of three complete passes over the entire width of each lift with a vibratory drum roller weighing a minimum of 6,000 pounds at a maximum operating speed of 3 mph. For embankment segments too narrow to accommodate a drum roller, a plate compactor shall be used.

## SECTION 5 – DRAINAGE

### 5-3 PUNCHEON PLACEMENT

On the following road(s), puncheon may be utilized in the subgrade on the following road. Puncheon shall consist of logs of at least 4 inches in diameter and shall be at least 17 feet long.

<u>Road</u>	<u>Stations</u>
1+00 SPUR	0+00 – 1+00
6+90 SPUR	1+20 – 6+90
6+00 SPUR	0+00 – 6+00

### 5-4 PUNCHEON RESTRICTED

At no time shall puncheon be used in the subgrade, unless listed in Clause 5-3 or approved by the Contract Administrator.

## SUBSECTION CULVERTS

### 5-5 CULVERTS

Culverts shall be installed as part of this contract. Culverts shall be installed concurrently with subgrade work and shall be installed before subgrade compaction and rock application. Culvert locations and the minimum requirements for culvert length and diameter are designated on the Culvert List. Culvert, downspout, and flume lengths shall be adjusted to fit as-built conditions and shall not terminate directly on unprotected soil. Culverts shall be new and meet the material specifications in Clauses 10-15 through 10-23.

### 5-6 USED CULVERT MATERIAL

The Purchaser may install used culverts on the following roads. All other roads shall have new culverts installed.

<u>Road</u>	<u>Stations</u>
D-2093	0+90
D-2093.1	0+75
D-5201	11+75, 14+50, 16+00

### 5-7 TEMPORARY STREAM CULVERT INSTALLATION

On the following roads, temporary stream culverts shall be located in the natural channel of the stream. Temporary culverts shall be installed as shown in the Type Ns Np Detail and associated drawings. Temporary culverts shall be removed as directed by the Contract Administrator. Geotextile fabric shall meet the specifications in Clause 10-2 Geotextile For Separation. Temporary fish stream culverts are subject to “Fish Stream Work Provisions” and shall be installed and removed between July 1 and September 30 of the same year.

<u>Road</u>	<u>Stations</u>	<u>Stream Type</u>
D-2093	0+90	F
D-2093.1	0+75	Ns
D-5201	11+75, 14+50	F, F

**5-11 UNUSED MATERIALS STATE PROPERTY**

On required roads, any materials listed on the Culvert List and Rock List that are not installed shall become the property of the State. Purchaser shall stockpile materials as directed by the Contract Administrator.

**5-12 CONTINGENCY CULVERTS**

The following culverts will be supplied by the Purchaser and will be available for installation on any road listed in the TYPICAL SECTION SHEET as directed by the Contract Administrator. If unused, the contingency culvert shall be placed at Loop Pit, or as otherwise directed by the Contract Administrator, prior to sale completion.

<u>Road</u>	<u>Size</u>
As Directed	18" x 30'
By C/A	

**SUBSECTION CULVERT INSTALLATION**

**5-15 CULVERT INSTALLATION**

Installation shall be in accordance with the Typical Cross Drain Culvert Installation Detail, Typical Type Ns Np Culvert Installation Detail, the National Corrugated Metal Pipe Association's "Installation Manual for Corrugated Steel Drainage Structures", and the Corrugated Polyethylene Pipe Association's "Recommended Installation Practices for Corrugated Polyethylene Pipe and Fittings". Corrugated Polyethylene pipe shall be installed in a manner consistent with the manufacturer's recommendations.

**5-16 APPROVAL FOR LARGER CULVERT INSTALLATION**

Installation of culverts 30 inches in diameter and over shall be subject to written approval by the District Engineer or their designee before backfilling.

**5-17 CROSS DRAIN SKEW AND SLOPE**

Cross drains on road grades in excess of 3% shall be skewed at least 30 degrees from perpendicular to the road centerline, except where the cross drain is at the low point in the road. Where the cross drain is at the low point in the road, culverts shall not be skewed. Cross drain culverts shall be installed at a slope steeper than the incoming ditch grade, but not less than 3% or more than 10%.

**5-18 CULVERT DEPTH OF COVER**

Cross drain culverts shall be installed with a depth of cover of not less than 18 inches of compacted depth over the top of the culvert at the shallowest point. Stream crossing culverts shall be installed with a depth of cover specified in the Engineer's design, Type Ns Np Typical Detail Sheet, or to the minimum depth recommended by the culvert manufacturer for the type of cover material over the pipe, whichever is greater.

**SUBSECTION ENERGY DISSIPATERS**

**5-20 ENERGY DISSIPATERS**

Energy dissipaters shall be installed to prevent erosion and are subject to approval by the Contract Administrator. Rock shall weigh at least 10 pounds and be placed by zero-drop-height method. Energy dissipater shall extend a minimum of ¾ foot to each side of the culvert at the outlet and a minimum of 2 feet beyond the outlet.

SUBSECTION CATCH BASINS, HEADWALLS, AND ARMORING

**5-25 CATCH BASINS**

Catch basins shall be constructed to resist erosion. Approximate dimensions are 1-2 feet deep, 1-2 feet wide, and 2-4 feet long.

**5-26 HEADWALLS FOR CROSS DRAIN CULVERTS**

Headwalls shall be constructed in accordance with the Typical Cross Drain Culvert Installation Detail at all cross drain culverts that specify the placement of rock. Rock used for headwalls shall consist of oversize or quarry spall material. Rock shall be placed on shoulders, slopes, and around culvert inlets and outlets. Rock shall not restrict the flow of water into culvert inlets or catch basins. No end dumping of rock is allowed.

**5-27 ARMORING FOR STREAM CROSSING CULVERTS**

At the following culvert(s), rip rap shall be set in place immediately following construction of the embankment. Rock shall be placed on shoulders, slopes, and around culvert inlets and outlets as designated on the Typical Type Ns Np Culvert Installation Detail as directed by the Contract Administrator. Rock shall not restrict the flow of water into culvert inlets or catch basins. Rock shall be set in place by machine. Placement shall be by zero-drop-height method only. No placement by end dumping or dropping of rock shall be allowed.

<u>Road</u>	<u>Stations</u>	<u>Rock Type</u>
D-2093.1	0+75	Oversize
RY-9000.61	0+50	Oversize

SECTION 6 – ROCK AND SURFACING

SUBSECTION ROCK SOURCE

**6-2 ROCK SOURCE ON STATE LAND**

Rock used in accordance with the quantities on the Rock List may be obtained from the following source(s) on state land at no charge to the Purchaser. Use of material from any other source must have prior written approval from the Contract Administrator. If other operators are using, or desire to use, the rock source(s), a joint operating plan shall be developed. All parties shall follow this plan. The Purchaser shall notify the Contract Administrator a minimum of 5 calendar days before starting any operations in the listed locations.

<u>Source</u>	<u>Location</u>	<u>Rock Type</u>
Thunder Pit	T29N R14W Sec. 2	8" Jaw Run, Oversize
Loop Pit	T29N R13W Sec. 3	4" Jaw Run, 1 ½" Minus Crushed, Pit Run

**6-3 ROCK SOURCE STATE LAND, EXISTING STOCKPILE**

Rock used in accordance with the quantities on the Rock List may be obtained from the following existing stockpile(s) on state land at no charge to the Purchaser. Purchaser shall remove no more than quantities listed below, unless authorized by the Contract Administrator.

<u>Source</u>	<u>Location</u>	<u>Quantity (yd<sup>3</sup>)</u>
8" Jaw Run	Thunder Pit	820 yd <sup>3</sup>
4" Jaw Run	Loop Pit	950 yd <sup>3</sup>
1 ½" Minus Crushed	Loop Pit	180 yd <sup>3</sup>

**6-5 ROCK FROM COMMERCIAL SOURCE**

Rock used in accordance with the quantities on the Rock List may be obtained from any commercial source at the Purchaser's expense. Rock sources will be subject to written approval by the Contract Administrator before their use.

**SUBSECTION ROCK SOURCE DEVELOPMENT**

**6-10 ROCK SOURCE DEVELOPMENT PLAN BY STATE**

All rock source development and use shall be in accordance with a written Rock Source Development and Reclamation Plan prepared by the State and included in this Road Plan. Rock source operations shall be conducted as directed by the Contract Administrator and in accordance with the plan. Upon completion of operations, the rock source shall be left in the condition specified in the Rock Source Development and Reclamation Plan, and approved in writing by the Contract Administrator. The Purchaser shall notify the Contract Administrator a minimum of 5 calendar days before starting any operations in the rock source.

**6-12 ROCK SOURCE SPECIFICATIONS**

Rock sources shall be in accordance with the following unless otherwise specified in Rock Source Development and reclamation plan:

- Pit walls shall not be undermined or over-steepened. The maximum slope of the walls shall be consistent with recognized engineering standards for the type of material being excavated in accordance with the following table:

Material	Maximum Slope Ratio (Horiz.:Vert.)	Maximum Slope Percent
Sand	2:1	50
Gravel	1.5:1	67
Common Earth	1:1	100
Fractured Rock	0.5:1	200
Solid Rock	0:1	vertical

- Pit walls shall be maintained in a condition to minimize the possibility of the walls sliding or failing.
- The width of pit benches shall be a minimum of 1.5 times the maximum length of the largest machine used.

- The surface of pit floors and benches shall be uniform and free-draining at a minimum 2% outslope gradient.
- All operations shall be carried out in compliance with all regulations of the Regulations and Standards Applicable to Metal and Nonmetal Mining and Milling Operations (30 CFR) U.S. Department of Labor, Mine Safety and Health Administration and Safety Standards for Construction Work (296-155 WAC), Washington Department of Labor and Industries.
- Block all vehicle access to the top of the pit faces.

**SUBSECTION ROCK GRADATIONS**

**6-29 1 ½-INCH MINUS CRUSHED ROCK**

% Passing 1 ½" square sieve	100%
% Passing 1" square sieve	50 - 85%
% Passing U.S. #4 sieve	30 - 50%
% Passing U.S. #40 sieve	16% maximum
% Passing U.S. #200 sieve	5% maximum

The portion of aggregate retained on the No. 4 sieve shall not contain more than 0.2% organic debris and trash. All percentages are by weight.

**6-36 4-INCH JAW RUN ROCK**

% Passing 4" square sieve	100%
% Passing 2" square sieve	55 - 75%
% Passing U.S. #4 sieve	15 - 45%
% Passing U.S. #200 sieve	5% maximum

The portion of aggregate retained on the No. 4 sieve shall not contain more than 0.2% organic debris and trash. All percentages are by weight.

**6-39 8-INCH JAW RUN ROCK**

% Passing 8" in one dimension	100%
% Passing 3" square sieve	45 - 65%

Rock shall not contain more than 5% organic debris and trash. All percentages are by weight.

**6-50 LIGHT LOOSE RIP RAP**

Rip rap shall consist of angular, hard, sound, and durable stone. It shall be free from segregation, seams, cracks, and other defects. Light loose rip rap shall be free of rock fines, soil, organic debris or other extraneous material, and shall meet the following requirements:

<u>At Least/Not More Than</u>	<u>Weight Range</u>	<u>Size Range</u>
20% / 90%	300 lbs. to 1 ton	12" - 36"

<b>6-52</b>	<b>OVERSIZE</b>	
	% Passing 8" square sieve	100%
	% Passing 4" square sieve	0%

Rock shall not contain more than 5 percent vegetative debris or trash. All percentages are by weight.

#### SUBSECTION ROCK MEASUREMENT

**6-55**    **ROCK APPLICATION MEASURED BY COMPACTED DEPTH**

Measurement of specified rock depths are defined as the compacted depth(s) using the compaction methods required in this Road Plan. Estimated quantities specified in the Rock List are estimated truck yards. Purchaser shall apply adequate amounts of rock to meet the specified rock depths. Specified rock depths are minimum requirements and are not subject to reduction.

#### SUBSECTION ROCK APPLICATION

**6-70**    **APPROVAL BEFORE ROCK APPLICATION**

Subgrade drainage installation including grading and compaction, shall be completed and approved in writing by the Contract Administrator, before rock application.

**6-71**    **ROCK APPLICATION**

Rock shall be applied in accordance with the specifications and quantities shown on the Rock List. Rock shall be spread, shaped, and compacted full-width concurrent with rock hauling operations. Rock shall be compacted in accordance with Compaction List, in lifts not to exceed 6 inches.

**6-72**    **ROCK APPLICATION AFTER HAULING**

Upon completion of all hauling operations, Purchaser shall apply 100 CY of 1 ½" minus crushed rock on the RY-9000. In addition, Purchaser shall apply the remainder of unused miscellaneous rock quantities shown on the Rock List as directed by the Contract Administrator.

**6-73**    **ROCK FOR WIDENED PORTIONS**

Turnarounds, turnouts, and areas with curve widening shall have rock applied to the same depth and specifications as the traveled way.

**6-78**    **ROCK FOR SPOT PATCHING**

Rock for spot patching shall be applied before any grading is done and before any rock lifts are applied. Once applied, spot patches shall be graded into the existing running surface.

### SECTION 7 – STRUCTURES

#### SUBSECTION STREAM CROSSING STRUCTURES GENERAL

**7-5**    **STRUCTURE DEBRIS**

The Purchaser shall ensure that debris from the installation or removal of structures does not enter any stream. Components removed from the existing structures(s) shall be placed at designated site(s), as directed in writing by the Contract Administrator. The

Purchaser is responsible for maintaining a clean jobsite, with all materials stored away from any high water mark or other area presenting a risk of the materials entering a stream. Debris entering any stream shall be removed immediately and placed in the site(s) designated for stockpiling or disposal. The Purchaser is responsible for retrieving all material carried downstream from the jobsite by the stream current.

**7-6 STREAM CROSSING INSTALLATION**

Installation of stream crossing structures shall be in accordance with the manufacturer's requirements, and as directed by the District Engineer or their designee.

**7-7 BANK PROTECTION FOR STREAM CROSSING STRUCTURES**

Bank protection shall be designed and constructed to prevent the undermining of the structure.

SUBSECTION ACCEPTANCE

**7-20 REQUIRED NOTIFICATION AND APPROVAL**

Purchaser shall provide the District engineer or their designee 3 day notification prior to beginning work on any temporary fish pipe work. Purchaser shall receive approval for completed temporary fish pipe installations and removals from the District engineer or their designee.

SUBSECTION GATE CLOSURE

**7-70 GATE CLOSURE**

On the following road(s), Purchaser shall keep gates closed and locked except during periods of haul. All gates that remain open during haul shall be locked or securely fastened in the open position. All gates shall be closed at termination of use.

<u>Road</u>	<u>Station</u>
RY-9009	1+00
Loop Pit	1+00

SECTION 8 – EROSION CONTROL

**8-1 SEDIMENT CONTROL STRUCTURES**

On the following road(s), Purchaser shall install sediment control structures as listed below.

<u>Road</u>	<u>Stations</u>	<u>Comments</u>
D-2093	1+40	2x Catch Basins with Silt Fence Left
RY-9000.61	0+60	2x Catch Basins with Silt Fence Left
RY-9000.61	0+60	2x Catch Basins with Silt Fence Right

**8-2 PROTECTION FOR EXPOSED SOIL**

Purchaser shall furnish and evenly spread a 3-inch layer of straw to all exposed soils at stream culvert installations. Soils shall not be allowed to sit exposed during any rain event.

## SUBSECTION REVEGETATION

### **8-15 REVEGETATION**

Purchaser shall grass seed and hay mulch all exposed soils including, but not limited to, stream culverts, waste areas, sidecast pull back areas, stream crossing removals, bridge installations, and other areas directed by the Contract Administrator. Revegetation of exposed soils shall be accomplished by manual dispersal of grass seed unless otherwise detailed in this Road Plan. Other methods of revegetation must be approved in writing by the Contract Administrator.

### **8-16 REVEGETATION SUPPLY**

All seed, mulch, hay, matting, etc. will be provided by the Purchaser.

### **8-17 REVEGETATION TIMING**

Purchaser shall perform revegetation during the first available opportunity. Soils shall not be allowed to sit exposed for longer than one month without receiving revegetation treatment unless otherwise approved in writing by the Contract Administrator. Soils shall not be allowed to sit exposed during any rain event.

### **8-18 PROTECTION FOR SEED**

Purchaser shall provide a protective cover over the revegetated area. The protective cover may consist of, but not be limited to, such items as dispersed hay mulch 3" thick or jute matting.

### **8-19 ASSURANCE FOR SEEDED AREA**

The Purchaser shall be responsible to ensure a uniform and dense crop of grass. The Purchaser shall reapply the seed and/or mulch in areas that have been damaged through any cause, before approval from the Contract Administrator. The Purchaser shall restore eroded or disturbed areas, clean up and properly dispose of eroded materials, and reapply the seed and/or mulch at no additional cost to the state.

SUBSECTION SEED, FERTILIZER, AND MULCH

**8-25 GRASS SEED**

Purchaser shall evenly spread the seed mixture listed below on all exposed soils at a rate of 60 pounds per acre of exposed soil.

<u>Seed Species</u>	<u>% by Weight</u>
• Perennial Ryegrass	40.00
• Creeping Red Fescue	40.00
• White Dutch Clover	10.00
• Colonial Bentgrass	10.00

Grass seed shall meet the following specifications:

1. Weed seed may not exceed 0.5% by weight.
2. All seed species must have a minimum 90% germination rate, unless otherwise specified.
3. Seed must be certified.
4. Seed must be furnished in standard containers showing the following information:
  - a. Common name of seed
  - b. Net weight
  - c. Percent of purity
  - d. Percentage of germination
  - e. Percentage of weed seed and inert material

SECTION 9 – POST-HAUL ROAD WORK

SUBSECTION STRUCTURES

**9-2 CULVERT REMOVAL FROM LIVE STREAM**

On the following road(s), Purchaser shall remove existing culverts from live streams and leave the resulting channel open with excavation slope and excavated channel width as specified. Excavated material shall be end hauled to an approved waste area designated in Clause 4-37 Waste Area Location. Culvert removal from live streams shall be in accordance with the associated drawings. Temporary fish stream culverts are subject to “Fish Stream Work Provisions” and shall be installed and removed between July 1 and September 30 of the same year.

<u>Road</u>	<u>Stations</u>	<u>Crossing Identifier</u>	<u>Excavated Channel Width</u>	<u>Slope Ratio</u>	<u>Stream Type</u>	<u>Comments</u>
D-2093	0+90	C1	8'	1.5:1	F	See Attached Drawings. Waste in road.
D-2093.1	0+75	C2	2'	1.5:1	Ns	No associated drawings. Waste in road.
D-5201	11+75	C3	10'	1.5:1	F	See Attached Drawings. Waste in road.
D-5201	14+50	C4	10'	1.5:1	F	See Attached Drawings. Waste in road.
D-2980	9+30	C7	10'	1.5:1	F	See Attached Drawings. Waste in road.

**9-3 REMOVAL OF CULVERT MATERIAL FROM STATE LAND**

Culvert material removed from roads becomes the property of the Purchaser and must be removed from state land.

SUBSECTION POST-HAUL MAINTENANCE

**9-5 POST-HAUL MAINTENANCE**

Post-haul maintenance shall be performed in accordance with the Forest Access Road Maintenance Specifications and as specified below.

<u>Road</u>	<u>Stations</u>	<u>Additional Requirements</u>
All	All	Clean culverts, clean ditches, grade road shape and compact as directed by the Contract Administrator. Apply post haul rock as per Clause 6-72.

SUBSECTION POST-HAUL LANDING MAINTENANCE

**9-10 LANDING DRAINAGE**

On all roads, Purchaser shall provide for drainage of the landing surface as approved in writing by the Contract Administrator.

**9-11 LANDING EMBANKMENT**

On all roads, landing embankments shall be sloped to original construction specifications.

SUBSECTION DECOMMISSIONING AND ABANDONMENT

**9-20 ROAD DECOMMISSIONING**

The following road(s) shall be decommissioned by the Purchaser before the termination of this contract.

<u>Road</u>	<u>Stations</u>	<u>Type</u>
D-2093	0+00 – 14+75	Light Decommissioning
D-2093.1	0+00 – 2+50	Light Decommissioning
D-5201	11+75 – 21+25	Light Decommissioning
<b>Total:</b>	<b>26.75 STAs</b>	

**9-22 LIGHT DECOMMISSIONING**

Decommissioning shall consist of:

1. Remove all culverts. Resulting back slopes shall be 1:1 or shallower for cross drains and 1.5:1, or as specified in approved drawings, for all live stream culvert removals. Material removed shall be placed on the roadbed and compacted, with slopes of 2:1 or shallower, or end-hauled to designated waste areas. Culverts removed shall become the property of the Purchaser and removed from State land.
2. Construct non-drivable water bars as directed by the Contract Administrator. On grades in excess of 3%, non-drivable water bars shall be skewed 30 degrees from the perpendicular of the road centerline.
3. Restore all ditchouts to drain water.
4. Repair or construct ditchlines.

5. Remove any berms, except as directed.
6. Restoration of natural stream channels across road prism, as directed by the Contract Administrator.
7. Removing all fill material as approved by the Contract Administrator.
8. All material from fill removals, culvert removals, and bridge removals shall be placed on roadbed and compacted, except that material listed in Clause 4-37.
9. Purchaser shall furnish and apply grass seed to all areas of exposed soil, including but not limited to: water bars, waste piles, and culvert removal sites. Grass seed shall be applied at a rate of 60 pounds per acre.
10. Block road to vehicular traffic using logs, slash, and stumps, as directed by the Contract Administrator.

## SECTION 10 MATERIALS

### SUBSECTION GEOTEXTILES

#### 10-2 GEOTEXTILE FOR SEPARATION

Geotextiles shall meet the following minimum requirements for strength and property qualities, and shall be designed by the manufacturer to be used for separation. Material shall be free of defects, cuts, and tears.

	<u>ASTM Test</u>	<u>Requirements</u>
Type	--	Non-woven
Apparent opening size	D 4751	No. 30 max
Water permittivity	D 4491	0.02 sec <sup>-1</sup>
Grab tensile strength	D 4632	160 lb
Grab tensile elongation	D 4632	>= 50%
Puncture strength	D 6241	310 lb
Tear strength	D 4533	50 lb
Ultraviolet stability	D 4355	50% retained after 500 hours of exposure

**10-6 GEOTEXTILE FOR TEMPORARY SILT FENCE**

Geotextiles shall meet the following minimum requirements for strength and property qualities, and shall be designed by the manufacturer to be used for filtration. Woven slit-film geotextiles will not be allowed. Material shall be free of defects, cuts, and tears.

	<u>ASTM Test</u>	<u>Requirements</u>
Type	--	Unsupported between posts
Apparent opening size	D 4751	No. 30 max., No. 100 min.
Water permittivity	D 4491	0.02 sec <sup>-1</sup>
Grab tensile strength	D 4632	180 lb in machine direction, 100lb in cross-machine direction
Grab tensile elongation	D 4632	30% max. at 180 lb or more
Ultraviolet stability	D 4355	70% retained after 500 hours of exposure

**SUBSECTION CULVERTS****10-15 CORRUGATED STEEL CULVERT**

Metallic coated steel culverts shall meet AASHTO M-36 (ASTM A-760) specifications. Culverts shall be aluminized (aluminum type 2 coated meeting AASHTO M-274).

**10-16 CORRUGATED ALUMINUM CULVERT**

Aluminum culverts shall meet AASHTO M-196 (ASTM A-745) specifications.

**10-17 CORRUGATED PLASTIC CULVERT**

Polyethylene culverts shall meet AASHTO M-294 specifications. Culverts shall be Type S – double walled with a corrugated exterior and smooth interior.

**10-18 CORRUGATED STEEL STRUCTURAL PLATE**

Structural plate culverts shall be galvanized steel meeting AASHTO M-167 (ASTM A-761) specifications.

**10-19 CORRUGATED ALUMINUM STRUCTURAL PLATE**

Structural plate culverts shall be aluminum alloy meeting AASHTO M-219 (ASTM A-746) specifications.

**10-20 FLUME AND DOWNSPOUT**

Downspouts and flumes shall meet the AASHTO specification designated for the culvert. Plastic downspouts and flumes shall be Type S – double walled with a corrugated exterior and smooth interior.

**10-21 METAL BAND**

Metal coupling and end bands shall meet the AASHTO specification designated for the culvert and shall have matching corrugations. On culverts 24 inches and smaller, bands shall have a minimum width of 12 inches. On culverts over 24 inches, bands shall have a minimum width of 24 inches.

**10-22 PLASTIC BAND**

Plastic coupling and end bands shall meet the AASHTO specification designated for the culvert. Only fittings supplied or recommended by the culvert manufacturer shall be

used. Couplings shall be split coupling band. Split coupling bands shall have a minimum of four corrugations, two on each side of the pipe joint.

**10-23 RUBBER CULVERT GASKETS**

Rubber gaskets must be continuous closed cell, synthetic expanded rubber gaskets conforming to the requirements of ASTM D 1056. Rubber gaskets must be used with all corrugated metal pipe coupling bands.


**10-24 GAGE AND CORRUGATION**

Metal culverts shall conform to the following specifications for gage and corrugation as a function of diameter.

<u>Diameter</u>	<u>Gage</u>	<u>Corrugation</u>
18"	16 (0.064")	2 <sup>2</sup> / <sub>3</sub> " X 1/2"
24" to 42"	14 (0.079")	2 <sup>2</sup> / <sub>3</sub> " X 1/2"
48" to 54"	12	3" X 1"
60" +	10	5" X 1"




## ROCK LIST SHEET



1. Rock quantities, subtotals and totals are "truck measure" estimates. Rock shall be applied to at least the depths listed.
2. All depths are compacted depths.
3. Rock slopes shall be 1½ (H) : 1 (V).
4. All rock sources are subject to approval by the Contract Administrator.
5. Pitrun is defined as pitrun or ballast per Line 6. Crushed is defined as any crushed rock from ¼" minus to 4" minus per Line 6. Oversize is defined as oversize, quarry spalls, light loose rip rap, or heavy loose rip rap per Line 6.
6. Rock sources = 1: Loop Pit Run, 2: Loop Pit 1 ½" minus, 3: Loop Pit 4" Jaw Run, 4: Thunder Pit 8" Jaw Run, 5: Thunder Pit Oversize

ROAD NAME	START STATION	END STATION	SUBGRADE WIDTH (ft)	Pitrun SOURCE	Pitrun WIDTH (ft)	Pitrun DEPTH (in)	Pitrun Quantity(yd <sup>3</sup> /sta)	Pitrun SUBTOTAL(yd <sup>3</sup> )	Crushed SOURCE	Crushed WIDTH (ft)	Crushed DEPTH (in)	Crushed Quantity(yd <sup>3</sup> /sta)	Crushed Subtotal(yd <sup>3</sup> )	Oversize/ Rip rap Source	Oversize/Rip Rap Quantity(yd <sup>3</sup> )
<b>D-2093</b>															
Lift	0+00	14+75							3		6	35	520		
Approach	0+05			1				20							
Culvert	0+90								3				20		
Turn-Around	14+75			1				50							
<b>D-2093.1</b>															
Lift	0+00	2+50		1		6	35	90							
Culvert	0+75			1				20						5	5
<b>D-5201</b>															
Lift	6+00	21+25		1		6	35	540							
Culvert	11+75								2				30		
Culvert	14+50								2				30		
Culvert	16+00			1				20						5	2
Turn-Around	21+25			1				50							
<b>D-2980</b>															
Spot Patch	3+00								2				20		
<b>4+00 SPUR</b>															
Lift	0+00	4+00		1		18	110	440							
Culvert	0+10			1				30							
Turn-Around	4+00			1				50							
<b>Totals:</b>								1310/0					80/540		7


## ROCK LIST SHEET CONTINUED



1. Rock quantities, subtotals and totals are "truck measure" estimates. Rock shall be applied to at least the depths listed.
2. All depths are compacted depths.
3. Rock slopes shall be 1½ (H) : 1 (V).
4. All rock sources are subject to approval by the Contract Administrator.
5. Pitrun is defined as pitrun or ballast per Line 6. Crushed is defined as any crushed rock from ¼" minus to 4" minus per Line 6. Oversize is defined as oversize, quarry spalls, light loose rip rap, or heavy loose rip rap per Line 6.
6. Rock sources = 1: Loop Pit Run, 2: Loop Pit 1 ½" minus, 3: Loop Pit 4" Jaw Run, 4: Thunder Pit 8" Jaw Run, 5: Thunder Pit Oversize

ROAD NAME	START STATION	END STATION	SUBGRADE WIDTH (ft)	Pitrun SOURCE	Pitrun WIDTH (ft)	Pitrun DEPTH (in)	Pitrun Quantity(yd <sup>3</sup> /sta)	Pitrun SUBTOTAL(yd <sup>3</sup> )	Crushed SOURCE	Crushed WIDTH (ft)	Crushed DEPTH (in)	Crushed Quantity(yd <sup>3</sup> /sta)	Crushed Subtotal(yd <sup>3</sup> )	Oversize/Rip rap Source	Oversize/Rip Rap Quantity(yd <sup>3</sup> )
<b>1+00 SPUR</b>															
Lift	0+00	1+00		1	12	80	80								
Culvert	0+05			1			30								
<b>6+90 SPUR</b>															
Lift	0+00	1+20		1	6	35	40								
Culvert	0+30			1			20							5	2
Ballast Lift	1+20	6+90		4	12	70	400								
Surface Lift	1+20	6+90							3	6	35	200			
Culvert	2+15			1			50							5	3
Turn-Around	6+90			1			50								
<b>6+00 SPUR</b>															
Ballast Lift	0+00	6+00		4	12	70	420								
Surface Lift	0+00	6+00							3	6	35	210			
Culvert	2+70			1			20							5	2
Culvert	5+00			1			20							5	2
Turn-Around	6+00			1			50								
<b>RY-9000.61</b>															
Lift	0+00	7+00		1	6	35	250								
Culvert	0+50			1			30							5	2
Culvert	1+50			1			20								
Totals:								660/820					0/410		11

## ROCK LIST SHEET CONTINUED




1. Rock quantities, subtotals and totals are "truck measure" estimates. Rock shall be applied to at least the depths listed.
2. All depths are compacted depths.
3. Rock slopes shall be 1½ (H) : 1 (V).
4. All rock sources are subject to approval by the Contract Administrator.
5. Pitrun is defined as pitrun or ballast per Line 6. Crushed is defined as any crushed rock from ¼" minus to 4" minus per Line 6. Oversize is defined as oversize, quarry spalls, light loose rip rap, or heavy loose rip rap per Line 6.
6. Rock sources = 1: Loop Pit Run, 2: Loop Pit 1 ½" minus, 3: Loop Pit 4" Jaw Run, 4: Thunder Pit 8" Jaw Run, 5: Thunder Pit Oversize

ROAD NAME	START STATION	END STATION	SUBGRADE WIDTH (ft)	Pitrun SOURCE	Pitrun WIDTH (ft)	Pitrun DEPTH (in)	Pitrun Quantity(yd <sup>3</sup> /sta)	Pitrun SUBTOTAL(yd <sup>3</sup> )	Crushed SOURCE	Crushed WIDTH (ft)	Crushed DEPTH (in)	Crushed Quantity(yd <sup>3</sup> /sta)	Crushed Subtotal(yd <sup>3</sup> )	Oversize/ Rip Rap Source	Oversize/Rip Rap Quantity(yd <sup>3</sup> )
<b>7+00 SPUR</b>															
Lift	0+00	7+00		1	6	35	250								
Landing	7+00			1			50								
<b>2+50 SPUR</b>															
Lift	0+00	2+50		1	6	35	90								
Landing	2+50			1			50								
<b>Contingency</b>															
Culvert				1			20							5	2
<b>Miscellaneous</b>															
Pit Run				1			100								
Crushed									2				100		
<b>Post-Haul</b>															
RY-9000									2				100		
Totals:								560/0					200/0		2
Grand Total:								2530/820					280/950		20





# TYPICAL INTERSECTION




NOT TO SCALE


## Typical Type Ns, Np Culvert Installation Detail Sheet.

- Water shall be diverted away from the work site before any "in stream" work begins, and shall continue until culvert installation is complete.
- Culvert lay shall match stream gradient up to 5%.
- Flumes longer than 10ft shall be staked on both sides at maximum intervals of 10ft with 6ft heavy duty steel fence posts, and fastened securely to the posts with No. 10 galvanized smooth wire or bolted to the fence posts.
- Rip rap shall be placed using a "zero height drop method", and shall be set in conjunction with the culvert installation.
- Rip rap shall be placed at headwalls, along the fill at the inlet, and at the end off flumes in accordance with this Detail. On culverts with no flume rip rap shall be placed along the fill at the outlet, unless there is stream drop or it is called for in the Road Plan, at which point it will be installed as an energy dissipater at the end of the culvert as specified in this Detail. All rip rap distance to be determined by the Contract Administrator or the District Engineer.
- Backfill compaction shall be achieved using a jumping jack, walk behind vibratory roller, or plate compactor on lifts not to exceed 8in. 3 complete passes per lift is required for compaction. Backfill shall be placed and compacted evenly on both sides of the culvert. Care shall be taken to ensure adequate compaction of backfill material under the haunches of the pipe. Excavation trench width shall be at least culvert diameter plus 3 times the width of the compactor footprint used.

Culvert Minimum Cover		
Diameter	Steel	Plastic
24"	18"	24"
30" - 42"	24"	24"
48" On	36"	36"




**Cross Section View: Flume**





**Plan View: No Dip**

**Cross Section View: No Flume**





**Plan View: Dip**



**Not To Scale**




# BRUSHING DETAIL



- 1) ALL VEGETATION WITHIN THE BRUSHING LIMITS SHALL BE CUT TO WITHIN 8' OF THE GROUND, UNLESS OTHERWISE DIRECTED BY THE CONTRACT ADMINISTRATOR.
- 2) ALL BRUSH, TREES, LIMBS, ETC. SHALL BE REMOVED FROM THE ROAD SURFACE.
- 3) ALL BRUSH, TREES, LIMBS, ETC. THAT MAY RESTRICT THE FLOW OF WATER SHALL BE REMOVED FROM THE DITCH LINE.
- 4) ALL DEBRIS THAT MAY ROLL OR MIGRATE INTO THE DITCH LINE SHALL BE REMOVED.

Loop Pit  
T29N, R13W, Sec. 3  
T30R13W



- Pit Development and Reclamation Plan**
1. Areas to be developed as directed by the Contract Administrator.
  2. Working face height shall not exceed 15 feet.
  3. Boulders shall be maintained along the top of the pit face and along the haul road in the pit at all times as directed by the Contract Administrator.
  4. Suitable drainage shall be maintained at all times.
  5. Rock pit operations, or operation of heavy equipment is not permitted from one hour before official sunrise to two hours after official sunrise, and from one hour before official sunset to one hour after official sunset from April 1 through September 23.

Map Drawn by  
Jed Nowak  
Updated 07/01/2019

**Legend**

	Existing Roads
	Existing Crushed Stockpiles
	1 1/4" Minus Stockpile
	4" minus Jaw Run Stockpile
	Rip Rap
	Pipe Bedding Material
	Pit Floor
	Stripped Area


**Thunder Pit  
T29N, R14W, Sec. 2**

0 50 100 Feet

1:600 (1" = 50')

**Pit Development and Reclamation Plan**

1. Areas to be developed as directed by the Contract Administrator.
2. Waste, Oversize and Riprap shall be placed as directed by the Contract Administrator.
3. Working face height shall not exceed 15 feet.



		SUMMARY - Road Development Costs												
SALE NAME:	Johnny's Shack	CONTRACT#:	30-099246	REGION:	Olympic	DISTRICT: Coast								
LEGAL DESCRIPTION:	T30N R14W													
ROAD NAME:		4+00 SPUR	1+00 SPUR	6+90 SPUR	6+00 SPUR	D-2090	D-2093	D-2093.1	D-5201	D-2900	D-2990	7+00 SPUR	TOTAL:	SHEET #2
ROAD TYPE:		Construction	Construction	Construction	Construction	Prehaul	Prehaul	Prehaul	Prehaul	Prehaul	Prehaul	Prehaul		
NUMBER OF STATIONS:		4.00	1.00	5.70	6.00	25.00	14.75	2.50	21.25	65.00	32.00	7.00	184.20	236.15
SIDE SLOPE:		30%	0%	30%	30%	0%	0%	0%	0%	0%	0%	0%		
CLEARING AND GRUBBING:		\$848	\$127	\$1,209	\$1,272	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$3,456	\$0
ROAD BRUSHING:		\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$108	\$1,170	\$576	\$0	\$1,854	\$99
EXCAVATION AND FILL:		\$1,130	\$113	\$1,610	\$1,695	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$4,548	\$0
ROAD GRADING:		\$0	\$0	\$0	\$0	\$163	\$96	\$16	\$138	\$423	\$208	\$46	\$1,089	\$1,410
DITCH CLEANING/CONSTRUCTION:		\$0	\$0	\$0	\$0	\$0	\$316	\$0	\$0	\$0	\$0	\$0	\$273	\$144
ROCK TOTALS (Cu. Yds.)/ROCK COSTS:		0	0	0	0	0	0	0	0	0	0	0	0	0
Ballast:	3449	3450	520	110	400	420	0	70	110	610	220	0	300	2759
			\$10,036	\$1,810	\$3,248	\$3,431	\$0	\$1,272	\$1,990	\$11,146	\$4,125	\$0	\$5,625	\$42,683
Surface:	1130	1130	0	0	200	210	0	540	0	60	100	0	0	1110
			\$0	\$0	\$3,707	\$3,902	\$0	\$9,681	\$0	\$1,082	\$1,850	\$0	\$0	\$20,222
Oversize:	20	20	0	0	0	0	0	0	0	0	20	0	0	20
			\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$195	\$0	\$0	\$195
CULVERTS AND FULMERS:			\$880	\$880	\$780	\$1,440	\$0	\$780	\$780	\$2,881	\$0	\$0	\$8,422	\$2,012
STRUCTURES:			\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0	\$0
MISC. EXPENSES:			\$23	\$6	\$33	\$35	\$146	\$1,215	\$191	\$1,198	\$380	\$187	\$534	\$3,948
OVERHEAD:			\$1,163	\$264	\$953	\$1,060	\$28	\$1,202	\$268	\$1,490	\$733	\$87	\$583	\$7,830
TOTAL COSTS:			\$14,080	\$3,199	\$11,540	\$12,836	\$337	\$14,562	\$3,245	\$18,042	\$8,875	\$1,059	\$7,060	\$94,835
														\$20,968
COST PER STATION:			\$3,520	\$3,199	\$2,025	\$2,139	\$13	\$987	\$1,298	\$849	\$137	\$33	\$1,009	\$515
														\$89.70
MOBILIZATION:														
														\$7,700
ROAD DEACTIVATION AND ABANDONMENT COSTS:														\$2,128
Pit Work														\$0
NOTE: This appraisal has no allowance for profit and risk.														
Sheet 1 of 3														
Plans to be furnished by:	Jed Nowak													



	10/8/2019	REGION - ROAD COST ESTIMATE - ROAD CLOSURE										
	SALE NAME: Johnny's Shack											
	Total stations Road Closure = 26.75											
I. MISC. ROAD CLOSURE COSTS:												
Road	Stations	Blocking	Waterbaring	Culvert Removal	Ripping	Guard Rail Install	Skidcast Pullback	Bridge Removal	Grass Seeding	Fill Removal	Large Fill Removal	Total
D-2093	14.75	\$80.00	\$80.00	\$40.00	\$165.00	\$153.00	\$75.00	\$1,195.00	\$116.00	\$230.00	\$256.25	\$660.00
D-2093.1	2.50	\$80.00	\$20.00	\$40.00						\$460.00		\$60.00
D-5201	9.50	\$80.00	\$60.00	\$120.00						\$920.00		\$1,180.00
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	\$0.00
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	\$0.00
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	\$0.00
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	\$0.00
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	\$0.00
	26.75	\$160.00	\$160.00	\$200.00	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00	\$1,380.00	\$0.00	\$1,900.00
							Total:	1,900				
VI. GENERAL EXPENSES:												
	Road No.	Road Closure			Overhead & General Exp. Add		12%					\$228
	Standard:	26.75					SHEET TOTAL =					\$2,128
	Stations:			Sheet 3 of 3			Date:	10/8/2019				
By: Jed Nowak												

## FOREST ACCESS ROAD MAINTENANCE SPECIFICATIONS

### Cuts and Fills

- Maintain slope lines to a stable gradient compatible with the cut slope/fill slope ratios. Remove slides from ditches and the roadway. Repair fill-failures in accordance with Clause 4-6 Embankment Slope Ratio, and with material approved by the Contract Administrator. Remove overhanging material from the top of cut slopes.
- Waste material from slides or other sources shall be placed and compacted in stable locations identified in the road plan or approved by the Contract Administrator, so that sediment will not deliver to any streams or wetlands.
- Slide material and debris shall not be mixed into the road surface materials, unless approved by the Contract Administrator.

### Surface

- Grade, shape, and compact the road surface, turnouts, and shoulders to the original shape on the Typical Section Sheet, to provide a smooth, rut-free traveled surface and maintain surface water runoff in an even, unconcentrated manner.
- Blading shall not undercut the backslope or cut into geotextile fabric on the road.
- If required by the Contract Administrator, water shall be applied as necessary to control dust and retain fine surface rock.
- Surface material shall not be bladed off the roadway. Replace surface material when lost or worn away, or as directed by the Contract Administrator.
- Remove shoulder berms, created by grading, to facilitate drainage, except as marked or directed by the Contract Administrator.
- For roads with geotextile fabric: spread surface aggregate to fill in soft spots and wheel ruts (barrel spread) to prevent damage to the geotextile fabric.

### Drainage

- Prevent silt bearing road surface and ditch runoff from delivering sediment to any streams or wetlands.
- Maintain rolling dips and drivable waterbars as needed to keep them functioning as intended.
- Maintain culvert headwalls to a level slightly below the road shoulder with material that will resist erosion. This is to allow for culverts that are overtopped to keep the water in the ditchline.
- Maintain energy dissipaters at culvert outlets with non-erodible material or rock.
- Keep ditches, culverts, and other drainage structures clear of obstructions and functioning as intended.
- Inspect and clean culverts at least monthly, with additional inspections during storms and periods of high runoff. This shall be done even during periods of inactivity.

### Preventative Maintenance


Perform preventative maintenance work to safeguard against storm damage, such as blading to ensure correct runoff, ditch and culvert cleaning, and waterbar maintenance.

### Termination of Use or End of Season

At the conclusion of logging operations, ensure all conditions of these specifications have been met.

## Debris

Remove fallen timber, limbs, and stumps from the slopes, roadway, ditchlines, and culvert inlets.




# Site Plan View

## Crossing C3

### D-5201 STA 11+75

### Temporary Log Fill Culvert



Proposed  
Subgrade  
Edge

Proposed Temporary  
24"x30" Culvert with  
Log Fill at STA 11+75

BMPs to be used as directed  
by Contract Administrator

CL

Existing  
Channel  
Alignment

Flow


Flow

11+00

0+50

12+00



2+00



J. Nowak  
Drawn 6/19/2019  
Revised 10/4/2019

Notes:  
Sec. 26 T30N R14W  
N 48.06973, W 124.45922  
Average BFW of 6'.  
WA DNR  
To be installed and removed between  
July 1 and Sept. 30 of same year.  
See Fish Stream Work Provisions.


Stream Profile View  
Crossing C3  
D-5201 STA 11+75  
Temporary Log Fill Culvert



Notes:  
Sec. 26 T30N R14W  
N 48.06973, W 124.45922  
Average BFW of 6'.  
WA DNR  
To be installed and removed between  
July 1 and Sept. 30 of same year.  
See Fish Stream Work Provisions.

J. Nowak  
Drawn 6/20/2019  
Revised 6/20/2019


# Road Profile View Crossing C3 D-5201 STA 11+75 Temporary Log Fill Culvert



## Notes:


Sec. 26 T30N R14W  
N 48.06973, W 124.45922  
Average BFW of 6'.  
WA DNR

To be installed and removed between  
July 1 and Sept. 30 of same year.  
See Fish Stream Work Provisions.



J. Nowak  
Drawn 6/20/2019  
Revised 6/20/2019

Site Plan View  
Crossing C4  
D-5201 STA 14+50  
Temporary Log Fill Culvert



Proposed Temporary  
24"x30' Culvert with  
Log Fill at STA 14+50

Proposed  
Subgrade  
Edge

2+50

Flow

Existing  
Channel  
Alignment

CL

1+00



Scale: 1"=16'



15+00

Notes:  
Sec. 26 T30N R14W  
N 48.06910, W 124.45844  
Average BFW of 6.1'.  
WA DNR  
To be installed and removed between  
July 1 and Sept. 30 of same year.  
See Fish Stream Work Provisions.



Stream Profile View  
Crossing C4  
D-5201 STA 14+50  
Temporary Log Fill Culvert



Notes:  
Sec. 26 T30N R14W  
N 48.06910, W 124.45844  
Average BFW of 6.1'.  
WA DNR  
To be installed and removed between  
July 1 and Sept. 30 of same year.  
See Fish Stream Work Provisions.

J. Nowak  
Drawn 6/25/2019  
Revised 6/25/2019

# Road Profile View Crossing C4 D-5201 STA 14+50 Temporary Log Fill Culvert



Notes:  
Sec. 26 T30N R14W  
N 48.06910, W 124.45844  
Average BFW of 6.1'.  
WA DNR  
To be installed and removed between  
July 1 and Sept. 30 of same year.  
See Fish Stream Work Provisions.

J. Nowak  
Drawn 6/25/2019  
Revised 6/25/2019




# Site Plan View

## Crossing C1

### D-2093 STA 0+90

### Temporary Log Fill Culvert



Notes:  
124.46987 48.05764  
Sec. 35 T30 R14W  
Channel Bed Width 4.6'  
WA DNR  
To be installed and removed between  
July 1 and Sept. 30 of same year  
See Fish Stream Work Provisions.




Drawn By: T. Kerschner  
Date: 6/20/2019  
Sheet 1 of 3

# Road Profile View

## Crossing C1

### D-2093 STA 0+90

### Temporary Log Fill Culvert



Notes:  
 124.46987 48.05764  
 Sec.35 T30 R14W  
 Channel Bed Width 4.6'  
 WA DNR  
 To be installed and removed between  
 July 1 and Sept. 30 of same year  
 See Fish Stream Work Provisions.




Drawn By: T. Kerschner  
 Date: 6/20/2019  
 Sheet 2 of 3

# Channel Profile View

## Crossing C1

### D-2093 STA 0+90

### Temporary Log Fill Culvert



**Notes:**

124.46987 48.05764

Sec. 35 T30 R14W


Channel Bed Width 4.6'

WA DNR

To be installed and removed between

July 1 and Sept. 30 of same year

See Fish Stream Work Provisions.




Drawn By: T. Kerschner  
Date: 6/20/2019  
Sheet 3 of 3

# Site Plan View

## Crossing C7

### D-2980 STA 9+30

### Culvert Removal



Notes:  
Sec. 25 T30N R14W  
N 48.06744, W 124.43485  
Average BFW of 6.3'  
WA DNR  
To be removed between  
July 1 and Sept. 30.  
See Fish Stream Work Provisions.



J. Nowak  
Drawn 8/29/2019  
Revised 8/29/2019

# Stream Profile View

## Crossing C7

### D-2980 STA 9+30


### Culvert Removal



Notes:  
Sec. 25 T30N R14W  
N 48.06744, W 124.43485  
Average BFW of 6.3'  
WA DNR  
To be removed between  
July 1 and Sept. 30.  
See Fish Stream Work Provisions.

J. Nowak  
Drawn 8/30/2019  
Revised 8/30/2019

# Road Profile View Crossing C7 D-2980 STA 9+30 Culvert Removal



Notes:  
 Sec. 25 T30N R14W  
 N 48.06744, W 124.43485  
 Average BFW of 6.3'  
 WA DNR  
 To be removed between  
 July 1 and Sept. 30.  
 See Fish Stream Work Provisions.

J. Nowak  
 Drawn 8/30/2019  
 Revised 8/30/2019

## FISH STREAM WORK PROVISIONS

1. TIMING LIMITATIONS: The fish culvert project may begin July 1 and shall be completed by September 30.
2. Work shall conform to plans and specifications in the road plan.
3. Prior to the commencement of in-stream work, the Purchaser shall isolate the work area in a manner that fish cannot enter the work area, capture and safely move fish and other fish life from the work area. The Purchaser shall have fish capture and transportation equipment ready and on the job site. Captured fish shall be immediately and safely transferred to free-flowing water downstream of the work area.

### TEMPORARY STREAM FLOW BYPASS

4. All in-stream work shall be conducted in the dry or in isolation from the stream flow by the installation of a bypass flume/pipe or by pumping the flow around the work area, back into the stream below the work area. Waste water pumped from within the work area shall terminate on the forest floor, sufficient distance from the stream to filter sediment prior to entering the stream.
5. The temporary bypass to divert flow around the work area shall be in place prior to initiation of other work in the wetted perimeter.
6. A sandbag revetment or similar device shall be installed at the bypass inlet to divert the entire flow through the bypass.
7. The bypass shall be of sufficient size to pass all flows and debris for the duration of the project.
8. If a pump is used for diverting water from the stream where fish are present, as per RCW 77.57.010 and 77.57.070, the pump intake shall be equipped with a fish guard to prevent passage of fish into the diversion pump. The pump intake shall be screened with 1/8 inch mesh to prevent fish from entering the pump. Velocity through the screened intake shall be less than 0.4 feet per second. Screens shall be maintained to prevent injury or entrapment of juvenile fish.


### WATER QUALITY

9. Extreme care shall be taken to ensure that no petroleum products, hydraulic fluid, chemicals, or any other toxic or deleterious materials are allowed to enter or leach into the stream.

# LOGGING PLAN MAP

SALE NAME: JOHNNY'S SHACK  
 AGREEMENT#: 30-099246  
 TOWNSHIP(S): T30R14W  
 TRUST(S): Capitol Grant (7)

REGION: Olympic Region  
 COUNTY(S): Clallam  
 ELEVATION RGE: 320' - 780'



All State Unless Otherwise Noted


Legend			
~ ~	Sale Boundary Tags		Streams
~ ~ ~	Right of Way Tags		Stream Type 3
~ ~ ~	Right of Way Tags		Stream Type 4
	Existing Roads		Stream Type 5
	Optional Pre-Haul Maintenance		Stream Break
	Landing - Proposed		Contours 40-foot
	Ground-based Harvest		County Boundaries
	Leave Tree Area		Public Land Survey Townships
	Riparian Mgt Zone		Public Land Survey Sections
			DNR Managed Lands



# LOGGING PLAN MAP

**SALE NAME:** JOHNNY'S SHACK  
**AGREEMENT#:** 30-099246  
**TOWNSHIP(S):** T30R14W  
**TRUST(S):** Capitol Grant (7)

**REGION:** Olympic Region  
**COUNTY(S):** Clallam  
**ELEVATION RGE:** 320' - 780'




## Legend

- |                               |                  |                      |                              |
|-------------------------------|------------------|----------------------|------------------------------|
| ~ ~ Sale Boundary Tags        | Streams          | Ground-based Harvest | County Boundaries            |
| Leave Tree Tags               | Stream Type 3    | Leave Tree Area      | Public Land Survey Townships |
| Existing Roads                | Stream Type 5    | Riparian Mgt Zone    | Public Land Survey Sections  |
| Optional Pre-Haul Maintenance | Stream Break     | Forested Wetland     | DNR Managed Lands            |
| Landing - Proposed            | Open Water       | Wetland Mgt Zone     |                              |
|                               | Survey Monument  |                      |                              |
|                               | Contours 40-foot |                      |                              |

# LOGGING PLAN MAP

**SALE NAME:** JOHNNY'S SHACK  
**AGREEMENT#:** 30-099246  
**TOWNSHIP(S):** T30R14W  
**TRUST(S):** Capitol Grant (7)

**REGION:** Olympic Region  
**COUNTY(S):** Clallam  
**ELEVATION RGE:** 320' - 780'



All State Unless Otherwise Noted


## Legend

- |                               |                  |                      |                              |
|-------------------------------|------------------|----------------------|------------------------------|
| ~ ~ Sale Boundary Tags        | Streams          | Ground-based Harvest | County Boundaries            |
| Leave Tree Tags               | Stream Type 3    | Leave Tree Area      | Public Land Survey Townships |
| ~ ~ Right of Way Tags         | Stream Type 5    | Riparian Mgt Zone    | Public Land Survey Sections  |
| Existing Roads                | Stream Break     | Forested Wetland     | DNR Managed Lands            |
| Optional Pre-Haul Maintenance | Survey Monument  |                      |                              |
| Optional Construction         | Contours 40-foot |                      |                              |
| Landing - Proposed            |                  |                      |                              |

# LOGGING PLAN MAP

SALE NAME: JOHNNY'S SHACK  
 AGREEMENT#: 30-099246  
 TOWNSHIP(S): T30R14W  
 TRUST(S): Capitol Grant (7)

REGION: Olympic Region  
 COUNTY(S): Clallam  
 ELEVATION RGE: 320' - 780'



All State Unless Otherwise Noted

## Legend

- |                               |                  |                      |                              |
|-------------------------------|------------------|----------------------|------------------------------|
| ~ ~ Sale Boundary Tags        | Streams          | Ground-based Harvest | County Boundaries            |
| ~ ~ Leave Tree Tags           | 3 Stream Type 3  | Leave Tree Area      | Public Land Survey Townships |
| ~ ~ Right of Way Tags         | 4 Stream Type 4  | Riparian Mgt Zone    | Public Land Survey Sections  |
| Existing Roads                | 5 Stream Type 5  | Forested Wetland     | DNR Managed Lands            |
| Optional Pre-Haul Maintenance | * Stream Break   | Wetland Mgt Zone     |                              |
| Optional Construction         | Survey Monument  |                      |                              |
| Gate                          | Contours 40-foot |                      |                              |
| Landing - Proposed            |                  |                      |                              |

